

6/11/15

CURRENT CONDITION

PULIS 12-8

API 05-001-08192

LOC'N SESE SEC 12, 1568W

KB 11' KB @ 5/60'

8⁵/₈" 24# @ 250' CMT w/180 SX

SLEEVE @ 1,214'

Fox Hills
@ 635-1,169'

2³/₈" TBG @ 5,030'

00 SX PERF 5,011-5,015 (4 JSPF)
00 SX PERF 5,030-5,038 (4 JSPF)
00 SX PERF 5,044-5,073 (4 JSPF)

PSTD @ 5,113'

TD @ 5,170'

4¹/₂" 10.5# @ 5,165' CMT w/300 SX
J-55

7/11/15

PROPOSED

PULIS 12-8

25 SX CMT PLUG
120' TO SURFACE

4 1/2" CSG
PULLED FROM
70'

API 05-001-08192
LOC'N SESE SEC 12, 1568 W
KB 11' KB @ 5160'

8 5/8" 24# @ 250' CMT w/180 SX

SLEEVE @ 1,214'

Fox Hills

635-1,169'

2 3/8" TBG @ 5,030'



CIBP @ 4400' CAP w/2 SX CMT

SX PERF 5,011-5,015 (4 JSPF)

SX PERF 5,030-5,038 (4 JSPF)

SX PERF 5,094-5,093 (4 JSPF)

PSTO @ 5,113'

TD @ 5,170'

4 1/2" 10.5# @ 5,165' CMT w/300 SX
J-55