

Cathedral Energy Services

Planning Report

Database:	USA EDM 5000 Multi Users DB	Local Co-ordinate Reference:	Well Morgan Hills 1D-7H-A168
Company:	Crestone Peak Resources	TVD Reference:	23' KB @ 5048.70usft (ENS 140)
Project:	DJ BASIN	MD Reference:	23' KB @ 5048.70usft (ENS 140)
Site:	S7-T1N-R68W (Woolley-Sosa/Becky/Morgan Hills)	North Reference:	True
Well:	Morgan Hills 1D-7H-A168	Survey Calculation Method:	Minimum Curvature
Wellbore:	HZ		
Design:	PLAN #4		

Project	DJ BASIN		
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	Colorado Northern Zone		

Site		S7-T1N-R68W (Woolley-Sosa/Becky/Morgan Hills)			
Site Position:		Northing:	1,265,216.88 usft	Latitude:	40.060530
From:	Lat/Long	Easting:	3,126,133.02 usft	Longitude:	-105.049370
Position Uncertainty:	0.00 usft	Slot Radius:	13-3/16 "	Grid Convergence:	0.29 °

Well	Morgan Hills 1D-7H-A168					
Well Position	+N/-S	0.00 usft	Northing:	1,269,405.67 usft	Latitude:	40.071987
	+E/-W	0.00 usft	Easting:	3,129,094.22 usft	Longitude:	-105.038713
Position Uncertainty		0.00 usft	Wellhead Elevation:	0.00 usft	Ground Level:	5,025.70 usft

Wellbore	HZ				
Magnetics	Model Name	Sample Date	Declination	Dip Angle	Field Strength
			(°)	(°)	(nT)
	IGRF2010	7/7/2014	8.57	66.64	52,606

Design	PLAN #4			
Audit Notes:				
Version:	Phase:	PLAN	Tie On Depth:	0.00
Vertical Section:	Depth From (TVD)	+N/-S	+E/-W	Direction
	(usft)	(usft)	(usft)	(°)
	0.00	0.00	0.00	180.00

Plan Sections										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
350.00	0.00	0.00	350.00	0.00	0.00	0.00	0.00	0.00	0.00	
1,256.83	9.07	290.57	1,253.05	25.16	-67.05	1.00	1.00	0.00	290.57	
6,853.07	9.07	290.57	6,779.35	335.05	-892.85	0.00	0.00	0.00	0.00	
8,018.36	89.90	179.00	7,528.86	-380.54	-991.43	8.00	6.94	-9.57	-111.34	
11,538.36	89.90	179.00	7,535.00	-3,900.00	-930.00	0.00	0.00	0.00	0.00	MH 1D-7H-A168 TGT
11,663.31	89.92	180.25	7,535.19	-4,024.95	-929.18	1.00	0.02	1.00	88.95	
17,461.82	89.92	180.25	7,543.00	-9,823.40	-954.41	0.00	0.00	0.00	0.00	MH 1D-7H-A168 PBH

Cathedral Energy Services

Planning Report

Database:	USA EDM 5000 Multi Users DB	Local Co-ordinate Reference:	Well Morgan Hills 1D-7H-A168
Company:	Crestone Peak Resources	TVD Reference:	23' KB @ 5048.70usft (ENS 140)
Project:	DJ BASIN	MD Reference:	23' KB @ 5048.70usft (ENS 140)
Site:	S7-T1N-R68W (Woolley-Sosa/Becky/Morgan Hills)	North Reference:	True
Well:	Morgan Hills 1D-7H-A168	Survey Calculation Method:	Minimum Curvature
Wellbore:	HZ		
Design:	PLAN #4		

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100u)	Comments / Formations
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
100.00	0.00	0.00	100.00	0.00	0.00	0.00	0.00	0.00	
200.00	0.00	0.00	200.00	0.00	0.00	0.00	0.00	0.00	
300.00	0.00	0.00	300.00	0.00	0.00	0.00	0.00	0.00	
350.00	0.00	0.00	350.00	0.00	0.00	0.00	0.00	0.00	KOP @ 350'
400.00	0.50	290.57	400.00	0.08	-0.20	-0.08	1.00	1.00	
500.00	1.50	290.57	499.98	0.69	-1.84	-0.69	1.00	1.00	
600.00	2.50	290.57	599.92	1.92	-5.11	-1.92	1.00	1.00	
700.00	3.50	290.57	699.78	3.75	-10.01	-3.75	1.00	1.00	
800.00	4.50	290.57	799.54	6.21	-16.54	-6.21	1.00	1.00	
900.00	5.50	290.57	899.16	9.27	-24.70	-9.27	1.00	1.00	
1,000.00	6.50	290.57	998.61	12.94	-34.48	-12.94	1.00	1.00	
1,000.09	6.50	290.57	998.70	12.94	-34.49	-12.94	0.00	0.00	Fox Hills - BASE
1,100.00	7.50	290.57	1,097.86	17.22	-45.89	-17.22	1.00	1.00	
1,200.00	8.50	290.57	1,196.89	22.11	-58.92	-22.11	1.00	1.00	
1,256.83	9.07	290.57	1,253.05	25.16	-67.05	-25.16	1.00	1.00	EOB; INC=9°
1,300.00	9.07	290.57	1,295.68	27.55	-73.42	-27.55	0.00	0.00	
1,400.00	9.07	290.57	1,394.43	33.09	-88.17	-33.09	0.00	0.00	
1,500.00	9.07	290.57	1,493.18	38.63	-102.93	-38.63	0.00	0.00	
1,600.00	9.07	290.57	1,591.93	44.16	-117.69	-44.16	0.00	0.00	
1,700.00	9.07	290.57	1,690.68	49.70	-132.44	-49.70	0.00	0.00	
1,800.00	9.07	290.57	1,789.43	55.24	-147.20	-55.24	0.00	0.00	
1,900.00	9.07	290.57	1,888.18	60.77	-161.96	-60.77	0.00	0.00	
2,000.00	9.07	290.57	1,986.93	66.31	-176.71	-66.31	0.00	0.00	
2,100.00	9.07	290.57	2,085.68	71.85	-191.47	-71.85	0.00	0.00	
2,200.00	9.07	290.57	2,184.43	77.39	-206.23	-77.39	0.00	0.00	
2,300.00	9.07	290.57	2,283.18	82.92	-220.98	-82.92	0.00	0.00	
2,400.00	9.07	290.57	2,381.93	88.46	-235.74	-88.46	0.00	0.00	
2,500.00	9.07	290.57	2,480.68	94.00	-250.50	-94.00	0.00	0.00	
2,600.00	9.07	290.57	2,579.43	99.54	-265.25	-99.54	0.00	0.00	
2,700.00	9.07	290.57	2,678.18	105.07	-280.01	-105.07	0.00	0.00	
2,800.00	9.07	290.57	2,776.93	110.61	-294.76	-110.61	0.00	0.00	
2,900.00	9.07	290.57	2,875.68	116.15	-309.52	-116.15	0.00	0.00	
3,000.00	9.07	290.57	2,974.43	121.69	-324.28	-121.69	0.00	0.00	
3,100.00	9.07	290.57	3,073.18	127.22	-339.03	-127.22	0.00	0.00	
3,200.00	9.07	290.57	3,171.93	132.76	-353.79	-132.76	0.00	0.00	
3,300.00	9.07	290.57	3,270.68	138.30	-368.55	-138.30	0.00	0.00	
3,400.00	9.07	290.57	3,369.43	143.84	-383.30	-143.84	0.00	0.00	
3,500.00	9.07	290.57	3,468.18	149.37	-398.06	-149.37	0.00	0.00	
3,600.00	9.07	290.57	3,566.93	154.91	-412.82	-154.91	0.00	0.00	
3,700.00	9.07	290.57	3,665.68	160.45	-427.57	-160.45	0.00	0.00	
3,800.00	9.07	290.57	3,764.43	165.99	-442.33	-165.99	0.00	0.00	
3,900.00	9.07	290.57	3,863.18	171.52	-457.08	-171.52	0.00	0.00	
4,000.00	9.07	290.57	3,961.93	177.06	-471.84	-177.06	0.00	0.00	
4,100.00	9.07	290.57	4,060.68	182.60	-486.60	-182.60	0.00	0.00	
4,200.00	9.07	290.57	4,159.43	188.13	-501.35	-188.13	0.00	0.00	
4,300.00	9.07	290.57	4,258.18	193.67	-516.11	-193.67	0.00	0.00	
4,400.00	9.07	290.57	4,356.93	199.21	-530.87	-199.21	0.00	0.00	
4,500.00	9.07	290.57	4,455.68	204.75	-545.62	-204.75	0.00	0.00	
4,530.40	9.07	290.57	4,485.70	206.43	-550.11	-206.43	0.00	0.00	Sussex
4,600.00	9.07	290.57	4,554.43	210.28	-560.38	-210.28	0.00	0.00	
4,700.00	9.07	290.57	4,653.18	215.82	-575.14	-215.82	0.00	0.00	

Cathedral Energy Services

Planning Report

Database:	USA EDM 5000 Multi Users DB	Local Co-ordinate Reference:	Well Morgan Hills 1D-7H-A168
Company:	Crestone Peak Resources	TVD Reference:	23' KB @ 5048.70usft (ENS 140)
Project:	DJ BASIN	MD Reference:	23' KB @ 5048.70usft (ENS 140)
Site:	S7-T1N-R68W (Woolley-Sosa/Becky/Morgan Hills)	North Reference:	True
Well:	Morgan Hills 1D-7H-A168	Survey Calculation Method:	Minimum Curvature
Wellbore:	HZ		
Design:	PLAN #4		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100u)	Comments / Formations
4,800.00	9.07	290.57	4,751.93	221.36	-589.89	-221.36	0.00	0.00	
4,900.00	9.07	290.57	4,850.68	226.90	-604.65	-226.90	0.00	0.00	
5,000.00	9.07	290.57	4,949.43	232.43	-619.41	-232.43	0.00	0.00	
5,100.00	9.07	290.57	5,048.18	237.97	-634.16	-237.97	0.00	0.00	
5,104.57	9.07	290.57	5,052.70	238.22	-634.84	-238.22	0.00	0.00	Shannon
5,200.00	9.07	290.57	5,146.93	243.51	-648.92	-243.51	0.00	0.00	
5,300.00	9.07	290.57	5,245.68	249.05	-663.67	-249.05	0.00	0.00	
5,400.00	9.07	290.57	5,344.43	254.58	-678.43	-254.58	0.00	0.00	
5,500.00	9.07	290.57	5,443.18	260.12	-693.19	-260.12	0.00	0.00	
5,600.00	9.07	290.57	5,541.93	265.66	-707.94	-265.66	0.00	0.00	
5,700.00	9.07	290.57	5,640.68	271.20	-722.70	-271.20	0.00	0.00	
5,800.00	9.07	290.57	5,739.43	276.73	-737.46	-276.73	0.00	0.00	
5,900.00	9.07	290.57	5,838.18	282.27	-752.21	-282.27	0.00	0.00	
6,000.00	9.07	290.57	5,936.93	287.81	-766.97	-287.81	0.00	0.00	
6,100.00	9.07	290.57	6,035.68	293.34	-781.73	-293.34	0.00	0.00	
6,200.00	9.07	290.57	6,134.43	298.88	-796.48	-298.88	0.00	0.00	
6,300.00	9.07	290.57	6,233.19	304.42	-811.24	-304.42	0.00	0.00	
6,400.00	9.07	290.57	6,331.94	309.96	-825.99	-309.96	0.00	0.00	
6,500.00	9.07	290.57	6,430.69	315.49	-840.75	-315.49	0.00	0.00	
6,600.00	9.07	290.57	6,529.44	321.03	-855.51	-321.03	0.00	0.00	
6,634.70	9.07	290.57	6,563.70	322.95	-860.63	-322.95	0.00	0.00	Teepee Buttes (*if present)
6,700.00	9.07	290.57	6,628.19	326.57	-870.26	-326.57	0.00	0.00	
6,800.00	9.07	290.57	6,726.94	332.11	-885.02	-332.11	0.00	0.00	
6,853.07	9.07	290.57	6,779.35	335.05	-892.85	-335.05	0.00	0.00	START BUILD/TURN
6,900.00	8.45	266.06	6,825.74	336.11	-899.76	-336.11	8.00	-1.31	
7,000.00	11.91	223.71	6,924.28	328.13	-914.24	-328.13	8.00	3.46	
7,100.00	18.42	205.45	7,020.80	306.37	-928.19	-306.37	8.00	6.51	
7,200.00	25.76	196.89	7,113.42	271.26	-941.31	-271.26	8.00	7.34	
7,300.00	33.39	192.00	7,200.34	223.47	-953.37	-223.47	8.00	7.63	
7,400.00	41.15	188.76	7,279.86	163.93	-964.12	-163.93	8.00	7.76	
7,500.00	48.98	186.40	7,350.44	93.81	-973.35	-93.81	8.00	7.82	
7,506.53	49.49	186.27	7,354.70	88.89	-973.90	-88.89	8.00	7.85	Sharon Springs
7,600.00	56.84	184.55	7,410.70	14.47	-980.89	-14.47	8.00	7.86	
7,603.67	57.13	184.49	7,412.70	11.40	-981.13	-11.40	8.00	7.88	Niobrara
7,700.00	64.73	183.00	7,459.47	-72.55	-986.59	72.55	8.00	7.89	
7,742.77	68.10	182.40	7,476.58	-111.70	-988.44	111.70	8.00	7.90	TPZ
7,800.00	72.63	181.65	7,495.81	-165.56	-990.34	165.56	8.00	7.90	
7,900.00	80.53	180.40	7,519.00	-262.73	-992.06	262.73	8.00	7.91	
7,933.15	83.16	180.01	7,523.70	-295.54	-992.17	295.54	8.00	7.91	B Chalk
8,000.00	88.45	179.22	7,528.59	-362.19	-991.72	362.19	8.00	7.91	
8,018.36	89.90	179.00	7,528.86	-380.54	-991.43	380.54	8.00	7.91	LP @ 7528' TVD; 89.9°
8,100.00	89.90	179.00	7,529.00	-462.17	-990.01	462.17	0.00	0.00	
8,200.00	89.90	179.00	7,529.17	-562.16	-988.26	562.16	0.00	0.00	
8,300.00	89.90	179.00	7,529.35	-662.14	-986.52	662.14	0.00	0.00	
8,400.00	89.90	179.00	7,529.52	-762.13	-984.77	762.13	0.00	0.00	
8,500.00	89.90	179.00	7,529.70	-862.11	-983.03	862.11	0.00	0.00	
8,600.00	89.90	179.00	7,529.87	-962.09	-981.28	962.09	0.00	0.00	
8,700.00	89.90	179.00	7,530.05	-1,062.08	-979.54	1,062.08	0.00	0.00	
8,800.00	89.90	179.00	7,530.22	-1,162.06	-977.79	1,162.06	0.00	0.00	
8,900.00	89.90	179.00	7,530.40	-1,262.05	-976.05	1,262.05	0.00	0.00	
9,000.00	89.90	179.00	7,530.57	-1,362.03	-974.30	1,362.03	0.00	0.00	
9,100.00	89.90	179.00	7,530.74	-1,462.02	-972.56	1,462.02	0.00	0.00	

Cathedral Energy Services

Planning Report

Database:	USA EDM 5000 Multi Users DB	Local Co-ordinate Reference:	Well Morgan Hills 1D-7H-A168
Company:	Crestone Peak Resources	TVD Reference:	23' KB @ 5048.70usft (ENS 140)
Project:	DJ BASIN	MD Reference:	23' KB @ 5048.70usft (ENS 140)
Site:	S7-T1N-R68W (Woolley-Sosa/Becky/Morgan Hills)	North Reference:	True
Well:	Morgan Hills 1D-7H-A168	Survey Calculation Method:	Minimum Curvature
Wellbore:	HZ		
Design:	PLAN #4		

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100u)	Comments / Formations
9,200.00	89.90	179.00	7,530.92	-1,562.00	-970.81	1,562.00	0.00	0.00	
9,300.00	89.90	179.00	7,531.09	-1,661.99	-969.06	1,661.99	0.00	0.00	
9,400.00	89.90	179.00	7,531.27	-1,761.97	-967.32	1,761.97	0.00	0.00	
9,500.00	89.90	179.00	7,531.44	-1,861.96	-965.57	1,861.96	0.00	0.00	
9,600.00	89.90	179.00	7,531.62	-1,961.94	-963.83	1,961.94	0.00	0.00	
9,700.00	89.90	179.00	7,531.79	-2,061.93	-962.08	2,061.93	0.00	0.00	
9,800.00	89.90	179.00	7,531.97	-2,161.91	-960.34	2,161.91	0.00	0.00	
9,900.00	89.90	179.00	7,532.14	-2,261.89	-958.59	2,261.89	0.00	0.00	
10,000.00	89.90	179.00	7,532.32	-2,361.88	-956.85	2,361.88	0.00	0.00	
10,100.00	89.90	179.00	7,532.49	-2,461.86	-955.10	2,461.86	0.00	0.00	
10,200.00	89.90	179.00	7,532.66	-2,561.85	-953.36	2,561.85	0.00	0.00	
10,300.00	89.90	179.00	7,532.84	-2,661.83	-951.61	2,661.83	0.00	0.00	
10,400.00	89.90	179.00	7,533.01	-2,761.82	-949.87	2,761.82	0.00	0.00	
10,500.00	89.90	179.00	7,533.19	-2,861.80	-948.12	2,861.80	0.00	0.00	
10,600.00	89.90	179.00	7,533.36	-2,961.79	-946.38	2,961.79	0.00	0.00	
10,700.00	89.90	179.00	7,533.54	-3,061.77	-944.63	3,061.77	0.00	0.00	
10,800.00	89.90	179.00	7,533.71	-3,161.76	-942.89	3,161.76	0.00	0.00	
10,900.00	89.90	179.00	7,533.89	-3,261.74	-941.14	3,261.74	0.00	0.00	
11,000.00	89.90	179.00	7,534.06	-3,361.73	-939.40	3,361.73	0.00	0.00	
11,100.00	89.90	179.00	7,534.23	-3,461.71	-937.65	3,461.71	0.00	0.00	
11,200.00	89.90	179.00	7,534.41	-3,561.69	-935.91	3,561.69	0.00	0.00	
11,300.00	89.90	179.00	7,534.58	-3,661.68	-934.16	3,661.68	0.00	0.00	
11,400.00	89.90	179.00	7,534.76	-3,761.66	-932.41	3,761.66	0.00	0.00	
11,500.00	89.90	179.00	7,534.93	-3,861.65	-930.67	3,861.65	0.00	0.00	
11,538.36	89.90	179.00	7,535.00	-3,900.00	-930.00	3,900.00	0.00	0.00	START TURN
11,600.00	89.91	179.62	7,535.10	-3,961.64	-929.26	3,961.64	1.00	0.02	
11,663.31	89.92	180.25	7,535.19	-4,024.95	-929.18	4,024.95	1.00	0.02	END OF TURN
11,700.00	89.92	180.25	7,535.24	-4,061.64	-929.34	4,061.64	0.00	0.00	
11,800.00	89.92	180.25	7,535.38	-4,161.64	-929.78	4,161.64	0.00	0.00	
11,900.00	89.92	180.25	7,535.51	-4,261.63	-930.21	4,261.63	0.00	0.00	
12,000.00	89.92	180.25	7,535.65	-4,361.63	-930.65	4,361.63	0.00	0.00	
12,100.00	89.92	180.25	7,535.78	-4,461.63	-931.08	4,461.63	0.00	0.00	
12,200.00	89.92	180.25	7,535.92	-4,561.63	-931.52	4,561.63	0.00	0.00	
12,300.00	89.92	180.25	7,536.05	-4,661.63	-931.95	4,661.63	0.00	0.00	
12,400.00	89.92	180.25	7,536.19	-4,761.63	-932.39	4,761.63	0.00	0.00	
12,500.00	89.92	180.25	7,536.32	-4,861.63	-932.82	4,861.63	0.00	0.00	
12,600.00	89.92	180.25	7,536.45	-4,961.63	-933.26	4,961.63	0.00	0.00	
12,700.00	89.92	180.25	7,536.59	-5,061.63	-933.69	5,061.63	0.00	0.00	
12,800.00	89.92	180.25	7,536.72	-5,161.63	-934.13	5,161.63	0.00	0.00	
12,900.00	89.92	180.25	7,536.86	-5,261.62	-934.56	5,261.62	0.00	0.00	
13,000.00	89.92	180.25	7,536.99	-5,361.62	-935.00	5,361.62	0.00	0.00	
13,100.00	89.92	180.25	7,537.13	-5,461.62	-935.43	5,461.62	0.00	0.00	
13,200.00	89.92	180.25	7,537.26	-5,561.62	-935.87	5,561.62	0.00	0.00	
13,300.00	89.92	180.25	7,537.40	-5,661.62	-936.30	5,661.62	0.00	0.00	
13,400.00	89.92	180.25	7,537.53	-5,761.62	-936.74	5,761.62	0.00	0.00	
13,500.00	89.92	180.25	7,537.67	-5,861.62	-937.17	5,861.62	0.00	0.00	
13,600.00	89.92	180.25	7,537.80	-5,961.62	-937.61	5,961.62	0.00	0.00	
13,700.00	89.92	180.25	7,537.94	-6,061.62	-938.04	6,061.62	0.00	0.00	
13,800.00	89.92	180.25	7,538.07	-6,161.62	-938.48	6,161.62	0.00	0.00	
13,900.00	89.92	180.25	7,538.20	-6,261.61	-938.91	6,261.61	0.00	0.00	
14,000.00	89.92	180.25	7,538.34	-6,361.61	-939.35	6,361.61	0.00	0.00	
14,100.00	89.92	180.25	7,538.47	-6,461.61	-939.78	6,461.61	0.00	0.00	

Cathedral Energy Services

Planning Report

Database:	USA EDM 5000 Multi Users DB	Local Co-ordinate Reference:	Well Morgan Hills 1D-7H-A168
Company:	Crestone Peak Resources	TVD Reference:	23' KB @ 5048.70usft (ENS 140)
Project:	DJ BASIN	MD Reference:	23' KB @ 5048.70usft (ENS 140)
Site:	S7-T1N-R68W (Woolley-Sosa/Becky/Morgan Hills)	North Reference:	True
Well:	Morgan Hills 1D-7H-A168	Survey Calculation Method:	Minimum Curvature
Wellbore:	HZ		
Design:	PLAN #4		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100u)	Comments / Formations
14,200.00	89.92	180.25	7,538.61	-6,561.61	-940.22	6,561.61	0.00	0.00	
14,300.00	89.92	180.25	7,538.74	-6,661.61	-940.65	6,661.61	0.00	0.00	
14,400.00	89.92	180.25	7,538.88	-6,761.61	-941.09	6,761.61	0.00	0.00	
14,500.00	89.92	180.25	7,539.01	-6,861.61	-941.53	6,861.61	0.00	0.00	
14,600.00	89.92	180.25	7,539.15	-6,961.61	-941.96	6,961.61	0.00	0.00	
14,700.00	89.92	180.25	7,539.28	-7,061.61	-942.40	7,061.61	0.00	0.00	
14,800.00	89.92	180.25	7,539.42	-7,161.60	-942.83	7,161.60	0.00	0.00	
14,900.00	89.92	180.25	7,539.55	-7,261.60	-943.27	7,261.60	0.00	0.00	
15,000.00	89.92	180.25	7,539.69	-7,361.60	-943.70	7,361.60	0.00	0.00	
15,100.00	89.92	180.25	7,539.82	-7,461.60	-944.14	7,461.60	0.00	0.00	
15,200.00	89.92	180.25	7,539.95	-7,561.60	-944.57	7,561.60	0.00	0.00	
15,300.00	89.92	180.25	7,540.09	-7,661.60	-945.01	7,661.60	0.00	0.00	
15,400.00	89.92	180.25	7,540.22	-7,761.60	-945.44	7,761.60	0.00	0.00	
15,500.00	89.92	180.25	7,540.36	-7,861.60	-945.88	7,861.60	0.00	0.00	
15,600.00	89.92	180.25	7,540.49	-7,961.60	-946.31	7,961.60	0.00	0.00	
15,700.00	89.92	180.25	7,540.63	-8,061.60	-946.75	8,061.60	0.00	0.00	
15,800.00	89.92	180.25	7,540.76	-8,161.59	-947.18	8,161.59	0.00	0.00	
15,900.00	89.92	180.25	7,540.90	-8,261.59	-947.62	8,261.59	0.00	0.00	
16,000.00	89.92	180.25	7,541.03	-8,361.59	-948.05	8,361.59	0.00	0.00	
16,100.00	89.92	180.25	7,541.17	-8,461.59	-948.49	8,461.59	0.00	0.00	
16,200.00	89.92	180.25	7,541.30	-8,561.59	-948.92	8,561.59	0.00	0.00	
16,300.00	89.92	180.25	7,541.44	-8,661.59	-949.36	8,661.59	0.00	0.00	
16,400.00	89.92	180.25	7,541.57	-8,761.59	-949.79	8,761.59	0.00	0.00	
16,500.00	89.92	180.25	7,541.71	-8,861.59	-950.23	8,861.59	0.00	0.00	
16,600.00	89.92	180.25	7,541.84	-8,961.59	-950.66	8,961.59	0.00	0.00	
16,700.00	89.92	180.25	7,541.97	-9,061.58	-951.10	9,061.58	0.00	0.00	
16,800.00	89.92	180.25	7,542.11	-9,161.58	-951.53	9,161.58	0.00	0.00	
16,900.00	89.92	180.25	7,542.24	-9,261.58	-951.97	9,261.58	0.00	0.00	
17,000.00	89.92	180.25	7,542.38	-9,361.58	-952.40	9,361.58	0.00	0.00	
17,100.00	89.92	180.25	7,542.51	-9,461.58	-952.84	9,461.58	0.00	0.00	
17,200.00	89.92	180.25	7,542.65	-9,561.58	-953.27	9,561.58	0.00	0.00	
17,300.00	89.92	180.25	7,542.78	-9,661.58	-953.71	9,661.58	0.00	0.00	
17,400.00	89.92	180.25	7,542.92	-9,761.58	-954.14	9,761.58	0.00	0.00	
17,461.82	89.92	180.25	7,543.00	-9,823.40	-954.41	9,823.40	0.00	0.00	TD at 17461.82

Cathedral Energy Services

Planning Report

Database:	USA EDM 5000 Multi Users DB	Local Co-ordinate Reference:	Well Morgan Hills 1D-7H-A168
Company:	Crestone Peak Resources	TVD Reference:	23' KB @ 5048.70usft (ENS 140)
Project:	DJ BASIN	MD Reference:	23' KB @ 5048.70usft (ENS 140)
Site:	S7-T1N-R68W (Woolley-Sosa/Becky/Morgan Hills)	North Reference:	True
Well:	Morgan Hills 1D-7H-A168	Survey Calculation Method:	Minimum Curvature
Wellbore:	HZ		
Design:	PLAN #4		

Targets									
Target Name									
- hit/miss target	Dip Angle	Dip Dir.	TVD	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude
- Shape	(°)	(°)	(usft)	(usft)	(usft)	(usft)	(usft)		
MH 1D-7H-A168 TGT 1C - plan hits target center - Point	0.00	0.00	7,535.00	-3,900.00	-930.00	1,265,500.88	3,128,184.52	40.061281	-105.042036
MH 1D-7H-A168 PBHL - plan misses target center by 120.00usft at 17461.82usft MD (7543.00 TVD, -9823.40 N, -954.41 E) - Point	0.00	0.00	7,663.00	-9,823.40	-954.41	1,259,577.44	3,128,190.92	40.045020	-105.042122
MH 1D-7H-A168 PBHL - plan hits target center - Point	0.00	0.00	7,543.00	-9,823.40	-954.41	1,259,577.44	3,128,190.92	40.045020	-105.042122
MH 1D-7H-A168 TGT - plan misses target center by 118.70usft at 11538.55usft MD (7535.00 TVD, -3900.20 N, -930.00 E) - Point	0.00	0.00	7,653.70	-3,900.00	-930.00	1,265,500.88	3,128,184.52	40.061281	-105.042036

Formations						
Measured Depth	Vertical Depth	Name	Lithology	Dip	Dip Direction	
(usft)	(usft)			(°)	(°)	
1,000.09	998.70	Fox Hills - BASE				
4,530.40	4,485.70	Sussex				
5,104.57	5,052.70	Shannon				
6,634.70	6,563.70	Teepee Buttes (*if present)				
7,506.53	7,354.70	Sharon Springs				
7,603.67	7,412.70	Niobrara				
7,933.15	7,523.70	B Chalk				

Plan Annotations				
Measured Depth	Vertical Depth	Local Coordinates		Comment
(usft)	(usft)	+N/-S (usft)	+E/-W (usft)	
350.00	350.00	0.00	0.00	KOP @ 350'
1,256.83	1,253.05	25.16	-67.05	EOB; INC=9°
6,853.07	6,779.35	335.05	-892.85	START BUILD/TURN
7,742.77	7,476.58	-111.70	-988.44	TPZ
8,018.36	7,528.86	-380.54	-991.43	LP @ 7528' TVD; 89.9°
11,538.36	7,535.00	-3,900.00	-930.00	START TURN
11,663.31	7,535.19	-4,024.95	-929.18	END OF TURN
17,461.82	7,543.00	-9,823.40	-954.41	TD at 17461.82