

FORM  
5A

Rev  
06/12

State of Colorado  
Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



DE	ET	OE	ES
----	----	----	----

Document Number:

401083308

Date Received:

07/25/2016

COMPLETED INTERVAL REPORT

The completed interval Report, Form 5A, shall be submitted within thirty (30) days of completing a formation (successful or not), when a formation is temporarily abandoned or permanently abandoned, for a recompletion, reperforation or restimulation, or when a formation is commingled. Fill out a section for each formation. Attach as many pages as required to fully describe the work. List in order of completion.

1. OGCC Operator Number: 100322

2. Name of Operator: NOBLE ENERGY INC

3. Address: 1625 BROADWAY STE 2200

City: DENVER State: CO Zip: 80202

4. Contact Name: Julie Webb

Phone: (720) 587-2223

Fax:

Email: jwebb@progressivepcs.net

5. API Number 05-123-41725-00

7. Well Name: Wells Ranch

8. Location: QtrQtr: NWSW Section: 32 Township: 6N Range: 62W Meridian: 6

9. Field Name: WATTENBERG Field Code: 90750

6. County: WELD

Well Number: AE32-635

Completed Interval

FORMATION: NIOBRARA Status: PRODUCING Treatment Type: FRACTURE STIMULATION

Treatment Date: 01/27/2016 End Date: 01/31/2016 Date of First Production this formation: 06/26/2016

Perforations Top: 7010 Bottom: 15873 No. Holes: 0 Hole size:

Provide a brief summary of the formation treatment: Open Hole: ☒

Niobrara Frac'd with 9031596 lbs Ottawa Sand, 9669508 gal silverstem and slickwater.

This formation is commingled with another formation: ☐ Yes ☒ No

Total fluid used in treatment (bbl): 230226

Max pressure during treatment (psi): 7220

Total gas used in treatment (mcf):

Fluid density at initial fracture (lbs/gal): 8.43

Type of gas used in treatment:

Min frac gradient (psi/ft): 0.82

Total acid used in treatment (bbl):

Number of staged intervals: 38

Recycled water used in treatment (bbl): 0

Flowback volume recovered (bbl): 13583

Fresh water used in treatment (bbl): 230226

Disposition method for flowback: RECYCLE

Total proppant used (lbs): 9031596

Rule 805 green completion techniques were utilized: ☒

Reason why green completion not utilized:

Fracture stimulations must be reported on FracFocus.org

Test Information:

Date: 06/29/2016 Hours: 24 Bbl oil: 581 Mcf Gas: 284 Bbl H2O: 1238

Calculated 24 hour rate: Bbl oil: 581 Mcf Gas: 284 Bbl H2O: 1238 GOR:

Test Method: Flowing Casing PSI: 5 Tubing PSI: 953 Choke Size: 20/64

Gas Disposition: SOLD Gas Type: WET Btu Gas: 1388 API Gravity Oil: 52

Tubing Size: 2 + 3/8 Tubing Setting Depth: 6637 Tbg setting date: 06/17/2016 Packer Depth:

Reason for Non-Production:

Date formation Abandoned: Squeeze: ☐ Yes ☐ No If yes, number of sacks cmt

\*\* Bridge Plug Depth: \*\* Sacks cement on top: \*\* Wireline and Cement Job Summary must be attached.

Comment:

Top packer set at 6870', bottom packer set at 15714'.

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: \_\_\_\_\_ Print Name: Julie Webb

Title: Senior Regulatory Analyst Date: 7/25/2016 Email jwebb@progressivepcs.net  
:

### Attachment Check List

**Att Doc Num**      **Name**

401083308	FORM 5A SUBMITTED
-----------	-------------------

Total Attach: 1 Files

### General Comments

**User Group**      **Comment**

**Comment Date**

		Stamp Upon Approval
--	--	---------------------

Total: 0 comment(s)