

GENERAL INPUTS	
Name	Savanna Riebe
Cell Phone Number	970-714-0288
Date	12/22/2016
WELL INPUTS	
Well Name	Zimmerman 24-17
API #	05-123-24027
WINS #	98862
Gyro Date:	Dec 2014
Surface Hole Size (in)	12.25
Prod Hole Size (in)	7.88
OH Excess Factor	60
Surface Casing (size/wt)	8-5/8", 24#
Surface Casing Shoe (ft)	446
Prod csg (size/wt)	4.5", 11.6#
Tubing OD (in)	2-3/8"
Tubing Set Depth (ft)	7188
Collar Above CIBP (ft)	7080
Collar Below CIBP (ft)	7124
Niobrara CIBP / BOC (ft)	7100
Niobrara TOC (ft)	6470
Niobrara Cement Vol (sx)	40
SUSX/SH BOC (ft)	4230
SUSX/SH TOC (ft)	3830
SUSX/SH Cement Vol (sx)	25
Bradenhead Issues? (Y/N)	N
Stub Plug BOC (ft)	800
Cut Casing Depth (ft)	490
Stub Plug TOC Form6 (ft)	396
Stub Plug TOC Calc (ft)	245
Stub Plug Cement Vol (sx)	90
GEOLOGY INPUTS	
FHM (ft)	698
Sussex Top (ft)	4031
Sussex Base (ft)	4262
Shannon Base (ft)	4681
Niobrara Top (ft)	6873
QUESTIONS?	
Who Drilled Well?	United States Exploration
Straight or Deviated Hole?	Deviated
Age of well (yr)	20
Any squeeze holes? (Y/N)	N
Details of Integrity Issues?	DV Tool @ 5066'
SUSX/SH Productive? (Y/N)	N
Gyro Found (Y/N)	Y
CBL Found (Y/N)	Y
Packer Downhole? (Y/N)	N
Packer Depth (ft)	7500

COLOR KEY



*If No Integrity Issues, Put "NONE"

