DISCLAIMER
The information contained in this report is for the exclusive use of the client specified above and may not be reproduced or forwarded to any third party without the express written consent of Weatherford. The opinions expressed in this report are based on the information supplied to Weatherford by the client. While every effort is made to ensure the accuracy of the opinions given, the well results depend on a number of factors, many of which are outside Weatherford's control and require interpretation. Weatherford does not guarantee the accuracy of any opinion and will not be liable for any loss or damage incurred by any person as a result of reliance on any opinion made in this report or any of Weatherford's services.

NOTE: TRIPPING SPEED SHOULD BE LESS THAN 90 FT/MIN WHEN POOH FOR THE 12.25" BHA

NOTE: KEEP ECD BELOW 12.7 PPG

Internal Report

Customer Name: Chevron North America
Well Name: Tubular Bells
Location: Gulf of Mexico
Rig Name: Transocean Deepwater Nautilus
Job Number: 1
Survey Name: Tubular Bells
Survey Date: 2 Jan 2014
Tie-In Depth: 0 ft
Survey Depth: 0 ft - 9,000 ft
Survey Interval: 30 ft
Survey Company: Weatherford International
Survey Engineer: Jeff Hall
Survey Type: Gyro
Survey Direction: Inclination Only
Survey Tool Type: Gyro
Survey Tool Number: 1
Survey Tool Range: 0 ft - 9,000 ft
Survey Tool Accuracy: 0.1°
Survey Tool Resolution: 0.1°
Survey Tool Sensor Offset: 0 ft
Survey Tool Sensor Type: Gyro
Survey Tool Sensor Number: 1
Survey Tool Sensor Range: 0 ft - 9,000 ft
Survey Tool Sensor Accuracy: 0.1°
Survey Tool Sensor