



# **Ursa Operating Company, LLC**

**Rio Blanco County, Colorado**

**BR C-240**

**BR C-240 32A-24-2-98**

**Wellbore #1**

**Plan: Design #1**

## **Standard Planning Report**

**18 January, 2017**



<b>Database:</b>	EDM 5000.1 Single User Db	<b>Local Co-ordinate Reference:</b>	Well BR C-240 32A-24-2-98
<b>Company:</b>	Ursa Operating Company, LLC	<b>TVD Reference:</b>	BR C-240 32A-24-2-98 @ 6332.5usft (Est KB)
<b>Project:</b>	Rio Blanco County, Colorado	<b>MD Reference:</b>	BR C-240 32A-24-2-98 @ 6332.5usft (Est KB)
<b>Site:</b>	BR C-240	<b>North Reference:</b>	True
<b>Well:</b>	BR C-240 32A-24-2-98	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Design #1		

<b>Project</b>	Rio Blanco County, Colorado		
<b>Map System:</b>	US State Plane 1983	<b>System Datum:</b>	Mean Sea Level
<b>Geo Datum:</b>	North American Datum 1983		
<b>Map Zone:</b>	Colorado Northern Zone		Using geodetic scale factor

<b>Site</b>	BR C-240		
<b>Site Position:</b>		<b>Northing:</b>	1,203,233.70 usft
<b>From:</b>	Map	<b>Easting:</b>	2,203,189.00 usft
<b>Position Uncertainty:</b>	0.0 usft	<b>Slot Radius:</b>	13-3/16 "
		<b>Latitude:</b>	39.856238800
		<b>Longitude:</b>	-108.338695300
		<b>Grid Convergence:</b>	-1.83 °

<b>Well</b>	BR C-240 32A-24-2-98, SHL: 39.8562388, -108.3386953		
<b>Well Position</b>	<b>+N/-S</b>	0.0 usft	<b>Northing:</b> 1,203,233.70 usft
	<b>+E/-W</b>	0.0 usft	<b>Easting:</b> 2,203,189.00 usft
<b>Position Uncertainty</b>	0.0 usft	<b>Wellhead Elevation:</b>	6,332.5 usft
		<b>Latitude:</b>	39.856238800
		<b>Longitude:</b>	-108.338695300
		<b>Ground Level:</b>	6,304.5 usft

<b>Wellbore</b>	Wellbore #1				
<b>Magnetics</b>	<b>Model Name</b>	<b>Sample Date</b>	<b>Declination (°)</b>	<b>Dip Angle (°)</b>	<b>Field Strength (nT)</b>
	IGRF2015	1/14/2017	9.94	65.83	51,723

<b>Design</b>	Design #1			
<b>Audit Notes:</b>				
<b>Version:</b>	<b>Phase:</b>	PROTOTYPE	<b>Tie On Depth:</b>	0.0
<b>Vertical Section:</b>	<b>Depth From (TVD) (usft)</b>	<b>+N/-S (usft)</b>	<b>+E/-W (usft)</b>	<b>Direction (°)</b>
	0.0	0.0	0.0	343.34

<b>Plan Sections</b>										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
500.0	0.00	0.00	500.0	0.0	0.0	0.00	0.00	0.00	0.00	
1,522.1	35.77	343.34	1,457.0	295.9	-88.5	3.50	3.50	0.00	343.34	
5,897.7	35.77	343.34	5,007.0	2,746.5	-821.8	0.00	0.00	0.00	0.00	
6,919.8	0.00	0.00	5,964.0	3,042.3	-910.4	3.50	-3.50	0.00	180.00	32A-24-2-98 TGT
11,723.8	0.00	0.00	10,768.0	3,042.3	-910.4	0.00	0.00	0.00	0.00	

<b>Database:</b>	EDM 5000.1 Single User Db	<b>Local Co-ordinate Reference:</b>	Well BR C-240 32A-24-2-98
<b>Company:</b>	Ursa Operating Company, LLC	<b>TVD Reference:</b>	BR C-240 32A-24-2-98 @ 6332.5usft (Est KB)
<b>Project:</b>	Rio Blanco County, Colorado	<b>MD Reference:</b>	BR C-240 32A-24-2-98 @ 6332.5usft (Est KB)
<b>Site:</b>	BR C-240	<b>North Reference:</b>	True
<b>Well:</b>	BR C-240 32A-24-2-98	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Design #1		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	0.00	
0.1	0.00	0.00	0.1	0.0	0.0	0.0	0.00	0.00	0.00	
SHL 39.8562388 -108.3386953										
100.0	0.00	0.00	100.0	0.0	0.0	0.0	0.00	0.00	0.00	
200.0	0.00	0.00	200.0	0.0	0.0	0.0	0.00	0.00	0.00	
300.0	0.00	0.00	300.0	0.0	0.0	0.0	0.00	0.00	0.00	
400.0	0.00	0.00	400.0	0.0	0.0	0.0	0.00	0.00	0.00	
500.0	0.00	0.00	500.0	0.0	0.0	0.0	0.00	0.00	0.00	
Start Build 3.50										
600.0	3.50	343.34	599.9	2.9	-0.9	3.1	3.50	3.50	0.00	
632.1	4.63	343.34	632.0	5.1	-1.5	5.3	3.50	3.50	0.00	
Green River Fm - Mahogany Bench										
689.4	6.63	343.34	689.0	10.5	-3.1	10.9	3.50	3.50	0.00	
Dissolution Surface										
700.0	7.00	343.34	699.5	11.7	-3.5	12.2	3.50	3.50	0.00	
800.0	10.50	343.34	798.3	26.3	-7.9	27.4	3.50	3.50	0.00	
900.0	14.00	343.34	896.0	46.6	-13.9	48.6	3.50	3.50	0.00	
1,000.0	17.50	343.34	992.3	72.6	-21.7	75.8	3.50	3.50	0.00	
1,100.0	21.00	343.34	1,086.7	104.2	-31.2	108.7	3.50	3.50	0.00	
1,200.0	24.50	343.34	1,178.9	141.2	-42.3	147.4	3.50	3.50	0.00	
1,300.0	28.00	343.34	1,268.5	183.6	-54.9	191.6	3.50	3.50	0.00	
1,400.0	31.50	343.34	1,355.3	231.1	-69.2	241.2	3.50	3.50	0.00	
1,500.0	35.00	343.34	1,439.0	283.6	-84.9	296.1	3.50	3.50	0.00	
1,522.1	35.77	343.34	1,457.0	295.9	-88.5	308.9	3.50	3.50	0.00	
Start 4375.6 hold at 1522.1 MD										
1,600.0	35.77	343.34	1,520.2	339.5	-101.6	354.4	0.00	0.00	0.00	
1,700.0	35.77	343.34	1,601.3	395.5	-118.4	412.8	0.00	0.00	0.00	
1,800.0	35.77	343.34	1,682.4	451.5	-135.1	471.3	0.00	0.00	0.00	
1,900.0	35.77	343.34	1,763.6	507.5	-151.9	529.8	0.00	0.00	0.00	
1,937.5	35.77	343.34	1,794.0	528.5	-158.2	551.7	0.00	0.00	0.00	
Green River Fm - Garden Gulch Mbr										
2,000.0	35.77	343.34	1,844.7	563.5	-168.6	588.2	0.00	0.00	0.00	
2,100.0	35.77	343.34	1,925.8	619.5	-185.4	646.7	0.00	0.00	0.00	
2,144.6	35.77	343.34	1,962.0	644.5	-192.9	672.7	0.00	0.00	0.00	
Wasatch										
2,200.0	35.77	343.34	2,007.0	675.5	-202.1	705.1	0.00	0.00	0.00	
2,300.0	35.77	343.34	2,088.1	731.6	-218.9	763.6	0.00	0.00	0.00	
2,400.0	35.77	343.34	2,169.2	787.6	-235.7	822.1	0.00	0.00	0.00	
2,500.0	35.77	343.34	2,250.4	843.6	-252.4	880.5	0.00	0.00	0.00	
2,600.0	35.77	343.34	2,331.5	899.6	-269.2	939.0	0.00	0.00	0.00	
2,700.0	35.77	343.34	2,412.6	955.6	-285.9	997.4	0.00	0.00	0.00	
2,800.0	35.77	343.34	2,493.8	1,011.6	-302.7	1,055.9	0.00	0.00	0.00	
2,900.0	35.77	343.34	2,574.9	1,067.6	-319.5	1,114.4	0.00	0.00	0.00	
3,000.0	35.77	343.34	2,656.0	1,123.6	-336.2	1,172.8	0.00	0.00	0.00	
3,100.0	35.77	343.34	2,737.2	1,179.6	-353.0	1,231.3	0.00	0.00	0.00	
3,200.0	35.77	343.34	2,818.3	1,235.6	-369.7	1,289.7	0.00	0.00	0.00	
3,300.0	35.77	343.34	2,899.4	1,291.6	-386.5	1,348.2	0.00	0.00	0.00	
3,400.0	35.77	343.34	2,980.6	1,347.6	-403.2	1,406.7	0.00	0.00	0.00	
3,500.0	35.77	343.34	3,061.7	1,403.6	-420.0	1,465.1	0.00	0.00	0.00	
3,600.0	35.77	343.34	3,142.8	1,459.6	-436.8	1,523.6	0.00	0.00	0.00	
3,700.0	35.77	343.34	3,224.0	1,515.6	-453.5	1,582.0	0.00	0.00	0.00	
3,800.0	35.77	343.34	3,305.1	1,571.6	-470.3	1,640.5	0.00	0.00	0.00	

<b>Database:</b>	EDM 5000.1 Single User Db	<b>Local Co-ordinate Reference:</b>	Well BR C-240 32A-24-2-98
<b>Company:</b>	Ursa Operating Company, LLC	<b>TVD Reference:</b>	BR C-240 32A-24-2-98 @ 6332.5usft (Est KB)
<b>Project:</b>	Rio Blanco County, Colorado	<b>MD Reference:</b>	BR C-240 32A-24-2-98 @ 6332.5usft (Est KB)
<b>Site:</b>	BR C-240	<b>North Reference:</b>	True
<b>Well:</b>	BR C-240 32A-24-2-98	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Design #1		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
3,900.0	35.77	343.34	3,386.2	1,627.6	-487.0	1,698.9	0.00	0.00	0.00
4,000.0	35.77	343.34	3,467.4	1,683.6	-503.8	1,757.4	0.00	0.00	0.00
4,040.2	35.77	343.34	3,500.0	1,706.2	-510.5	1,780.9	0.00	0.00	0.00
<b>Surface Casing</b>									
4,100.0	35.77	343.34	3,548.5	1,739.7	-520.6	1,815.9	0.00	0.00	0.00
4,200.0	35.77	343.34	3,629.6	1,795.7	-537.3	1,874.3	0.00	0.00	0.00
4,300.0	35.77	343.34	3,710.8	1,851.7	-554.1	1,932.8	0.00	0.00	0.00
4,400.0	35.77	343.34	3,791.9	1,907.7	-570.8	1,991.2	0.00	0.00	0.00
4,500.0	35.77	343.34	3,873.0	1,963.7	-587.6	2,049.7	0.00	0.00	0.00
4,600.0	35.77	343.34	3,954.2	2,019.7	-604.3	2,108.2	0.00	0.00	0.00
4,700.0	35.77	343.34	4,035.3	2,075.7	-621.1	2,166.6	0.00	0.00	0.00
4,800.0	35.77	343.34	4,116.4	2,131.7	-637.9	2,225.1	0.00	0.00	0.00
4,900.0	35.77	343.34	4,197.6	2,187.7	-654.6	2,283.5	0.00	0.00	0.00
5,000.0	35.77	343.34	4,278.7	2,243.7	-671.4	2,342.0	0.00	0.00	0.00
5,100.0	35.77	343.34	4,359.8	2,299.7	-688.1	2,400.5	0.00	0.00	0.00
5,153.2	35.77	343.34	4,403.0	2,329.5	-697.1	2,431.6	0.00	0.00	0.00
<b>Ft Union</b>									
5,200.0	35.77	343.34	4,441.0	2,355.7	-704.9	2,458.9	0.00	0.00	0.00
5,300.0	35.77	343.34	4,522.1	2,411.7	-721.7	2,517.4	0.00	0.00	0.00
5,400.0	35.77	343.34	4,603.2	2,467.7	-738.4	2,575.8	0.00	0.00	0.00
5,500.0	35.77	343.34	4,684.4	2,523.7	-755.2	2,634.3	0.00	0.00	0.00
5,600.0	35.77	343.34	4,765.5	2,579.7	-771.9	2,692.8	0.00	0.00	0.00
5,700.0	35.77	343.34	4,846.6	2,635.7	-788.7	2,751.2	0.00	0.00	0.00
5,800.0	35.77	343.34	4,927.8	2,691.7	-805.4	2,809.7	0.00	0.00	0.00
5,897.7	35.77	343.34	5,007.0	2,746.4	-821.8	2,866.8	0.00	0.00	0.00
<b>Start Drop -3.50</b>									
5,900.0	35.69	343.34	5,008.9	2,747.7	-822.2	2,868.1	3.48	-3.48	0.00
6,000.0	32.19	343.34	5,091.8	2,801.2	-838.2	2,924.0	3.50	-3.50	0.00
6,100.0	28.69	343.34	5,178.0	2,849.8	-852.7	2,974.6	3.50	-3.50	0.00
6,200.0	25.19	343.34	5,267.2	2,893.2	-865.7	3,019.9	3.50	-3.50	0.00
6,300.0	21.69	343.34	5,358.9	2,931.3	-877.1	3,059.7	3.50	-3.50	0.00
6,400.0	18.19	343.34	5,452.9	2,963.9	-886.9	3,093.8	3.50	-3.50	0.00
6,500.0	14.69	343.34	5,548.8	2,991.1	-895.0	3,122.1	3.50	-3.50	0.00
6,600.0	11.19	343.34	5,646.2	3,012.5	-901.4	3,144.5	3.50	-3.50	0.00
6,700.0	7.69	343.34	5,744.9	3,028.2	-906.1	3,160.9	3.50	-3.50	0.00
6,729.4	6.67	343.34	5,774.0	3,031.8	-907.2	3,164.6	3.50	-3.50	0.00
<b>Ohio Creek</b>									
6,800.0	4.19	343.34	5,844.3	3,038.2	-909.1	3,171.3	3.50	-3.50	0.00
6,900.0	0.69	343.34	5,944.2	3,042.2	-910.3	3,175.5	3.50	-3.50	0.00
6,919.8	0.00	0.00	5,964.0	3,042.3	-910.4	3,175.6	3.50	-3.50	0.00
<b>Start 4804.0 hold at 6919.8 MD - Back to Vertical - Williams Fork - Top of Gas - 32A-24-2-98 TGT</b>									
7,000.0	0.00	0.00	6,044.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
7,100.0	0.00	0.00	6,144.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
7,200.0	0.00	0.00	6,244.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
7,300.0	0.00	0.00	6,344.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
7,400.0	0.00	0.00	6,444.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
7,500.0	0.00	0.00	6,544.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
7,600.0	0.00	0.00	6,644.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
7,700.0	0.00	0.00	6,744.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
7,800.0	0.00	0.00	6,844.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
7,900.0	0.00	0.00	6,944.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00

<b>Database:</b>	EDM 5000.1 Single User Db	<b>Local Co-ordinate Reference:</b>	Well BR C-240 32A-24-2-98
<b>Company:</b>	Ursa Operating Company, LLC	<b>TVD Reference:</b>	BR C-240 32A-24-2-98 @ 6332.5usft (Est KB)
<b>Project:</b>	Rio Blanco County, Colorado	<b>MD Reference:</b>	BR C-240 32A-24-2-98 @ 6332.5usft (Est KB)
<b>Site:</b>	BR C-240	<b>North Reference:</b>	True
<b>Well:</b>	BR C-240 32A-24-2-98	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Design #1		

## Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
8,000.0	0.00	0.00	7,044.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
8,100.0	0.00	0.00	7,144.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
8,200.0	0.00	0.00	7,244.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
8,300.0	0.00	0.00	7,344.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
8,400.0	0.00	0.00	7,444.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
8,500.0	0.00	0.00	7,544.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
8,600.0	0.00	0.00	7,644.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
8,700.0	0.00	0.00	7,744.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
8,800.0	0.00	0.00	7,844.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
8,900.0	0.00	0.00	7,944.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
9,000.0	0.00	0.00	8,044.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
9,100.0	0.00	0.00	8,144.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
9,200.0	0.00	0.00	8,244.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
9,300.0	0.00	0.00	8,344.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
9,400.0	0.00	0.00	8,444.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
9,500.0	0.00	0.00	8,544.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
9,600.0	0.00	0.00	8,644.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
9,700.0	0.00	0.00	8,744.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
9,800.0	0.00	0.00	8,844.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
9,900.0	0.00	0.00	8,944.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
10,000.0	0.00	0.00	9,044.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
10,028.8	0.00	0.00	9,073.0	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
<b>Cameo</b>									
10,100.0	0.00	0.00	9,144.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
10,200.0	0.00	0.00	9,244.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
10,300.0	0.00	0.00	9,344.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
10,400.0	0.00	0.00	9,444.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
10,500.0	0.00	0.00	9,544.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
10,573.8	0.00	0.00	9,618.0	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
<b>Rollins</b>									
10,600.0	0.00	0.00	9,644.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
10,700.0	0.00	0.00	9,744.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
10,717.8	0.00	0.00	9,762.0	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
<b>Cozzette</b>									
10,800.0	0.00	0.00	9,844.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
10,900.0	0.00	0.00	9,944.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
11,000.0	0.00	0.00	10,044.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
11,051.8	0.00	0.00	10,096.0	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
<b>Corcoran</b>									
11,100.0	0.00	0.00	10,144.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
11,200.0	0.00	0.00	10,244.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
11,300.0	0.00	0.00	10,344.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
11,400.0	0.00	0.00	10,444.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
11,500.0	0.00	0.00	10,544.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
11,600.0	0.00	0.00	10,644.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
11,700.0	0.00	0.00	10,744.2	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
11,723.8	0.00	0.00	10,768.0	3,042.3	-910.4	3,175.6	0.00	0.00	0.00
<b>BHL 39.8645905 -108.3419383 - TD at 11723.8</b>									

<b>Database:</b>	EDM 5000.1 Single User Db	<b>Local Co-ordinate Reference:</b>	Well BR C-240 32A-24-2-98
<b>Company:</b>	Ursa Operating Company, LLC	<b>TVD Reference:</b>	BR C-240 32A-24-2-98 @ 6332.5usft (Est KB)
<b>Project:</b>	Rio Blanco County, Colorado	<b>MD Reference:</b>	BR C-240 32A-24-2-98 @ 6332.5usft (Est KB)
<b>Site:</b>	BR C-240	<b>North Reference:</b>	True
<b>Well:</b>	BR C-240 32A-24-2-98	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Design #1		

## Design Targets

### Target Name

- hit/miss target	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude
- Shape									
32A-24-2-98 TGT	0.00	0.00	5,964.0	3,042.3	-910.4	1,206,303.57	2,202,376.50	39.864590500	-108.341938300
- plan hits target center									
- Rectangle (sides W100.0 H40.0 D4,804.0)									

## Formations

Measured Depth (usft)	Vertical Depth (usft)	Name	Lithology	Dip (°)	Dip Direction (°)
632.1	627.5	Green River Fm - Mahogany Bench		0.00	
689.4	684.5	Dissolution Surface		0.00	
1,937.5	1,789.5	Green River Fm - Garden Gulch Mbr		0.00	
2,144.6	1,957.5	Wasatch		0.00	
5,153.2	4,398.5	Ft Union		0.00	
6,729.4	5,769.5	Ohio Creek		0.00	
6,919.8	5,959.5	Williams Fork		0.00	
6,919.8	5,959.5	Top of Gas		0.00	
10,028.8	9,068.5	Cameo		0.00	
10,573.8	9,613.5	Rollins		0.00	
10,717.8	9,757.5	Cozzette		0.00	
11,051.8	10,091.5	Corcoran		0.00	

## Plan Annotations

Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates		Comment
		+N/-S (usft)	+E/-W (usft)	
0.1	0.1	0.0	0.0	SHL 39.8562388 -108.3386953
500.0	500.0	0.0	0.0	Start Build 3.50
1,522.1	1,457.0	295.9	-88.5	Start 4375.6 hold at 1522.1 MD
4,040.2	3,500.0	1,706.2	-510.5	Surface Casing
5,897.7	5,007.0	2,746.4	-821.8	Start Drop -3.50
6,919.8	5,964.0	3,042.3	-910.4	Start 4804.0 hold at 6919.8 MD
6,919.8	5,964.0	3,042.3	-910.4	Back to Vertical
11,723.8	10,768.0	3,042.3	-910.4	BHL 39.8645905 -108.3419383
11,723.8	10,768.0	3,042.3	-910.4	TD at 11723.8

