Attachment #2 – Proposed Plugged Wellbore Diagram

Crestone Peak Resources

Well : **Regnier 4-4-19**
Field : **Wattenberg**
County : **Weld** **State : Colorado**
Surface : **Lat: 40.122921 Long: -105.044047**
: **2242 FSL, 2047 FEL NWSE Sec 19 T2N R68W**
API # : **05-123-24954**
Grd Elev : **4972' GR** **KB Elevation: 4987' KB**

Log Tops:

Fox Hills Base	303'
Upper Pierre Base	1292'
Sussex	4252'
Shannon Base	5015'
Niobrara	7273'
Codell	7565'
J Sand	7996'

Well History:

Spud	01/05/2008
TD	01/11/2008

Surface Casing
8-5/8" 24# IPSCO J-55
Surface Casing set @ 727',
cmt'd w/ 370 sx. 16 jts.



CICR set @ 1350'

Internal cement plug w/ 120 sx cement from 1350' to surface

CIBP set @ 1410'

Squeeze holes @ 1400' w/ 340 sx cement circulated to surface

Stage Cmt 3724'-5112'
w/ 330 sx
CBL 01/19/2008

DV Tool set @ 5112'

CIBP set @ 5250' w/ 100 sx cement from ~3923'-5250'

TOC @ 6684'
CBL 01/19/2008

CIBP set @ 7270' w/ 40 sx cement from ~6743'-7270'

Niobrara Perfs
7338'-7358' w/ 2 SPF
Frac'd w/ 173,545 gal fluid and 250,700# 20/40 sand (01/19/2008)

Production Casing
4-½" 11.6# IPSCO I-80 Production Casing set @ 8150', cmt'd w/ 270 sx. 194 jts.

Codell Perfs
7566'-7586' w/ 4 SPF
Frac'd w/ 111,034 gal fluid and 250,140# 20/40 sand (01/19/2008)

CIBP set @ 7950' w/ 20 sx cement from ~7686'-7950'

J Sand Perfs
8010'-8030' w/ 2 SPF
Frac'd w/ 173,460 gal fluid and 250,540# 20/40 sand (01/19/2008)

PBTD 8065'

TD 8164'

Drawn by:	Date:			
Tyler Barela	01/12/2017			