

EXTRACTION OIL & GAS

WELD COUNTY, COLORADO (NAD 83)

SW SW SEC. 22 T4N R68W 6th P.M.

HFE 6

ORIGINAL WELLBORE

11 January, 2017

Plan: PROPOSAL #3





Project: WELD COUNTY, COLORADO (NAD 83)
Site: SW SW SEC. 22 T4N R68W 6th P.M.
Well: HFE 6
Wellbore: ORIGINAL WELLBORE
Design: PROPOSAL #3

ANNOTATIONS

TVD	MD	Inc	Azi	+N/-S	+E/-W	VSect	Dep	Annotation
0.0	0.0	0.00	0.00	0.0	0.0	0.0	0.0	SHL: 1125ft FSL & 1019ft FWL of Sec 22
2100.0	2100.0	0.00	0.00	0.0	0.0	0.0	0.0	START NUDGE (2°/100ft BUR)
3029.9	3047.1	18.94	274.49	12.1	-154.7	-153.8	155.1	EOB TO 18.94° INC
5437.2	5592.2	18.94	274.49	76.8	-978.3	-972.9	981.3	END OF TANGENT
6367.1	6539.2	0.00	274.49	88.9	-1132.9	-1126.6	1136.4	EOD TO VERTICAL
6397.1	6569.2	0.00	0.00	88.9	-1132.9	-1126.6	1136.4	KOP (10°/100ft BUR)
6970.0	7469.1	90.00	88.69	102.0	-560.2	-554.0	1709.2	HZ LP: 1240ft FSL & 460ft FWL of Sec 22
6970.0	11862.4	90.00	88.70	202.1	3832.0	3837.3	6102.5	BHL: 1240ft FSL & 460ft FEL of Sec 22

WELLBORE TARGET DETAILS (LAT/LONG)


Name	TVD	+N/-S	+E/-W	Latitude	Longitude
KOP - HFE 6 (P3)	6397.1	88.9	-1132.9	40.294965	-104.999167
HZ LP - HFE 6 (P3)	6970.0	102.0	-560.1	40.295001	-104.997114
BHL - HFE 6 (P3)	6970.0	202.1	3832.0	40.295275	-104.981369

FORMATION TOP DETAILS

TVDPath	MDPath	Formation
3285.0	3316.8	PARKMAN
3925.0	3993.4	SUSSEX
4340.0	4432.2	SHANNON
6780.0	6988.6	SHARON SPRINGS
6830.0	7060.0	NIOBRARA
6970.0	7469.1	NIO C TOP





PROPOSED LOCAL COORDINATES:

SHL: 1125ft FSL & 1019ft FWL of Sec 29
HZ LP: 1240ft FSL & 460ft FWL of Sec 22
BHL: 1240ft FSL & 460ft FEL of Sec 22



Azimuths to True North
Magnetic North: 8.38°

Magnetic Field
Strength: 52370.0nT
Dip Angle: 66.75°
Date: 14/12/2016
Model: IGRF2015



Planning Report



Database:	EDM 5000.1 Single User Db	Local Co-ordinate Reference:	Well HFE 6
Company:	EXTRACTION OIL & GAS	TVD Reference:	KB-EST @ 4934.0usft
Project:	WELD COUNTY, COLORADO (NAD 83)	MD Reference:	KB-EST @ 4934.0usft
Site:	SW SW SEC. 22 T4N R68W 6th P.M.	North Reference:	True
Well:	HFE 6	Survey Calculation Method:	Minimum Curvature
Wellbore:	ORIGINAL WELLBORE		
Design:	PROPOSAL #3		

Project	WELD COUNTY, COLORADO (NAD 83)		
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	Colorado Northern Zone		Using geodetic scale factor

Site	SW SW SEC. 22 T4N R68W 6th P.M.		
Site Position:		Northing:	1,350,393.80 usft
From:	Lat/Long	Easting:	3,140,798.83 usft
Position Uncertainty:	0.0 usft	Slot Radius:	1.10000ft
		Latitude:	40.294131
		Longitude:	-104.995243
		Grid Convergence:	0.33 °

Well	HFE 6		
Well Position	+N/-S	214.9 usft	Northing: 1,350,608.94 usfi
	+E/-W	38.2 usft	Easting: 3,140,835.82 usfi
Position Uncertainty	0.0 usft	Wellhead Elevation:	usfi
		Latitude:	40.294721
		Longitude:	-104.995106
		Ground Level:	4,918.0 usft

Wellbore	ORIGINAL WELLBORE				
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF2015	14/12/2016	8.38	66.75	52,370

Design	PROPOSAL #3				
Audit Notes:					
Version:	Phase:	PROTOTYPE	Tie On Depth:	0.0	
Vertical Section:	Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)	Direction (°)	
	0.0	0.0	0.0	86.98	

Plan Sections											
MD (usft)	Inc (°)	Azi (°)	Vertical Depth	SS (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100usf)	Build Rate (°/100usf)	Turn Rate (°/100usf)	TFO (°)	Target
0.0	0.00	0.00	0.0	-4,934.0	0.0	0.0	0.00	0.00	0.00	0.00	
2,100.0	0.00	0.00	2,100.0	-2,834.0	0.0	0.0	0.00	0.00	0.00	0.00	
3,047.1	18.94	274.49	3,029.9	-1,904.1	12.1	-154.6	2.00	2.00	0.00	274.49	
5,592.2	18.94	274.49	5,437.2	503.2	76.8	-978.3	0.00	0.00	0.00	0.00	
6,539.2	0.00	0.00	6,367.1	1,433.1	88.9	-1,132.9	2.00	-2.00	0.00	180.00	
6,569.2	0.00	0.00	6,397.1	1,463.1	88.9	-1,132.9	0.00	0.00	0.00	0.00	KOP - HFE 6 (P3)
7,469.1	90.00	88.69	6,970.0	2,036.0	102.0	-560.1	10.00	10.00	9.86	88.69	HZ LP - HFE 6 (P3)
11,862.4	90.00	88.70	6,970.0	2,036.0	202.1	3,832.0	0.00	0.00	0.00	99.87	BHL - HFE 6 (P3)

Database:	EDM 5000.1 Single User Db	Local Co-ordinate Reference:	Well HFE 6
Company:	EXTRACTION OIL & GAS	TVD Reference:	KB-EST @ 4934.0usft
Project:	WELD COUNTY, COLORADO (NAD 83)	MD Reference:	KB-EST @ 4934.0usft
Site:	SW SW SEC. 22 T4N R68W 6th P.M.	North Reference:	True
Well:	HFE 6	Survey Calculation Method:	Minimum Curvature
Wellbore:	ORIGINAL WELLBORE		
Design:	PROPOSAL #3		

Planned Survey

MD (usft)	Inc (°)	Azi (°)	TVD (usft)	SS (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
SHL: 1125ft FSL & 1019ft FWL of Sec 22										
0.0	0.00	0.00	0.0	4,934.00	0.0	0.0	0.0	0.00	0.00	0.00
100.0	0.00	0.00	100.0	4,834.00	0.0	0.0	0.0	0.00	0.00	0.00
200.0	0.00	0.00	200.0	4,734.00	0.0	0.0	0.0	0.00	0.00	0.00
300.0	0.00	0.00	300.0	4,634.00	0.0	0.0	0.0	0.00	0.00	0.00
400.0	0.00	0.00	400.0	4,534.00	0.0	0.0	0.0	0.00	0.00	0.00
500.0	0.00	0.00	500.0	4,434.00	0.0	0.0	0.0	0.00	0.00	0.00
600.0	0.00	0.00	600.0	4,334.00	0.0	0.0	0.0	0.00	0.00	0.00
700.0	0.00	0.00	700.0	4,234.00	0.0	0.0	0.0	0.00	0.00	0.00
800.0	0.00	0.00	800.0	4,134.00	0.0	0.0	0.0	0.00	0.00	0.00
900.0	0.00	0.00	900.0	4,034.00	0.0	0.0	0.0	0.00	0.00	0.00
1,000.0	0.00	0.00	1,000.0	3,934.00	0.0	0.0	0.0	0.00	0.00	0.00
1,100.0	0.00	0.00	1,100.0	3,834.00	0.0	0.0	0.0	0.00	0.00	0.00
1,200.0	0.00	0.00	1,200.0	3,734.00	0.0	0.0	0.0	0.00	0.00	0.00
1,300.0	0.00	0.00	1,300.0	3,634.00	0.0	0.0	0.0	0.00	0.00	0.00
1,400.0	0.00	0.00	1,400.0	3,534.00	0.0	0.0	0.0	0.00	0.00	0.00
1,500.0	0.00	0.00	1,500.0	3,434.00	0.0	0.0	0.0	0.00	0.00	0.00
1,600.0	0.00	0.00	1,600.0	3,334.00	0.0	0.0	0.0	0.00	0.00	0.00
1,700.0	0.00	0.00	1,700.0	3,234.00	0.0	0.0	0.0	0.00	0.00	0.00
1,800.0	0.00	0.00	1,800.0	3,134.00	0.0	0.0	0.0	0.00	0.00	0.00
1,900.0	0.00	0.00	1,900.0	3,034.00	0.0	0.0	0.0	0.00	0.00	0.00
2,000.0	0.00	0.00	2,000.0	2,934.00	0.0	0.0	0.0	0.00	0.00	0.00
START NUDGE (2°/100ft BUR)										
2,100.0	0.00	0.00	2,100.0	2,834.00	0.0	0.0	0.0	0.00	0.00	0.00
2,200.0	2.00	274.49	2,200.0	2,734.02	0.1	-1.7	-1.7	2.00	2.00	0.00
2,300.0	4.00	274.49	2,299.8	2,634.16	0.5	-7.0	-6.9	2.00	2.00	0.00
2,400.0	6.00	274.49	2,399.5	2,534.55	1.2	-15.6	-15.6	2.00	2.00	0.00
2,500.0	8.00	274.49	2,498.7	2,435.30	2.2	-27.8	-27.6	2.00	2.00	0.00
2,600.0	10.00	274.49	2,597.5	2,336.53	3.4	-43.4	-43.1	2.00	2.00	0.00
2,700.0	12.00	274.49	2,695.6	2,238.38	4.9	-62.4	-62.1	2.00	2.00	0.00
2,800.0	14.00	274.49	2,793.1	2,140.94	6.7	-84.8	-84.4	2.00	2.00	0.00
2,900.0	16.00	274.49	2,889.6	2,044.36	8.7	-110.6	-110.0	2.00	2.00	0.00
3,000.0	18.00	274.49	2,985.3	1,948.73	11.0	-139.8	-139.0	2.00	2.00	0.00
EOB TO 18.94° INC										
3,047.1	18.94	274.49	3,029.9	1,904.06	12.1	-154.7	-153.8	2.00	2.00	0.00
3,100.0	18.94	274.49	3,080.0	1,854.02	13.5	-171.8	-170.8	0.00	0.00	0.00
3,200.0	18.94	274.49	3,174.6	1,759.44	16.0	-204.1	-203.0	0.00	0.00	0.00
3,300.0	18.94	274.49	3,269.1	1,664.85	18.6	-236.5	-235.2	0.00	0.00	0.00
PARKMAN										
3,316.8	18.94	274.49	3,285.0	1,649.00	19.0	-241.9	-240.6	0.00	0.00	0.00
3,400.0	18.94	274.49	3,363.7	1,570.27	21.1	-268.9	-267.4	0.00	0.00	0.00
3,500.0	18.94	274.49	3,458.3	1,475.68	23.6	-301.2	-299.6	0.00	0.00	0.00
3,600.0	18.94	274.49	3,552.9	1,381.10	26.2	-333.6	-331.7	0.00	0.00	0.00
3,700.0	18.94	274.49	3,647.5	1,286.51	28.7	-365.9	-363.9	0.00	0.00	0.00
3,800.0	18.94	274.49	3,742.1	1,191.93	31.3	-398.3	-396.1	0.00	0.00	0.00
3,900.0	18.94	274.49	3,836.7	1,097.34	33.8	-430.7	-428.3	0.00	0.00	0.00
SUSSEX										
3,993.4	18.94	274.49	3,925.0	1,009.00	36.2	-460.9	-458.3	0.00	0.00	0.00
4,000.0	18.94	274.49	3,931.2	1,002.76	36.3	-463.0	-460.5	0.00	0.00	0.00
4,100.0	18.94	274.49	4,025.8	908.17	38.9	-495.4	-492.6	0.00	0.00	0.00
4,200.0	18.94	274.49	4,120.4	813.59	41.4	-527.7	-524.8	0.00	0.00	0.00
4,300.0	18.94	274.49	4,215.0	719.00	44.0	-560.1	-557.0	0.00	0.00	0.00
4,400.0	18.94	274.49	4,309.6	624.42	46.5	-592.5	-589.2	0.00	0.00	0.00

Database:	EDM 5000.1 Single User Db	Local Co-ordinate Reference:	Well HFE 6
Company:	EXTRACTION OIL & GAS	TVD Reference:	KB-EST @ 4934.0usft
Project:	WELD COUNTY, COLORADO (NAD 83)	MD Reference:	KB-EST @ 4934.0usft
Site:	SW SW SEC. 22 T4N R68W 6th P.M.	North Reference:	True
Well:	HFE 6	Survey Calculation Method:	Minimum Curvature
Wellbore:	ORIGINAL WELLBORE		
Design:	PROPOSAL #3		

Planned Survey

MD (usft)	Inc (°)	Azi (°)	TVD (usft)	SS (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
SHANNON										
4,432.2	18.94	274.49	4,340.0	594.00	47.3	-602.9	-599.5	0.00	0.00	0.00
4,500.0	18.94	274.49	4,404.2	529.83	49.0	-624.8	-621.4	0.00	0.00	0.00
4,600.0	18.94	274.49	4,498.8	435.25	51.6	-657.2	-653.6	0.00	0.00	0.00
4,700.0	18.94	274.49	4,593.3	340.66	54.1	-689.5	-685.7	0.00	0.00	0.00
4,800.0	18.94	274.49	4,687.9	246.07	56.6	-721.9	-717.9	0.00	0.00	0.00
4,900.0	18.94	274.49	4,782.5	151.49	59.2	-754.3	-750.1	0.00	0.00	0.00
5,000.0	18.94	274.49	4,877.1	56.90	61.7	-786.6	-782.3	0.00	0.00	0.00
5,100.0	18.94	274.49	4,971.7	-37.68	64.3	-819.0	-814.5	0.00	0.00	0.00
5,200.0	18.94	274.49	5,066.3	-132.27	66.8	-851.3	-846.6	0.00	0.00	0.00
5,300.0	18.94	274.49	5,160.9	-226.85	69.3	-883.7	-878.8	0.00	0.00	0.00
5,400.0	18.94	274.49	5,255.4	-321.44	71.9	-916.1	-911.0	0.00	0.00	0.00
5,500.0	18.94	274.49	5,350.0	-416.02	74.4	-948.4	-943.2	0.00	0.00	0.00
END OF TANGENT										
5,592.2	18.94	274.49	5,437.2	-503.23	76.8	-978.3	-972.9	0.00	0.00	0.00
5,600.0	18.78	274.49	5,444.6	-510.61	77.0	-980.8	-975.4	2.01	-2.01	0.00
5,700.0	16.78	274.49	5,539.8	-605.83	79.4	-1,011.2	-1,005.6	2.00	-2.00	0.00
5,800.0	14.78	274.49	5,636.1	-702.05	81.5	-1,038.3	-1,032.6	2.00	-2.00	0.00
5,900.0	12.78	274.49	5,733.2	-799.17	83.3	-1,062.1	-1,056.2	2.00	-2.00	0.00
6,000.0	10.78	274.49	5,831.1	-897.05	84.9	-1,082.5	-1,076.5	2.00	-2.00	0.00
6,100.0	8.78	274.49	5,929.6	-995.59	86.3	-1,099.4	-1,093.3	2.00	-2.00	0.00
6,200.0	6.78	274.49	6,028.7	-1,094.67	87.3	-1,112.9	-1,106.8	2.00	-2.00	0.00
6,300.0	4.78	274.49	6,128.2	-1,194.15	88.1	-1,122.9	-1,116.7	2.00	-2.00	0.00
6,400.0	2.78	274.49	6,227.9	-1,293.93	88.6	-1,129.5	-1,123.3	2.00	-2.00	0.00
6,500.0	0.78	274.49	6,327.9	-1,393.88	88.9	-1,132.6	-1,126.4	2.00	-2.00	0.00
EOD TO VERTICAL										
6,539.2	0.00	274.49	6,367.1	-1,433.07	88.9	-1,132.9	-1,126.6	2.00	-2.00	0.00
KOP (10°/100ft BUR)										
6,569.2	0.00	0.00	6,397.1	-1,463.07	88.9	-1,132.9	-1,126.6	0.00	0.00	0.00
6,600.0	3.08	88.69	6,427.9	-1,493.86	88.9	-1,132.1	-1,125.8	9.99	9.99	0.00
6,700.0	13.08	88.69	6,526.7	-1,592.74	89.2	-1,118.0	-1,111.8	10.00	10.00	0.00
6,800.0	23.08	88.69	6,621.7	-1,687.68	90.0	-1,087.1	-1,080.8	10.00	10.00	0.00
6,900.0	33.08	88.69	6,709.8	-1,775.80	91.0	-1,040.1	-1,033.8	10.00	10.00	0.00
SHARON SPRINGS										
6,988.6	41.94	88.69	6,780.0	-1,846.00	92.3	-986.2	-980.0	10.00	10.00	0.00
7,000.0	43.08	88.69	6,788.4	-1,854.41	92.4	-978.5	-972.2	10.00	10.00	0.00
NIOBRARA										
7,060.0	49.08	88.69	6,830.0	-1,896.00	93.4	-935.3	-929.1	10.00	10.00	0.00
7,100.0	53.08	88.69	6,855.1	-1,921.14	94.1	-904.2	-898.0	10.00	10.00	0.00
7,200.0	63.08	88.69	6,907.9	-1,973.94	96.1	-819.4	-813.2	10.00	10.00	0.00
7,300.0	73.08	88.69	6,945.2	-2,011.21	98.2	-726.8	-720.6	10.00	10.00	0.00
7,400.0	83.09	88.69	6,965.8	-2,031.83	100.4	-629.1	-622.9	10.00	10.00	0.00
HZ LP: 1240ft FSL & 460ft FWL of Sec 22 - NIO C TOP										
7,469.1	90.00	88.69	6,970.0	-2,036.00	102.0	-560.1	-554.0	10.00	10.00	0.00
7,500.0	90.00	88.69	6,970.0	-2,036.00	102.7	-529.3	-523.1	0.00	0.00	0.00
7,600.0	90.00	88.69	6,970.0	-2,036.00	105.0	-429.3	-423.2	0.00	0.00	0.00
7,700.0	90.00	88.69	6,970.0	-2,036.00	107.3	-329.3	-323.2	0.00	0.00	0.00
7,800.0	90.00	88.69	6,970.0	-2,035.99	109.6	-229.4	-223.3	0.00	0.00	0.00
7,900.0	90.00	88.69	6,970.0	-2,035.99	111.9	-129.4	-123.3	0.00	0.00	0.00
8,000.0	90.00	88.69	6,970.0	-2,035.99	114.2	-29.4	-23.4	0.00	0.00	0.00
8,100.0	90.00	88.69	6,970.0	-2,035.99	116.5	70.5	76.6	0.00	0.00	0.00
8,200.0	90.00	88.69	6,970.0	-2,035.99	118.7	170.5	176.5	0.00	0.00	0.00
8,300.0	90.00	88.69	6,970.0	-2,035.99	121.0	270.5	276.5	0.00	0.00	0.00

Planning Report



Database:	EDM 5000.1 Single User Db	Local Co-ordinate Reference:	Well HFE 6
Company:	EXTRACTION OIL & GAS	TVD Reference:	KB-EST @ 4934.0usft
Project:	WELD COUNTY, COLORADO (NAD 83)	MD Reference:	KB-EST @ 4934.0usft
Site:	SW SW SEC. 22 T4N R68W 6th P.M.	North Reference:	True
Well:	HFE 6	Survey Calculation Method:	Minimum Curvature
Wellbore:	ORIGINAL WELLBORE		
Design:	PROPOSAL #3		

Planned Survey										
MD (usft)	Inc (°)	Azi (°)	TVD (usft)	SS (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
8,400.0	90.00	88.69	6,970.0	-2,035.99	123.3	370.5	376.5	0.00	0.00	0.00
8,500.0	90.00	88.69	6,970.0	-2,035.98	125.6	470.4	476.4	0.00	0.00	0.00
8,600.0	90.00	88.69	6,970.0	-2,035.98	127.9	570.4	576.4	0.00	0.00	0.00
8,700.0	90.00	88.69	6,970.0	-2,035.98	130.2	670.4	676.3	0.00	0.00	0.00
8,800.0	90.00	88.69	6,970.0	-2,035.98	132.5	770.4	776.3	0.00	0.00	0.00
8,900.0	90.00	88.69	6,970.0	-2,035.98	134.7	870.3	876.2	0.00	0.00	0.00
9,000.0	90.00	88.69	6,970.0	-2,035.98	137.0	970.3	976.2	0.00	0.00	0.00
9,100.0	90.00	88.69	6,970.0	-2,035.98	139.3	1,070.3	1,076.1	0.00	0.00	0.00
9,200.0	90.00	88.69	6,970.0	-2,035.98	141.6	1,170.3	1,176.1	0.00	0.00	0.00
9,300.0	90.00	88.69	6,970.0	-2,035.98	143.9	1,270.2	1,276.1	0.00	0.00	0.00
9,400.0	90.00	88.69	6,970.0	-2,035.98	146.1	1,370.2	1,376.0	0.00	0.00	0.00
9,500.0	90.00	88.69	6,970.0	-2,035.98	148.4	1,470.2	1,476.0	0.00	0.00	0.00
9,600.0	90.00	88.69	6,970.0	-2,035.98	150.7	1,570.2	1,575.9	0.00	0.00	0.00
9,700.0	90.00	88.69	6,970.0	-2,035.98	153.0	1,670.1	1,675.9	0.00	0.00	0.00
9,800.0	90.00	88.69	6,970.0	-2,035.98	155.3	1,770.1	1,775.8	0.00	0.00	0.00
9,900.0	90.00	88.69	6,970.0	-2,035.98	157.5	1,870.1	1,875.8	0.00	0.00	0.00
10,000.0	90.00	88.70	6,970.0	-2,035.98	159.8	1,970.1	1,975.7	0.00	0.00	0.00
10,100.0	90.00	88.70	6,970.0	-2,035.98	162.1	2,070.0	2,075.7	0.00	0.00	0.00
10,200.0	90.00	88.70	6,970.0	-2,035.98	164.4	2,170.0	2,175.6	0.00	0.00	0.00
10,300.0	90.00	88.70	6,970.0	-2,035.98	166.6	2,270.0	2,275.6	0.00	0.00	0.00
10,400.0	90.00	88.70	6,970.0	-2,035.98	168.9	2,370.0	2,375.6	0.00	0.00	0.00
10,500.0	90.00	88.70	6,970.0	-2,035.98	171.2	2,469.9	2,475.5	0.00	0.00	0.00
10,600.0	90.00	88.70	6,970.0	-2,035.98	173.5	2,569.9	2,575.5	0.00	0.00	0.00
10,700.0	90.00	88.70	6,970.0	-2,035.98	175.7	2,669.9	2,675.4	0.00	0.00	0.00
10,800.0	90.00	88.70	6,970.0	-2,035.98	178.0	2,769.8	2,775.4	0.00	0.00	0.00
10,900.0	90.00	88.70	6,970.0	-2,035.99	180.3	2,869.8	2,875.3	0.00	0.00	0.00
11,000.0	90.00	88.70	6,970.0	-2,035.99	182.6	2,969.8	2,975.3	0.00	0.00	0.00
11,100.0	90.00	88.70	6,970.0	-2,035.99	184.8	3,069.8	3,075.2	0.00	0.00	0.00
11,200.0	90.00	88.70	6,970.0	-2,035.99	187.1	3,169.7	3,175.2	0.00	0.00	0.00
11,300.0	90.00	88.70	6,970.0	-2,035.99	189.4	3,269.7	3,275.2	0.00	0.00	0.00
11,400.0	90.00	88.70	6,970.0	-2,035.99	191.6	3,369.7	3,375.1	0.00	0.00	0.00
11,500.0	90.00	88.70	6,970.0	-2,035.99	193.9	3,469.7	3,475.1	0.00	0.00	0.00
11,600.0	90.00	88.70	6,970.0	-2,036.00	196.2	3,569.6	3,575.0	0.00	0.00	0.00
11,700.0	90.00	88.70	6,970.0	-2,036.00	198.4	3,669.6	3,675.0	0.00	0.00	0.00
11,800.0	90.00	88.70	6,970.0	-2,036.00	200.7	3,769.6	3,774.9	0.00	0.00	0.00
BHL: 1240ft FSL & 460ft FEL of Sec 22										
11,862.4	90.00	88.70	6,970.0	-2,036.00	202.1	3,832.0	3,837.3	0.00	0.00	0.00

Formations						
MD (usft)	TVD (usft)	Name	Lithology	Dip (°)	Dip Direction (°)	
3,316.8	3,285.0	PARKMAN				
3,993.4	3,925.0	SUSSEX				
4,432.2	4,340.0	SHANNON				
6,988.6	6,780.0	SHARON SPRINGS				
7,060.0	6,830.0	NIOBRARA				
7,469.1	6,970.0	NIO C TOP				

Database:	EDM 5000.1 Single User Db	Local Co-ordinate Reference:	Well HFE 6
Company:	EXTRACTION OIL & GAS	TVD Reference:	KB-EST @ 4934.0usft
Project:	WELD COUNTY, COLORADO (NAD 83)	MD Reference:	KB-EST @ 4934.0usft
Site:	SW SW SEC. 22 T4N R68W 6th P.M.	North Reference:	True
Well:	HFE 6	Survey Calculation Method:	Minimum Curvature
Wellbore:	ORIGINAL WELLBORE		
Design:	PROPOSAL #3		

Plan Annotations

MD (usft)	TVD (usft)	Local Coordinates		Comment
		+N/-S (usft)	+E/-W (usft)	
0.0	0.0	0.0	0.0	SHL: 1125ft FSL & 1019ft FWL of Sec 22
2,100.0	2,100.0	0.0	0.0	START NUDGE (2°/100ft BUR)
3,047.1	3,029.9	12.1	-154.7	EOB TO 18.94° INC
5,592.2	5,437.2	76.8	-978.3	END OF TANGENT
6,539.2	6,367.1	88.9	-1,132.9	EOD TO VERTICAL
6,569.2	6,397.1	88.9	-1,132.9	KOP (10°/100ft BUR)
7,469.1	6,970.0	102.0	-560.2	HZ LP: 1240ft FSL & 460ft FWL of Sec 22
11,862.4	6,970.0	202.1	3,832.0	BHL: 1240ft FSL & 460ft FEL of Sec 22