

| | | | | |
|-------------------------------------|-------------------------------------|-------------------------------|---|---------------------------------------|
| Well Configuration Type DEVIATED | Original KB Elevation (ft) 4,699 | KB - GL / MSL (ftKB) 14.00 | KB-Casing Flange Distance (ft) 14.00 | KB-Tubing Head Distance (ft) 10.00 |
|-------------------------------------|-------------------------------------|-------------------------------|---|---------------------------------------|

Directions To Well
WCR 54, SOUTH 0.2 MILE ON WCR 51, WEST 1/10, N 1/10 INTO.'

| Des | OD (in) | Top (ftKB) | Btm (ftKB) | Run Date |
|-------------------------|---------|------------|------------|-----------------|
| Retrievable Bridge Plug | 3.99 | 6,672.0 | 6,680.4 | 1/12/2017 12:00 |
| Sand plug | 3.99 | 6,667.8 | 6,672.0 | 1/12/2017 12:30 |

| | | |
|--------------------------------|------------------------------|--|
| Report Start Date 1/12/2017 | Report End Date 1/12/2017 | Operations Summary ...IWP=0.0 TBG./0.0 CSG., SURF=0.0 CONDUCT SAFETY MEETING, PROCEED TO TRIPIH W/ 216 JNTS, SET RBP @ 6,680.36'FT KB+/-, (SET WITH 15.00'FT OUT TOP OF SLIPS), MU KELLY LINES, CIRCULATE/VACATE PRESENT WELLBORE GAS OBSERVING REVERSE CIRCULATING PROCESS, CLOSE TIW VALVE, MU KELLY LINES TO ANNULUS, PRESSURE TEST RBP/ANNULUS/WH TO 2,500.0 FOR 15 MINS, TEST GOOD, RELEASE PRESSURES TO RIG FLAT TANK, LD 10 JNTS, SPOT 2X BAGS OF 50# SAND, MU KELLY LINES TO TBG. PUMP TBG. VOLUME 1X+2 BBLs, LD AN ADDITIONAL 10 JNTS, MU TBG. HANGER ON JNT #195, EOT @ 6,042.46'FT KB W/ BHA=EOT, LAND TBG. IN WH VIA TBG. HANGER, MU WHPINS, ND 5K BOPE, NU TOP 5K PRODUCTION FLANGE W/ INTREGAL MASTER/BALON VALVE, SECURE WELLBORE W/ SIGN (TEMPORARILY SHUT IN), RD BWS #7, SECURE WELL/LOCATION, MOL..... |
|--------------------------------|------------------------------|--|