

NOBLE ENERGY INC.
Wells Ranch USX BB 05-15
SWSE 5-5N-63W
645 FSL & 1977 FEL
WELD COUNTY, CO
Wattenberg
CURRENT WELLBORE SCHEMATIC
with PROPOSED P&A

API: 05-123-25281
COGCC #

GL Elev: 4728'
KB Elev: 4740'

Spud Date: 6/21/2007

Surface Casing :
8-5/8" 24# J-55 @ 485'
Cement: 256 sx
TOC: Surface

WW	N/A
SC	485
FH	412


685
612

No Sussex completions within 1 mile

TOC @ 1854'

Nio Top 6500'

Production Casing :
4-1/2" 11.60# M-80 @ 6971'
Cement: 820 sx
TD Date: 6/25/2007



Cut surface casing off 6'-8' below surface.

Cut production casing at 685'
Cmt to surface from 50' in csg stub (735')
with 250 sx cmt

Pump 210 sx plug through/on CICR
Cmt Coverage inside PC: 1581'
Cmt Coverage outside PC: 1310'
Set CICR at 1710'
Shoot sqz perfs at 1810'

Set CIBP at 6466' with 2 sx cement
New TOC: 6440'

Niobrara Perforations 6516'-
6532' & 6608'-6624'

Codell Perforations 6784'-6795'

TD: 6972'