

FORM
5A

Rev
06/12

State of Colorado

Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



DE	ET	OE	ES
----	----	----	----

Document Number:

400920240

Date Received:

COMPLETED INTERVAL REPORT

The completed interval Report, Form 5A, shall be submitted within thirty (30) days of completing a formation (successful or not), when a formation is temporarily abandoned or permanently abandoned, for a recompletion, reperforation or restimulation, or when a formation is commingled. Fill out a section for each formation. Attach as many pages as required to fully describe the work. List in order of completion.

1. OGCC Operator Number: <u>69175</u>	4. Contact Name: <u>Ally Gale</u>
2. Name of Operator: <u>PDC ENERGY INC</u>	Phone: <u>(303) 831-3931</u>
3. Address: <u>1775 SHERMAN STREET - STE 3000</u>	Fax: <u>(303) 860-5838</u>
City: <u>DENVER</u> State: <u>CO</u> Zip: <u>80203</u>	Email: <u>alexandria.gale@pdce.com</u>

5. API Number <u>05-123-40569-00</u>	6. County: <u>WELD</u>
7. Well Name: <u>Rieder</u>	Well Number: <u>18T-221</u>
8. Location: QtrQtr: <u>SESE</u> Section: <u>18</u> Township: <u>4N</u> Range: <u>67W</u> Meridian: <u>6</u>	
9. Field Name: <u>WATTENBERG</u> Field Code: <u>90750</u>	

Completed Interval

FORMATION: NIOBRARA Status: PRODUCING Treatment Type: FRACTURE STIMULATION

Treatment Date: 09/26/2015 End Date: 09/28/2015 Date of First Production this formation: 10/10/2015
Perforations Top: 7413 Bottom: 11543 No. Holes: Hole size:

Provide a brief summary of the formation treatment: Open Hole:

20 Stage Sliding Sleeve
Total Fluid 77,345 bbls
Gel Fluid: 56,277 bbls
Slickwater Fluid: 21,068 bbls
Total Proppant 3,954,700 lbs
Silica Proppant: 3,954,700 lbs
Method for determining flowback volume: measuring flowback tank volumes

This formation is commingled with another formation: Yes No

Total fluid used in treatment (bbl): 77345 Max pressure during treatment (psi): 4249
Total gas used in treatment (mcf): Fluid density at initial fracture (lbs/gal): 8.34
Type of gas used in treatment: Min frac gradient (psi/ft): 0.89
Total acid used in treatment (bbl): Number of staged intervals: 20
Recycled water used in treatment (bbl): Flowback volume recovered (bbl): 1936
Fresh water used in treatment (bbl): 77345 Disposition method for flowback: DISPOSAL
Total proppant used (lbs): 3954700 Rule 805 green completion techniques were utilized:

Reason why green completion not utilized:

Fracture stimulations must be reported on FracFocus.org

Test Information:

Date: 10/16/2015 Hours: 24 Bbl oil: 255 Mcf Gas: 408 Bbl H2O: 620
Calculated 24 hour rate: Bbl oil: 255 Mcf Gas: 408 Bbl H2O: 620 GOR: 1600
Test Method: Flowing Casing PSI: 1410 Tubing PSI: 1350 Choke Size: 16/64
Gas Disposition: SOLD Gas Type: WET Btu Gas: 1266 API Gravity Oil: 50
Tubing Size: 2 + 3/8 Tubing Setting Depth: 7105 Tbg setting date: 10/09/2015 Packer Depth:

Reason for Non-Production:

Date formation Abandoned: Squeeze: Yes No If yes, number of sacks cmt

** Bridge Plug Depth: ** Sacks cement on top: ** Wireline and Cement Job Summary must be attached.

Comment:
Swell Packer set at 7413'

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.
Signed: Print Name: Ally Gale
Title: Regulatory Technician I Date: Email alexandria.gale@pdce.com

Attachment Check List

Att Doc Num	Name

Total Attach: 0 Files

General Comments

User Group

Comment

Comment Date

		Stamp Upon Approval
--	--	---------------------

Total: 0 comment(s)