

Equipment Description

- 1) Wellhead (2-9/16" 5M psi Tree)
- 2) 4' x 10' Horizontal 3 Phase Low Pressure Separator (150 psi)
- 3) 4' x 27' Vertical Heater Treater (125 psi)
- 4) Tank Battery (3 - 400 bbl Oil Tanks + 3 - 400 bbl Fiberglass Water Tanks)
- 5) Flair Stack with Automatic Igniter

Flowlines Description

- 1) Wellhead to LPS - 2.5" Sch 40, 0.203" wall, seamless welded flowline
- 2) LPS (Gas) to Flare Line - 2.0" Grade "A", 0.109" wall, ERW line pipe
- 3) LPS (Oil) to Heater Treater & Oil Storage Tanks - 2.0" Grade "A", 0.109" wall, ERW line pipe
- 4) LPS (Water) To Water Storage Tanks - 3" Grade "A", 0.109" wall, ERW line pipe
- 5) Heater Treater (Gas) to Flare Line - 2.0" Grade "A", 0.109" wall, ERW line pipe
- 6) Heater Treater (Oil) to Oil Storage Tanks - 2.0" Grade "A", 0.109" wall, ERW line pipe
- 7) Heater Treater (Water) to Water Storage Tanks - 3.0" Grade "A", 0.109" wall, ERW line pipe
- 8) Oil Storage Tanks Lower Equalizing Lines - 4.0" Grade "A", 0.109" wall, ERW line pipe
- 9) Oil Storage Tanks Upper Equalizing Lines - 2.0" Grade "A", 0.109" wall, ERW line pipe
- 10) Water Storage Tanks Lower Equalizing Lines - 4.0" Grade "A", 0.109" wall, ERW line pipe
- 11) Water Storage Tanks Upper Equalizing Lines - 2.0" Grade "A", 0.109" wall, ERW line pipe
- 12) Flare Line - 2.0" Grade "A", 0.109" wall, ERW line pipe

