



SRC ENERGY

**Operator:** SRC Energy  
**Well Name:** Hall 19-21  
**Legal:** NENW, Section 19, Township 6N, Range 67W  
**Location:** Weld County, CO  
**API:** 05-123-33898  
**Surface:** 8.625" 24# @ 644'                      **Hole Size:** 12.25"                      **TOC:** Surface  
**Production:** 4.5" 11.6# @ 7,147'                      **Hole Size:** 7.875"                      **TOC:** 2,030 (CBL)  
**Perforations:** 6,738' – 7,014' (Niobrara-Fort Hays-Codell)  
**TD:** 7,175'

P&A Procedure

1. Conduct pre-job safety meeting and complete daily JSA
2. Blow down well if necessary, circulate hole with treated water
3. Dig out around wellhead and check surface annulus for pressure
4. MIRU WO unit, ND wellhead, NU BOP, tally all pipe
5. TIH w/ 4-1/2", 11.6# CIBP, set at 6,663'
6. Pressure test csg to 500 psi for 15 minutes
7. Set 15 sx on top of CIBP (cover 200' above Niobrara top)
8. Cut 4.5" @ 694', and POOH
9. TIH to 744' and pump shoe plug (0' – 744')
  - a. 295 sx of 15.8# class G neat 1.15 cu./ft. yield cement
  - b. 100' out of surface casing
  - c. Wait 4 hours and tag plug
10. RDMO WO unit
11. Dig up wellhead and cut off 10' below restored ground level, top off if necessary
12. Weld on cap with ID plate, inscribed with well location, and identity
13. Backfill, clean location
14. P&A complete