

8 5/8"
Surf Csg @ 278'
TOC: Circ to Surface

Top Perf: 600'

Bot Perf : 601'

CIBP @ 650'

TOC: 2031'

Cement Plug: 2 sx

CBP: 2790'

Top Perf: 2916'

Bot Perf : 2926'

4.5" Csg set @: 2995'

TD 3018'

PBTD: 2946'

Wellbore Dia			Price #9		
Status	Producing		Operator	Stelbar Oil Corp	
Lease	Price		Zone	Niobrara	
Field	DeNova		API	05-121-10437-00	
State:	Colorado		Division:		
Location	2040' FNL & 2040' FWL, SE/4 NW/4 Sec 8-T2S-R49W, 6th PM, Washington County, CO: ? Acre Spacing				
Reference:					
KB	4,389	TVD	3018'	Orig PBTD	2946'
GL	4,383	MTD	3018'	SN	2849'

Casing	Weight/Grade	Depth	Cmt Sx	Hole	TOC
N/A Conductor					
8 5/8"	24#/K-55	278'	100	12 1/4"	Circ to Surface
4.5"	10.5#,K-55	2995'	100 sx 50/50 Poz	6 1/4"	2031'

Spud	7/5/1990		Top Perf	2916'	
Completion	8/7/1990		Bot Perf	2926'	

Perf: 2916'-2926', 10' @ 2 SPF, 20 holes. Stim w/ 40% CO2 water frac w/ 32,000 gals frac fluid, 39,000# 20/40 sand, 48,500# 10/20 sand, 10,000# 8/12 sand, 60 tons CO2

P&A procedure:- Set CIBP @ 2850' and dump 2 sx cmt on top
- Set CIBP @ 650', fill hole with water.
- Perf the 4 1/2" csg @ 600' (1'), 4 spf
- Establish circulation with water up 4 1/2"x 8 5/8" annulus
- Pump cmt down 4 1/2 csg and circ to surface through annulus (~150 sx)
- Top off well with cmt (~50 sx)
- Cut off csghead and weld on plate

Date sketch checked	**6/10/15**	by:	TWL	
Date tubulars checked	**8/3/17**	by:	TWL	

Current Tubulars

Tubing String Size	Grade	# Jnts	Type	Length, ft	Depth, ft
			KBE	6.00	6.00
2 3/8	J-55	92	Plain Tbg	2842.80	2848.80
2 3/8		1	SN	1.10	2849.90
2 3/8		1	Packer	2.00	2851.90
2 3/8	J-55	2	Plain Tbg	62.36	2914.26
					2914.26
			Bottom of Tbg String:		**2914.26**

Rods String Size	Grade	# Rods	Length, ft	Depth, ft

Latitude and Longitude Location:	
Latitude:	**39.896773**
Longitude:	**-102.8893**