



SRC ENERGY

Operator: Brandy Oilman Consultants
Well Name: South Woods 10-3
Legal: NESW, Section 10, Township 6N, Range 66W
Location: Weld County, CO
API: 05-123-12622
Surface: 8.625, 24# @ 300' (permitted) **Hole Size:** 12.25 **TOC:** Surface (calc)
Production: 4.5, 11.6# **Hole Size:** 7.875
TD: 7995'

P&A Procedure

1. Conduct pre-job safety meeting and complete daily JSA
2. Dig out to find wellhead and check pressure
3. Cut cap off, extend surface pipe to achieve ground level
4. MIRU WO unit, NU BOP, tally all pipe to be ran in well
5. If necessary, mill cement down to 400'.
6. "Wash run" to depth that the well allows
7. TOOH, remove BHA for milling
8. TIH to 6050' based off of pipe tally and pump a 150' plug (6050'-5900')
 - a. 70 sx of 15.8# class G neat 1.15 cu./ft. yield cement, (5900' – 6050')
 - b. Wait 4 hours and tag plug
9. TIH to 4100' based off of pipe tally and pump a 100' plug (4100'-4000')
 - a. 50 sx of 15.8# class G neat 1.15 cu./ft. yield cement, (4000' – 4100')
 - b. Wait 4 hours and tag plug
10. TIH to 400' based off of pipe tally and pump a 400' plug to surface (400'-0')
 - a. 185 sx of 15.8 class G neat 1.15 cu./ft yield cement (0'-400')
 - b. Wait 4 hours and tag plug
11. RDMO WO unit
12. Remove extension of surface pipe. Top off if necessary
13. Weld back on cap with ID plate, inscribed with well location, and identity
14. Backfill, clean location
15. P&A complete