



Kerr-McGee Oil & Gas Onshore LP

A subsidiary of Anadarko Petroleum Corporation

1099 18th Street
Denver, CO 80202
720-929-6000

August 25, 2017

Matt Lepore
Director, Colorado Oil and Gas Conservation Commission
Department of Natural Resources
The Chancery Building
1120 Lincoln Street, Suite 801
Denver, CO 80203

Re: Request for Exception to Rule 317.p
PAPA JO 2-25 35C-17HZ – Doc # 401195775
PAPA JO 2-25 29N-8HZ – Doc # 401195777
PAPA JO 2-25 35N-17HZ – DOC # 401195781
PAPA JO 2-25 29N2-8HZ – DOC # 401195785
PAPA JO 2-25 35N2-17HZ – DOC # 401195794
PAPA JO 2-25 29C-8HZ – DOC # 401195812
PAPA JO 2-25 35C2-17HZ – DOC # 401195814
PAPA JO 2-25 29N3-8HZ – DOC # 401195815
PAPA JO 2-25 36N-8HZ – DOC # 401195817
PAPA JO 2-25 28N-8HZ – DOC # 401195820
YELLOWHAMMER 4C-8HZ - Doc # 401130409
YELLOWHAMMER 13N-17HZ - Doc # 401130413
YELLOWHAMMER 30N2-8HZ - Doc # 401130414
YELLOWHAMMER 30N-8HZ - Doc # 401130415
YELLOWHAMMER 34C-17HZ - Doc # 401130416
YELLOWHAMMER 34N-17HZ - Doc # 401130417
Township 1 North, Range 68 West
Section 8: NWSW
Weld County, Colorado

Dear Director Lepore:

Kerr-McGee Oil & Gas Onshore LP (“KMG”) respectfully requests approval for an exception to Rule 317.p to only run a cased-hole pulsed neutron, gamma-ray, and cement bond log from the kickoff point into the surface casing on one of the first wells drilled on this multi-well location. A Cement Bond Log with cased-hole gamma-ray log will be run on production casing or on intermediate casing if production liner is run. The other wells on this multi-well location will be logged with only a cement bond log with cased-hole gamma-ray log from kickoff point into the surface casing. Rule 317.p of the Colorado Oil and Gas Commission’s Rules and Regulations requires wells to be logged with a minimum of a resistivity log with gamma ray. The above-named wells are requested to be exempt from this requirement due to the proximity of existing well(s) with acceptable resistivity logs with gamma ray. The available log(s) meet

the offsetting well requirements and have a surface location within seven hundred fifty (750) feet of the proposed well(s).

One of the first wells drilled will be logged with a cased-hole pulsed neutron, gamma-ray, and cement bond log. The other wells on this multi-well location will run a cement bond and gamma ray log from the kickoff point into the surface casing. The Drilling Completion Report (Form 5) submitted for each well will indicate that no open-hole logs were run.

The existing well(s) within seven hundred and fifty feet (750) with acceptable resistivity logs with gamma ray are listed in the table below:

Well Name	Well Number	API Number	Distance From Well(s)	Azimuth (Degrees)	COGCC Well File Document Number and log type
WOOLLEY	14-8	05-123-23214	888	214	Doc #1405007 – Induction Log
WOOLEY	23-8	05-123-23213	894	45	Doc #1382528 – Induction Log

Should you have any questions, please contact our office. Thank you for your consideration.

Sincerely,

Kerr-McGee Oil & Gas Onshore LP



Shayelyn Marshall
Regulatory Analyst