



REV: 3 10-02-17 D.COX (PAD MOVE & PAD NAME CHANGE)

NOTE: Earthwork calculations require a fill of 1.0' @ the location stake for balance. All fill is to be compacted to a minimum of 95% of the maximum dry density obtained by AASHTO method t-99.

APPROXIMATE EARTHWORK QUANTITIES	
TOTAL CUT	15,260 Cu. Yds.
FILL	15,260 Cu. Yds.
EXCESS MATERIAL	0 Cu. Yds.
EXCESS UNBALANCE (After Interim Rehabilitation)	0 Cu. Yds.

APPROXIMATE SURFACE DISTURBANCE AREAS		
	DISTANCE	ACRES
WELL SITE AREA OF MAX. DISTURBANCE	NA	±5.024
ACCESS ROAD DISTURBANCE	±169'	±0.130
TOTAL SURFACE USE AREA		±5.154

WELL TABULATION	
B11-23-24XRLNB	196' FNL 483' FEL

FINISHED GRADE ELEVATION AT WELL HEAD = 4708.2'

- NOTES:
- Round corners at 35' radius or as needed.
 - Contours shown at 2' intervals.
 - Cut slopes 3:1 (Typ.).
 - Fill slopes 4:1 (Typ.).



UELS, LLC
Corporate Office * 85 South 200 East
Vernal, UT 84078 * (435) 789-1017

BONANZA CREEK ENERGY
OPERATING COMPANY, LLC

MUSTANG U-22 PAD
NE 1/4 NE 1/4, SECTION 22, T4N, R63W, 6th P.M.
WELD COUNTY, COLORADO

SURVEYED BY	JAMES FRESHWATER	09-01-17	SCALE
DRAWN BY	M.D.	05-08-17	1" = 60'

INITIAL PLAT