



SRC ENERGY

Operator: SRC Energy
Well Name: Aufrect N 02-10
Legal: NWSE, Section 2, Township 5N, Range 67W
Location: Weld County, CO
API: 05-123-26505
Surface: 8.625" 24# @ 909' **Hole Size:** 12.25" **TOC:** Surface
Production: 4.5" 11.6# @ 7,835' **Hole Size:** 7.875" **TOC:** 1,840' (CBL)
Perforations: 7,213' – 7,233' (Codell)
TD: 7,840'

P&A Procedure

1. Conduct pre-job safety meeting and complete daily JSA
2. Blow down well if necessary, circulate hole with treated water
3. Dig out around wellhead and perform bradenhead test
4. MIRU WO unit, ND wellhead, NU BOP, tally all pipe
5. TIH w/ 4-1/2 11.6# CIBP, set at 7138'
6. Pressure test casing to 500 psi for 15 minutes
7. Set 43 sx on top of CIBP (cover 200' above Niobrara top)
8. Cut 4.5" @ 1009', and POOH
9. TIH to 1059' and pump stub plug (0' – 1059')
 - a. 409 sx of 15.8# class G neat 1.15 cu./ft. yield cement
 - b. 150' out of surface casing
 - c. Wait 4 hours and tag plug
10. RDMO WO unit
11. Dig up wellhead and cut off 10' below restored ground level, top off if necessary
12. Weld on cap with ID plate, inscribed with well location, and identity
13. Backfill, clean location
14. P&A complete