



SRC ENERGY

**Operator:** SRC Energy  
**Well Name:** Aufrect N 2-16  
**Legal:** SESE, Section 2, Township 5N, Range 67W  
**Location:** Weld County, CO  
**API:** 05-123-26503  
**Surface:** 8.625" 24# @ 906' **Hole Size:** 12.25" **TOC:** Surface  
**Production:** 4.5" 11.6# @ 7,810' **Hole Size:** 7.875" **TOC:** 980' (CBL)  
**Perforations:** 7,182' – 7,204' (Codell)  
**TD:** 7,813'

P&A Procedure

1. Conduct pre-job safety meeting and complete daily JSA
2. Blow down well if necessary, circulate hole with treated water
3. Dig out around wellhead and perform bradenhead test
4. MIRU WO unit, ND wellhead, NU BOP, tally all pipe
5. TIH w/ 4-1/2 11.6# CIBP, set at 7107'
6. Pressure test casing to 500 psi for 15 minutes
7. Set 42 sx on top of CIBP (cover 200' above Niobrara top)
8. TIH to 960' and perforate casing
  - a. Circulate 258 sx through perforations to create 960' annulus plug
9. TIH to 960' and pump casing plug (0' – 960')
  - a. 92 sx of 15.8# class G neat 1.15 cu./ft. yield cement
  - b. Wait 4 hours and tag plug
10. RDMO WO unit
11. Dig up wellhead and cut off 10' below restored ground level, top off if necessary
12. Weld on cap with ID plate, inscribed with well location, and identity
13. Backfill, clean location
14. P&A complete