



SRC ENERGY

Operator: SRC Energy
Well Name: Aufrecht N 02-09
Legal: NESE, Section 2, Township 5N, Range 67W
Location: Weld County, CO
API: 05-123-26506
Surface: 8.625" 24# @ 913' **Hole Size:** 12.25" **TOC:** Surface
Production: 4.5" 11.6# @ 7,357' **Hole Size:** 7.875" **TOC:** 563' (CBL)
Perforations: 7,204' – 7,223' (Codell)
TD: 7,361'

P&A Procedure

1. Conduct pre-job safety meeting and complete daily JSA
2. Blow down well if necessary, circulate hole with treated water
3. Dig out around wellhead and perform bradenhead test
4. MIRU WO unit, ND wellhead, NU BOP, tally all pipe
5. TIH w/ 4-1/2 11.6# CIBP, set at 7129'
6. Pressure test casing to 500 psi for 15 minutes
7. Set 43 sx on top of CIBP (cover 200' above Niobrara top)
8. TIH to 550' and perforate casing
9. TIH to 963'
 - a. Circulate 148 sx through perforations to create 550' annulus plug
 - b. Pump 92 sx to create casing plug (0' – 963')
 - c. Wait 4 hours and tag plug
10. RDMO WO unit
11. Dig up wellhead and cut off 10' below restored ground level, top off if necessary
12. Weld on cap with ID plate, inscribed with well location, and identity
13. Backfill, clean location
14. P&A complete