



# Bison Oil Well Cementing Single Cement Surface Pipe

Date: 7/4/2017  
 Invoice #: 300104  
 API#: 05-123-44796  
 Foreman: JASON KELEHER

**Customer:** Anadarko Petroleum Corporation  
**Well Name:** CANNON 29N-4HZ

County: Weld  
 State: Colorado  
 Sec: 33  
 Twp: 3N  
 Range: 65W  
 Consultant: BRYAN  
 Rig Name & Number: CARTEL 88  
 Distance To Location: 24  
 Units On Location: 4028-3106,4034-3213,4020-3217  
 Time Requested: 1930  
 Time Arrived On Location: 1800  
 Time Left Location:

WELL DATA	Cement Data
Casing Size OD (in) : 9.625	Cement Name: BFN III
Casing Weight (lb) : 36.00	Cement Density (lb/gal) : 14.2
Casing Depth (ft.) : 1,862	Cement Yield (cuft) : 1.48
Total Depth (ft) : 1872	Gallons Per Sack: 7.48
Open Hole Diameter (in.) : 13.50	% Excess: 15%
Conductor Length (ft) : 80	Displacement Fluid lb/gal: 8.3
Conductor ID : 15.25	BBL to Pit: 21.0
Shoe Joint Length (ft) : 45	Fluid Ahead (bbls): 30.0
Landing Joint (ft) : 12	H2O Wash Up (bbls): 20.0
Max Rate: 8	Spacer Ahead Makeup
Max Pressure: 2000	30 BBL WATER, DYE IN 2ND 10

Calculated Results	Pressure of cement in annulus
<b>Displacement:</b> 141.45 bbls	(Casing ID Squared) X (.0009714) X (Casing Depth + Landing Joint - Shoe Joint)
<b>cuft of Shoe</b> 19.36 cuft (Casing ID Squared) X (.005454) X (Shoe Joint ft)	<b>Pressure of cement in annulus</b>
<b>cuft of Conductor</b> 61.05 cuft (Conductor Width Squared) -(Casing Size OD Squared) X (.005454) X (Conductor Length ft)	<b>Hydrostatic Pressure:</b> 1373.78 PSI
<b>cuft of Casing</b> 1001.69 cuft (Open Hole Squared)-(Casing Size Squared) X (.005454) X (Casing Depth - Conductor Length )	<b>Pressure of the fluids inside casing</b>
<b>Total Slurry Volume</b> 1082.10 cuft (cuft of Shoe) + (cuft of Conductor) + (cuft of Casing)	<b>Displacement:</b> 783.74 psi
<b>bbls of Slurry</b> 192.72 bbls (Total Slurry Volume) X (.1781)	<b>Shoe Joint:</b> 32.90 psi
<b>Sacks Needed</b> 731 sk (Total Slurry Volume) ÷ (Cement Yield) X (% Excess Cement)	<b>Total</b> 816.64 psi
<b>Mix Water</b> 130.21 bbls (Sacks Needed) X (Gallons Per Sack) ÷ 42	<b>Differential Pressure:</b> 557.14 psi
	<b>Collapse PSI:</b> 2020.00 psi
	<b>Burst PSI:</b> 3520.00 psi
	<b>Total Water Needed:</b> 321.66 bbls

X Authorization To Proceed

Customers hereby acknowledges and specifically agrees to the terms and condition on this work order, including, without limitation, the provisions on this work order.



# ANADARKO CANNON 29N-4HZ SURFACE

