



SRC ENERGY

Operator: SRC Energy
Well Name: Sena 15-21
Legal: NENW, Section 15, Township 6N, Range 66W
Location: Weld County, CO
API: 05-123-25640
Surface: 8.625" 24# @ 725' **Hole Size:** 12.25" **TOC:** Surface
Production: 4.5" 11.6# @ 7,408' **Hole Size:** 7.875" **TOC:** 812' (CBL)
Perforations: 6,970' – 7,108' (Niobrara), 7,268' – 7,284' (Codell)
TD: 7,441'

P&A Procedure

1. Conduct pre-job safety meeting and complete daily JSA
2. Blow down well if necessary, circulate hole with treated water
3. Dig out around wellhead and perform bradenhead test
4. MIRU WO unit, ND wellhead, NU BOP, tally all pipe
5. TIH w/ 4-1/2 11.6# CIBP, set at 6895'
6. Pressure test casing to 500 psi for 15 minutes
7. Set 16 sx on top of CIBP (cover 200' above Niobrara top)
8. TIH to 3,000' and set 48 sx creating balance plug (2,500'-3,000')
9. TIH to 775' and perforate casing
10. TIH w/ 4-1/2 11.6# CICR, set at 725'
 - a. Circulate 211 sx through CICR (775' annulus plug & 50' casing plug)
 - b. Sting out of CICR and pump 69 sx creating casing plug from 725' to surface
11. RDMO WO unit
12. Dig up wellhead and cut off 10' below restored ground level, top off if necessary
13. Weld on cap with ID plate, inscribed with well location, and identity
14. Backfill, clean location
15. P&A complete