Gyrodata

Client: Well Name:
Field: Rig:
Job Number: Survey Type:
Survey Date:

Horizontal Coordinate Reference System:
Grid Convention:
Vertical Reference:
Vertical Coordinate Reference System:
Geoid Name:
Geoid Model:
Magnetic Declination:
Total Gravity Field Strength:
Total Magnetic Field Strength:
Gravity Model:
Magnetic Model:

Horizontal Survey Accuracy
API Interim Accuracy @ 95%

Vertical Survey Accuracy
API Interim Accuracy @ 95%

Reference Accuracy Model:
Non-Magnetic Drill String Accuracy Model: AXYdBgdAzmSag

Log Variables

Log Variable	Description	Units
AXYdBgdAzmSag	Accelerometer X, Y, Drill Bearing, Azimuth, Sag	
MTF	Magnetic Tool Face	deg
GTF	Gravity Tool Face	deg
HS	High Side	deg
INC	Inclination	deg
AZM	Azimuth	deg
DLS	Dogleg Severity	deg/100ft
VS	Vertical Section	ft
TVD	True Vertical Depth	ft
NS	Northing	ft
EW	Easting	ft

Gyrodata Incorporated
11470 Haden Road, Houston, Texas 77041 USA
Phone: 713-461-3146 Fax: 713-461-1536 Email: info@gyrodata.com

Gyrodata

BOND HODU

Client: Well Name:
Field: Rig:
Job Number: Survey Type:
Survey Date:

Horizontal Coordinate Reference System:
Grid Convention:
Vertical Reference:
Vertical Coordinate Reference System:
Geoid Name:
Geoid Model:
Magnetic Declination:
Total Gravity Field Strength:
Total Magnetic Field Strength:
Gravity Model:
Magnetic Model:

Horizontal Survey Accuracy
API Interim Accuracy @ 95%

Vertical Survey Accuracy
API Interim Accuracy @ 95%

Reference Accuracy Model:
Non-Magnetic Drill String Accuracy Model: AXYdBgdAzmSag

Log Variables

Log Variable	Description	Units
AXYdBgdAzmSag	Accelerometer X, Y, Drill Bearing, Azimuth, Sag	
MTF	Magnetic Tool Face	deg
GTF	Gravity Tool Face	deg
HS	High Side	deg
INC	Inclination	deg
AZM	Azimuth	deg
DLS	Dogleg Severity	deg/100ft
VS	Vertical Section	ft
TVD	True Vertical Depth	ft
NS	Northing	ft
EW	Easting	ft

Gyrodata Incorporated
11470 Haden Road, Houston, Texas 77041 USA
Phone: 713-461-3146 Fax: 713-461-1536 Email: info@gyrodata.com

Gyrodata

BOND HODU - Run with 1 of 79

Client:
Well Name:
Field:
Rig:
Job Number:
Survey Type:
Survey Date:

Horizontal Coordinate Reference System:
Grid Convention:
Vertical Reference:
Vertical Coordinate Reference System:
Geoid Name:
Geoid Model:
Magnetic Declination:
Total Gravity Field Strength:
Total Magnetic Field Strength:
Gravity Model:
Magnetic Model:

Horizontal Survey Accuracy
API Interim Accuracy @ 95%

Vertical Survey Accuracy
API Interim Accuracy @ 95%

Reference Accuracy Model:
Non-Magnetic Drill String Accuracy Model: AXYdBgdAzmSag

Log Variable	Description	Units
AXYdBgdAzmSag	Accelerometer X, Y, Drill Bearing, Azimuth, Sag	
MTF	Magnetic Tool Face	deg
GTF	Gravity Tool Face	deg
HS	High Side	deg
INC	Inclination	deg
AZM	Azimuth	deg
DLS	Dogleg Severity	deg/100ft
VS	Vertical Section	ft
TVD	True Vertical Depth	ft
NS	Northing	ft
EW	Easting	ft

Gyrodata Incorporated
11470 Haden Road, Houston, Texas 77041 USA
Phone: 713-461-3146 Fax: 713-461-1536 Email: info@gyrodata.com





	Zero	Cal	Zero	Cal	Gain	Offset
3'	0.001	1.564	0.000	72.000	46.061	-0.056
CAL	0.000	0.750				
5'	-0.004	1.918	0.000	72.000	37.452	0.159
SUM						
S1	0.023	1.659	0.000	72.000	44.001	-1.001
S2	0.027	1.526	0.000	72.000	48.029	-1.300
S3	0.038	1.584	0.000	72.000	46.586	-1.779
S4	0.036	1.552	0.000	72.000	47.492	-1.702
S5	0.033	1.668	0.000	72.000	44.047	-1.449
S6	0.023	1.771	0.000	72.000	41.200	-0.958
S7	0.022	1.867	0.000	72.000	39.027	-0.877
S8	0.026	1.757	0.000	72.000	41.600	-1.092

Internal Reference Calibration, performed (Not Performed):

	Raw (v)		Calibrated (v)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
CAL	0.000	0.750	0.000	0.750	1.000	0.000

Air Zero Calibration, performed (Not Performed):

	Raw (v)	Calibrated (v)	Results
	Zero	Zero	Offset
3'	0.000	0.000	0.000
5'	0.000	0.000	0.000
SUM			
S1	0.000	0.000	0.000
S2	0.000	0.000	0.000
S3	0.000	0.000	0.000
S4	0.000	0.000	0.000
S5	0.000	0.000	0.000
S6	0.000	0.000	0.000
S7	0.000	0.000	0.000
S8	0.000	0.000	0.000

Temperature Calibration Report

Serial Number: IPPO2-01
Tool Model: 2 3/4" RIB Analog
Performed: Fri Aug 26 11:07:15 2016

	Reference		Reading	
Low Reference:	0.00	degF	0.00	usec
High Reference:	1.00	degF	1.00	usec

Gain: 0.33
Offset: 0.00
Delta Spacing 1

Sensor	Offset (ft)	Schematic	Description	Length (ft)	O.D. (in)	Weight (lb
			CableHead-TitanConeType2	1.03	1.44	3.60
CCL	18.96		CCL_Log-2 3/4" TekCo (IPSN7-03) 450 Deg. CCL	1.83	2.75	33.00
			TekCo-275_Tekco 2 3/4" Tekco Adjustable SPRING Centralizer	2.73	2.75	25.00
TEMP	12.78					
WVFS8	11.49					
WVFS7	11.49		RBTA-2 3/4" RIB Analog (IPPO2-01) Radial Incremented Bond Tool with Temp	9.13	2.75	102.00
WVFS6	11.49					
WVFS5	11.49					
WVFS4	11.49					
WVFS3	11.49					
WVFS2	11.49					
WVFS1	11.49					
WVF3FT	10.74					
WVF5FT	9.74					
WVFSYNC	6.41					
WVFTEMP	6.41					
WVFCAL	6.41		TekCo-275_Tekco 2 3/4" Tekco Adjustable SPRING Centralizer	2.73	2.75	25.00
			GR_Log-2 3/4" TekCo (ISHV2-03) 400 Deg. Gamma Ray	3.68	2.75	47.00
GR	1.04					
LOCTIM	0.00					
UTCTIM	0.00					

Dataset: 2017-09-25_extrac_mld11_cbl.db: field/well/run1/pass3.1
Total length: 21.13 ft
Total weight: 235.60 lb
O.D.: 2.75 in

gyrodata

Company	Extraction Oil and Gas
Well	MLD 11
Field	Wattenberg
County	Weld
State	Colorado
Country	U.S.A.