

NOBLE ENERGY INC.
 Speicher 31-15
 NWNE 15-6N-64W
 676 FNL & 1799 FEL
 WELD COUNTY, CO
 Wattenberg
CURRENT WELLBORE SCHEMATIC
 with PROPOSED P&A

API: 05-123-23539
 COGCC #

GL Elev: 4783
 KB Elev: 4795

Spud Date: 3/3/2006

Surface Casing :
 8-5/8", J-55, 24# @ 880'
 Cement: 495 sx
 TOC: Surface


WW	780	980
FH	469	669
SC	880	1080

No Sussex completions within 1 mile

TOC @ 3270'

Nio Top 6713'

Production Casing :
 4-1/2", I-80, 11.60# @ 7074'
 Cement: 420 sx
 TD Date: 3/4/2006



Cut surface casing off 6'-8' below surface.

Cut production casing at 1080'
 Cmt to surface with 375 sx at 1130'

Pump 240 sx plug through/on CICR
 Cmt Coverage inside PC: 2271'
 Cmt Coverage outside PC: 2000'-2500'
 Set CICR at 2400'
 Shoot sqz perms at 2500'

Set CIBP at 6664' with 2 sx cement
 New TOC: 6639'

Niobrara Perforations: 6,714' - 6862'

TD: 7100