



# **Ursa Operating Company, LLC**

**Rio Blanco County, Colorado**

**Jimmy Gulch 3G Pad**

**Jimmy Gulch 3G 22B-3-3-97**

**Wellbore #1**

**Plan: Design #1**

## **Standard Planning Report**

**25 July, 2017**



<b>Database:</b>	EDM 5000.1 Single User Db	<b>Local Co-ordinate Reference:</b>	Well Jimmy Gulch 3G 22B-3-3-97
<b>Company:</b>	Ursa Operating Company, LLC	<b>TVD Reference:</b>	Jimmy Gulch 3G 22B-3-3-97 @ 6681.0usft (Est KB)
<b>Project:</b>	Rio Blanco County, Colorado	<b>MD Reference:</b>	Jimmy Gulch 3G 22B-3-3-97 @ 6681.0usft (Est KB)
<b>Site:</b>	Jimmy Gulch 3G Pad	<b>North Reference:</b>	True
<b>Well:</b>	Jimmy Gulch 3G 22B-3-3-97	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Design #1		

<b>Project</b>	Rio Blanco County, Colorado		
<b>Map System:</b>	US State Plane 1983	<b>System Datum:</b>	Mean Sea Level
<b>Geo Datum:</b>	North American Datum 1983		
<b>Map Zone:</b>	Colorado Northern Zone		Using geodetic scale factor

<b>Site</b>	Jimmy Gulch 3G Pad				
<b>Site Position:</b>		<b>Northing:</b>	1,189,455.95 usft	<b>Latitude:</b>	39.820187318
<b>From:</b>	Lat/Long	<b>Easting:</b>	2,223,396.68 usft	<b>Longitude:</b>	-108.265221184
<b>Position Uncertainty:</b>	0.0 usft	<b>Slot Radius:</b>	13-3/16 "	<b>Grid Convergence:</b>	-1.79 °

<b>Well</b>	Jimmy Gulch 3G 22B-3-3-97, SHL: Lat 39.820167032 Long -108.265245155					
<b>Well Position</b>	<b>+N/-S</b>	-7.4 usft	<b>Northing:</b>	1,189,448.77 usft	<b>Latitude:</b>	39.820167032
	<b>+E/-W</b>	-6.7 usft	<b>Easting:</b>	2,223,389.72 usft	<b>Longitude:</b>	-108.265245155
<b>Position Uncertainty</b>		0.0 usft	<b>Wellhead Elevation:</b>	6,681.0 usft	<b>Ground Level:</b>	6,660.0 usft

<b>Wellbore</b>	Wellbore #1				
<b>Magnetics</b>	<b>Model Name</b>	<b>Sample Date</b>	<b>Declination (°)</b>	<b>Dip Angle (°)</b>	<b>Field Strength (nT)</b>
	IGRF2015	7/21/2017	9.85	65.80	51,653

<b>Design</b>	Design #1			
<b>Audit Notes:</b>				
<b>Version:</b>	<b>Phase:</b>	PROTOTYPE	<b>Tie On Depth:</b>	0.0
<b>Vertical Section:</b>	<b>Depth From (TVD) (usft)</b>	<b>+N/-S (usft)</b>	<b>+E/-W (usft)</b>	<b>Direction (°)</b>
	0.0	0.0	0.0	278.41

<b>Plan Sections</b>										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
1,000.0	0.00	0.00	1,000.0	0.0	0.0	0.00	0.00	0.00	0.00	
1,198.9	6.96	278.41	1,198.4	1.8	-11.9	3.50	3.50	0.00	278.41	
7,205.3	6.96	278.41	7,160.6	108.2	-732.2	0.00	0.00	0.00	0.00	
7,404.3	0.00	0.00	7,359.0	110.0	-744.1	3.50	-3.50	0.00	180.00	JG 3G 22B-3-3-97 TC
13,084.3	0.00	0.00	13,039.0	110.0	-744.1	0.00	0.00	0.00	0.00	

<b>Database:</b>	EDM 5000.1 Single User Db	<b>Local Co-ordinate Reference:</b>	Well Jimmy Gulch 3G 22B-3-3-97
<b>Company:</b>	Ursa Operating Company, LLC	<b>TVD Reference:</b>	Jimmy Gulch 3G 22B-3-3-97 @ 6681.0usft (Est KB)
<b>Project:</b>	Rio Blanco County, Colorado	<b>MD Reference:</b>	Jimmy Gulch 3G 22B-3-3-97 @ 6681.0usft (Est KB)
<b>Site:</b>	Jimmy Gulch 3G Pad	<b>North Reference:</b>	True
<b>Well:</b>	Jimmy Gulch 3G 22B-3-3-97	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Design #1		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	0.00	0.00
0.1	0.00	0.00	0.1	0.0	0.0	0.0	0.00	0.00	0.00	0.00
<b>SHL 39.820167032, -108.265245155</b>										
100.0	0.00	0.00	100.0	0.0	0.0	0.0	0.00	0.00	0.00	0.00
200.0	0.00	0.00	200.0	0.0	0.0	0.0	0.00	0.00	0.00	0.00
300.0	0.00	0.00	300.0	0.0	0.0	0.0	0.00	0.00	0.00	0.00
400.0	0.00	0.00	400.0	0.0	0.0	0.0	0.00	0.00	0.00	0.00
500.0	0.00	0.00	500.0	0.0	0.0	0.0	0.00	0.00	0.00	0.00
600.0	0.00	0.00	600.0	0.0	0.0	0.0	0.00	0.00	0.00	0.00
700.0	0.00	0.00	700.0	0.0	0.0	0.0	0.00	0.00	0.00	0.00
800.0	0.00	0.00	800.0	0.0	0.0	0.0	0.00	0.00	0.00	0.00
900.0	0.00	0.00	900.0	0.0	0.0	0.0	0.00	0.00	0.00	0.00
1,000.0	0.00	0.00	1,000.0	0.0	0.0	0.0	0.00	0.00	0.00	0.00
<b>Start Build 3.50</b>										
1,100.0	3.50	278.41	1,099.9	0.4	-3.0	3.1	3.50	3.50	0.00	0.00
1,170.3	5.96	278.41	1,170.0	1.3	-8.8	8.9	3.50	3.50	0.00	0.00
<b>Green River Fm - Mahogany Bench</b>										
1,198.9	6.96	278.41	1,198.4	1.8	-11.9	12.1	3.50	3.50	0.00	0.00
<b>Start 6006.4 hold at 1198.9 MD</b>										
1,200.0	6.96	278.41	1,199.5	1.8	-12.1	12.2	0.00	0.00	0.00	0.00
1,227.7	6.96	278.41	1,227.0	2.3	-15.4	15.6	0.00	0.00	0.00	0.00
<b>Dissolution Surface</b>										
1,300.0	6.96	278.41	1,298.8	3.6	-24.1	24.3	0.00	0.00	0.00	0.00
1,400.0	6.96	278.41	1,398.0	5.3	-36.1	36.4	0.00	0.00	0.00	0.00
1,500.0	6.96	278.41	1,497.3	7.1	-48.0	48.6	0.00	0.00	0.00	0.00
1,600.0	6.96	278.41	1,596.6	8.9	-60.0	60.7	0.00	0.00	0.00	0.00
1,700.0	6.96	278.41	1,695.8	10.6	-72.0	72.8	0.00	0.00	0.00	0.00
1,800.0	6.96	278.41	1,795.1	12.4	-84.0	84.9	0.00	0.00	0.00	0.00
1,900.0	6.96	278.41	1,894.3	14.2	-96.0	97.1	0.00	0.00	0.00	0.00
2,000.0	6.96	278.41	1,993.6	16.0	-108.0	109.2	0.00	0.00	0.00	0.00
2,100.0	6.96	278.41	2,092.9	17.7	-120.0	121.3	0.00	0.00	0.00	0.00
2,200.0	6.96	278.41	2,192.1	19.5	-132.0	133.4	0.00	0.00	0.00	0.00
2,300.0	6.96	278.41	2,291.4	21.3	-144.0	145.5	0.00	0.00	0.00	0.00
2,368.1	6.96	278.41	2,359.0	22.5	-152.1	153.8	0.00	0.00	0.00	0.00
<b>Green River Fm - Garden Gulch Mbr</b>										
2,400.0	6.96	278.41	2,390.7	23.1	-156.0	157.7	0.00	0.00	0.00	0.00
2,500.0	6.96	278.41	2,489.9	24.8	-168.0	169.8	0.00	0.00	0.00	0.00
2,593.8	6.96	278.41	2,583.0	26.5	-179.2	181.2	0.00	0.00	0.00	0.00
<b>Wasatch Fm</b>										
2,600.0	6.96	278.41	2,589.2	26.6	-179.9	181.9	0.00	0.00	0.00	0.00
2,700.0	6.96	278.41	2,688.4	28.4	-191.9	194.0	0.00	0.00	0.00	0.00
2,800.0	6.96	278.41	2,787.7	30.1	-203.9	206.1	0.00	0.00	0.00	0.00
2,900.0	6.96	278.41	2,887.0	31.9	-215.9	218.3	0.00	0.00	0.00	0.00
3,000.0	6.96	278.41	2,986.2	33.7	-227.9	230.4	0.00	0.00	0.00	0.00
3,100.0	6.96	278.41	3,085.5	35.5	-239.9	242.5	0.00	0.00	0.00	0.00
3,200.0	6.96	278.41	3,184.8	37.2	-251.9	254.6	0.00	0.00	0.00	0.00
3,300.0	6.96	278.41	3,284.0	39.0	-263.9	266.8	0.00	0.00	0.00	0.00
3,400.0	6.96	278.41	3,383.3	40.8	-275.9	278.9	0.00	0.00	0.00	0.00
3,500.0	6.96	278.41	3,482.5	42.6	-287.9	291.0	0.00	0.00	0.00	0.00
3,600.0	6.96	278.41	3,581.8	44.3	-299.9	303.1	0.00	0.00	0.00	0.00
3,700.0	6.96	278.41	3,681.1	46.1	-311.9	315.2	0.00	0.00	0.00	0.00
3,800.0	6.96	278.41	3,780.3	47.9	-323.8	327.4	0.00	0.00	0.00	0.00

<b>Database:</b>	EDM 5000.1 Single User Db	<b>Local Co-ordinate Reference:</b>	Well Jimmy Gulch 3G 22B-3-3-97
<b>Company:</b>	Ursa Operating Company, LLC	<b>TVD Reference:</b>	Jimmy Gulch 3G 22B-3-3-97 @ 6681.0usft (Est KB)
<b>Project:</b>	Rio Blanco County, Colorado	<b>MD Reference:</b>	Jimmy Gulch 3G 22B-3-3-97 @ 6681.0usft (Est KB)
<b>Site:</b>	Jimmy Gulch 3G Pad	<b>North Reference:</b>	True
<b>Well:</b>	Jimmy Gulch 3G 22B-3-3-97	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Design #1		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
3,900.0	6.96	278.41	3,879.6	49.6	-335.8	339.5	0.00	0.00	0.00	
4,000.0	6.96	278.41	3,978.9	51.4	-347.8	351.6	0.00	0.00	0.00	
4,021.3	6.96	278.41	4,000.0	51.8	-350.4	354.2	0.00	0.00	0.00	
<b>Surface Casing</b>										
4,100.0	6.96	278.41	4,078.1	53.2	-359.8	363.7	0.00	0.00	0.00	
4,200.0	6.96	278.41	4,177.4	55.0	-371.8	375.9	0.00	0.00	0.00	
4,300.0	6.96	278.41	4,276.6	56.7	-383.8	388.0	0.00	0.00	0.00	
4,400.0	6.96	278.41	4,375.9	58.5	-395.8	400.1	0.00	0.00	0.00	
4,500.0	6.96	278.41	4,475.2	60.3	-407.8	412.2	0.00	0.00	0.00	
4,600.0	6.96	278.41	4,574.4	62.1	-419.8	424.3	0.00	0.00	0.00	
4,700.0	6.96	278.41	4,673.7	63.8	-431.8	436.5	0.00	0.00	0.00	
4,800.0	6.96	278.41	4,773.0	65.6	-443.8	448.6	0.00	0.00	0.00	
4,900.0	6.96	278.41	4,872.2	67.4	-455.7	460.7	0.00	0.00	0.00	
5,000.0	6.96	278.41	4,971.5	69.1	-467.7	472.8	0.00	0.00	0.00	
5,052.9	6.96	278.41	5,024.0	70.1	-474.1	479.2	0.00	0.00	0.00	
<b>Ft Union</b>										
5,100.0	6.96	278.41	5,070.7	70.9	-479.7	484.9	0.00	0.00	0.00	
5,200.0	6.96	278.41	5,170.0	72.7	-491.7	497.1	0.00	0.00	0.00	
5,300.0	6.96	278.41	5,269.3	74.5	-503.7	509.2	0.00	0.00	0.00	
5,400.0	6.96	278.41	5,368.5	76.2	-515.7	521.3	0.00	0.00	0.00	
5,500.0	6.96	278.41	5,467.8	78.0	-527.7	533.4	0.00	0.00	0.00	
5,600.0	6.96	278.41	5,567.1	79.8	-539.7	545.6	0.00	0.00	0.00	
5,700.0	6.96	278.41	5,666.3	81.6	-551.7	557.7	0.00	0.00	0.00	
5,800.0	6.96	278.41	5,765.6	83.3	-563.7	569.8	0.00	0.00	0.00	
5,900.0	6.96	278.41	5,864.8	85.1	-575.7	581.9	0.00	0.00	0.00	
6,000.0	6.96	278.41	5,964.1	86.9	-587.7	594.0	0.00	0.00	0.00	
6,100.0	6.96	278.41	6,063.4	88.6	-599.6	606.2	0.00	0.00	0.00	
6,200.0	6.96	278.41	6,162.6	90.4	-611.6	618.3	0.00	0.00	0.00	
6,300.0	6.96	278.41	6,261.9	92.2	-623.6	630.4	0.00	0.00	0.00	
6,400.0	6.96	278.41	6,361.2	94.0	-635.6	642.5	0.00	0.00	0.00	
6,500.0	6.96	278.41	6,460.4	95.7	-647.6	654.6	0.00	0.00	0.00	
6,600.0	6.96	278.41	6,559.7	97.5	-659.6	666.8	0.00	0.00	0.00	
6,700.0	6.96	278.41	6,658.9	99.3	-671.6	678.9	0.00	0.00	0.00	
6,800.0	6.96	278.41	6,758.2	101.1	-683.6	691.0	0.00	0.00	0.00	
6,900.0	6.96	278.41	6,857.5	102.8	-695.6	703.1	0.00	0.00	0.00	
7,000.0	6.96	278.41	6,956.7	104.6	-707.6	715.3	0.00	0.00	0.00	
7,100.0	6.96	278.41	7,056.0	106.4	-719.6	727.4	0.00	0.00	0.00	
7,205.3	6.96	278.41	7,160.6	108.2	-732.2	740.1	0.00	0.00	0.00	
<b>Start Drop -3.50</b>										
7,300.0	3.65	278.41	7,254.8	109.5	-740.8	748.9	3.50	-3.50	0.00	
7,398.3	0.21	278.41	7,353.0	110.0	-744.1	752.2	3.50	-3.50	0.00	
<b>Ohio Creek</b>										
7,404.3	0.00	0.00	7,359.0	110.0	-744.1	752.2	3.50	-3.50	1,359.84	
<b>Back to Vertical - Start 5680.0 hold at 7404.3 MD - Top of Gas - JG 3G 22B-3-3-97 TGT</b>										
7,500.0	0.00	0.00	7,454.7	110.0	-744.1	752.2	0.00	0.00	0.00	
7,564.3	0.00	0.00	7,519.0	110.0	-744.1	752.2	0.00	0.00	0.00	
<b>Williams Fork</b>										
7,600.0	0.00	0.00	7,554.7	110.0	-744.1	752.2	0.00	0.00	0.00	
7,700.0	0.00	0.00	7,654.7	110.0	-744.1	752.2	0.00	0.00	0.00	
7,800.0	0.00	0.00	7,754.7	110.0	-744.1	752.2	0.00	0.00	0.00	
7,900.0	0.00	0.00	7,854.7	110.0	-744.1	752.2	0.00	0.00	0.00	

<b>Database:</b>	EDM 5000.1 Single User Db	<b>Local Co-ordinate Reference:</b>	Well Jimmy Gulch 3G 22B-3-3-97
<b>Company:</b>	Ursa Operating Company, LLC	<b>TVD Reference:</b>	Jimmy Gulch 3G 22B-3-3-97 @ 6681.0usft (Est KB)
<b>Project:</b>	Rio Blanco County, Colorado	<b>MD Reference:</b>	Jimmy Gulch 3G 22B-3-3-97 @ 6681.0usft (Est KB)
<b>Site:</b>	Jimmy Gulch 3G Pad	<b>North Reference:</b>	True
<b>Well:</b>	Jimmy Gulch 3G 22B-3-3-97	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Design #1		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
8,000.0	0.00	0.00	7,954.7	110.0	-744.1	752.2	0.00	0.00	0.00	
8,100.0	0.00	0.00	8,054.7	110.0	-744.1	752.2	0.00	0.00	0.00	
8,200.0	0.00	0.00	8,154.7	110.0	-744.1	752.2	0.00	0.00	0.00	
8,300.0	0.00	0.00	8,254.7	110.0	-744.1	752.2	0.00	0.00	0.00	
8,400.0	0.00	0.00	8,354.7	110.0	-744.1	752.2	0.00	0.00	0.00	
8,500.0	0.00	0.00	8,454.7	110.0	-744.1	752.2	0.00	0.00	0.00	
8,600.0	0.00	0.00	8,554.7	110.0	-744.1	752.2	0.00	0.00	0.00	
8,700.0	0.00	0.00	8,654.7	110.0	-744.1	752.2	0.00	0.00	0.00	
8,800.0	0.00	0.00	8,754.7	110.0	-744.1	752.2	0.00	0.00	0.00	
8,900.0	0.00	0.00	8,854.7	110.0	-744.1	752.2	0.00	0.00	0.00	
9,000.0	0.00	0.00	8,954.7	110.0	-744.1	752.2	0.00	0.00	0.00	
9,100.0	0.00	0.00	9,054.7	110.0	-744.1	752.2	0.00	0.00	0.00	
9,200.0	0.00	0.00	9,154.7	110.0	-744.1	752.2	0.00	0.00	0.00	
9,300.0	0.00	0.00	9,254.7	110.0	-744.1	752.2	0.00	0.00	0.00	
9,400.0	0.00	0.00	9,354.7	110.0	-744.1	752.2	0.00	0.00	0.00	
9,500.0	0.00	0.00	9,454.7	110.0	-744.1	752.2	0.00	0.00	0.00	
9,600.0	0.00	0.00	9,554.7	110.0	-744.1	752.2	0.00	0.00	0.00	
9,700.0	0.00	0.00	9,654.7	110.0	-744.1	752.2	0.00	0.00	0.00	
9,800.0	0.00	0.00	9,754.7	110.0	-744.1	752.2	0.00	0.00	0.00	
9,900.0	0.00	0.00	9,854.7	110.0	-744.1	752.2	0.00	0.00	0.00	
10,000.0	0.00	0.00	9,954.7	110.0	-744.1	752.2	0.00	0.00	0.00	
10,100.0	0.00	0.00	10,054.7	110.0	-744.1	752.2	0.00	0.00	0.00	
10,200.0	0.00	0.00	10,154.7	110.0	-744.1	752.2	0.00	0.00	0.00	
10,300.0	0.00	0.00	10,254.7	110.0	-744.1	752.2	0.00	0.00	0.00	
10,400.0	0.00	0.00	10,354.7	110.0	-744.1	752.2	0.00	0.00	0.00	
10,500.0	0.00	0.00	10,454.7	110.0	-744.1	752.2	0.00	0.00	0.00	
10,600.0	0.00	0.00	10,554.7	110.0	-744.1	752.2	0.00	0.00	0.00	
10,700.0	0.00	0.00	10,654.7	110.0	-744.1	752.2	0.00	0.00	0.00	
10,800.0	0.00	0.00	10,754.7	110.0	-744.1	752.2	0.00	0.00	0.00	
10,900.0	0.00	0.00	10,854.7	110.0	-744.1	752.2	0.00	0.00	0.00	
11,000.0	0.00	0.00	10,954.7	110.0	-744.1	752.2	0.00	0.00	0.00	
11,034.3	0.00	0.00	10,989.0	110.0	-744.1	752.2	0.00	0.00	0.00	
<b>Cameo</b>										
11,100.0	0.00	0.00	11,054.7	110.0	-744.1	752.2	0.00	0.00	0.00	
11,200.0	0.00	0.00	11,154.7	110.0	-744.1	752.2	0.00	0.00	0.00	
11,300.0	0.00	0.00	11,254.7	110.0	-744.1	752.2	0.00	0.00	0.00	
11,400.0	0.00	0.00	11,354.7	110.0	-744.1	752.2	0.00	0.00	0.00	
11,500.0	0.00	0.00	11,454.7	110.0	-744.1	752.2	0.00	0.00	0.00	
11,534.3	0.00	0.00	11,489.0	110.0	-744.1	752.2	0.00	0.00	0.00	
<b>Rollins</b>										
11,600.0	0.00	0.00	11,554.7	110.0	-744.1	752.2	0.00	0.00	0.00	
11,700.0	0.00	0.00	11,654.7	110.0	-744.1	752.2	0.00	0.00	0.00	
11,701.3	0.00	0.00	11,656.0	110.0	-744.1	752.2	0.00	0.00	0.00	
<b>Cozette Fm</b>										
11,800.0	0.00	0.00	11,754.7	110.0	-744.1	752.2	0.00	0.00	0.00	
11,900.0	0.00	0.00	11,854.7	110.0	-744.1	752.2	0.00	0.00	0.00	
12,000.0	0.00	0.00	11,954.7	110.0	-744.1	752.2	0.00	0.00	0.00	
12,058.3	0.00	0.00	12,013.0	110.0	-744.1	752.2	0.00	0.00	0.00	
<b>Corcoran</b>										
12,100.0	0.00	0.00	12,054.7	110.0	-744.1	752.2	0.00	0.00	0.00	
12,200.0	0.00	0.00	12,154.7	110.0	-744.1	752.2	0.00	0.00	0.00	
12,300.0	0.00	0.00	12,254.7	110.0	-744.1	752.2	0.00	0.00	0.00	

<b>Database:</b>	EDM 5000.1 Single User Db	<b>Local Co-ordinate Reference:</b>	Well Jimmy Gulch 3G 22B-3-3-97
<b>Company:</b>	Ursa Operating Company, LLC	<b>TVD Reference:</b>	Jimmy Gulch 3G 22B-3-3-97 @ 6681.0usft (Est KB)
<b>Project:</b>	Rio Blanco County, Colorado	<b>MD Reference:</b>	Jimmy Gulch 3G 22B-3-3-97 @ 6681.0usft (Est KB)
<b>Site:</b>	Jimmy Gulch 3G Pad	<b>North Reference:</b>	True
<b>Well:</b>	Jimmy Gulch 3G 22B-3-3-97	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Design #1		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
12,400.0	0.00	0.00	12,354.7	110.0	-744.1	752.2	0.00	0.00	0.00	
12,500.0	0.00	0.00	12,454.7	110.0	-744.1	752.2	0.00	0.00	0.00	
12,600.0	0.00	0.00	12,554.7	110.0	-744.1	752.2	0.00	0.00	0.00	
12,700.0	0.00	0.00	12,654.7	110.0	-744.1	752.2	0.00	0.00	0.00	
12,800.0	0.00	0.00	12,754.7	110.0	-744.1	752.2	0.00	0.00	0.00	
12,900.0	0.00	0.00	12,854.7	110.0	-744.1	752.2	0.00	0.00	0.00	
13,000.0	0.00	0.00	12,954.7	110.0	-744.1	752.2	0.00	0.00	0.00	
13,084.3	0.00	0.00	13,039.0	110.0	-744.1	752.2	0.00	0.00	0.00	
<b>TD at 13084.3 - BHL 39.8204690, -108.2678943</b>										

Design Targets										
Target Name	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude	
JG 3G 22B-3-3-97 TGT	0.00	0.00	7,359.0	110.0	-744.1	1,189,581.93	2,222,649.39	39.820469000	-108.267894300	
- hit/miss target										
- Shape										
- plan hits target center										
- Rectangle (sides W100.0 H40.0 D5,680.0)										


Formations						
Measured Depth (usft)	Vertical Depth (usft)	Name	Lithology	Dip (°)	Dip Direction (°)	
1,170.3	1,170.0	Green River Fm - Mahogany Bench		0.00		
1,227.7	1,227.0	Dissolution Surface		0.00		
2,368.1	2,359.0	Green River Fm - Garden Gulch Mbr		0.00		
2,593.8	2,583.0	Wasatch Fm		0.00		
5,052.9	5,024.0	Ft Union		0.00		
7,398.3	7,353.0	Ohio Creek		0.00		
7,404.3	7,359.0	Top of Gas		0.00		
7,564.3	7,519.0	Williams Fork		0.00		
11,034.3	10,989.0	Cameo		0.00		
11,534.3	11,489.0	Rollins		0.00		
11,701.3	11,656.0	Cozzette Fm		0.00		
12,058.3	12,013.0	Corcoran		0.00		

<b>Database:</b>	EDM 5000.1 Single User Db	<b>Local Co-ordinate Reference:</b>	Well Jimmy Gulch 3G 22B-3-3-97
<b>Company:</b>	Ursa Operating Company, LLC	<b>TVD Reference:</b>	Jimmy Gulch 3G 22B-3-3-97 @ 6681.0usft (Est KB)
<b>Project:</b>	Rio Blanco County, Colorado	<b>MD Reference:</b>	Jimmy Gulch 3G 22B-3-3-97 @ 6681.0usft (Est KB)
<b>Site:</b>	Jimmy Gulch 3G Pad	<b>North Reference:</b>	True
<b>Well:</b>	Jimmy Gulch 3G 22B-3-3-97	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Design #1		

Plan Annotations				
Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates		Comment
		+N/-S (usft)	+E/-W (usft)	
0.1	0.1	0.0	0.0	SHL 39.820167032, -108.265245155
1,000.0	1,000.0	0.0	0.0	Start Build 3.50
1,198.9	1,198.4	1.8	-11.9	Start 6006.4 hold at 1198.9 MD
4,021.3	4,000.0	51.8	-350.4	Surface Casing
7,205.3	7,160.6	108.2	-732.2	Start Drop -3.50
7,404.3	7,359.0	110.0	-744.1	Back to Vertical
7,404.3	7,359.0	110.0	-744.1	Start 5680.0 hold at 7404.3 MD
13,084.3	13,039.0	110.0	-744.1	TD at 13084.3
13,084.3	13,039.0	110.0	-744.1	BHL 39.8204690, -108.2678943



Well Name: Jimmy Gulch 3G 22B-3-3-97  
 Surface Location: Jimmy Gulch 3G Pad  
 North American Datum 1983 US State Plane 1983 Colorado Northern Zone  
 Ground Elevation: 6660.0  
 +N/-S 0.0 +E/-W 0.0 Northing 1189448.78 Easting 2223389.72 Latitude 39.820167032 Longitude -108.265245155  
 Est KB Jimmy Gulch 3G 22B-3-3-97 @ 6681.0usft (Est KB)



Azimuths to True North  
 Magnetic North: 9.85°  
 Magnetic Field  
 Strength: 51652.6snT  
 Dip Angle: 65.80°  
 Date: 7/21/2017  
 Model: IGRF2015

Jimmy Gulch 3G Pad  
 Jimmy Gulch 3G 22B-3-3-97  
 Design #1  
 21:17, July 25 2017

WELLBORE TARGET DETAILS (MAP CO-ORDINATES AND LAT/LONG)

Name	TVD	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude	Shape
JG 3G 22B-3-3-97 TGT	7359.0	110.0	-744.1	1189581.93	2222649.39	39.820469000	-108.267894300	Rectangle (Sides: L40.0 W100.0)

SECTION DETAILS

Sec	MD	Inc	Azi	TVD	+N/-S	+E/-W	Dleg	TFace	VSec	Target
1	0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.0	
2	1000.0	0.00	0.00	1000.0	0.0	0.0	0.00	0.00	0.0	
3	1198.9	6.96	278.41	1198.4	1.8	-11.9	3.50	278.41	12.1	
4	7205.3	6.96	278.41	7160.6	108.2	-732.2	0.00	0.00	740.1	
5	7404.3	0.00	0.00	7359.0	110.0	-744.1	3.50	180.00	752.2	JG 3G 22B-3-3-97 TGT
6	13084.3	0.00	0.00	13039.0	110.0	-744.1	0.00	0.00	752.2	

ANNOTATIONS

TVD	MD	Annotation
0.1	0.1	SHL 39.820167032, -108.265245155
1000.0	1000.0	Start Build 3.50
1198.4	1198.9	Start 6006.4 hold at 1198.9 MD
4000.0	4021.3	Surface Casing
7160.6	7205.3	Start Drop -3.50
7359.0	7404.3	Back to Vertical
7359.0	7404.3	Start 5680.0 hold at 7404.3 MD
13039.0	13084.3	TD at 13084.3
13039.0	13084.3	BHL 39.8204690, -108.2678943

FORMATION TOP DETAILS

TVDPath	MDPath	Formation	DipAngle	DipDir
1170.0	1170.3	Mahogany Bench	0.00	
1227.0	1227.7	Dissolution Surface	0.00	
2359.0	2368.1	Garden Gulch Mbr	0.00	
2583.0	2593.8	Wasatch Fm	0.00	
5024.0	5052.9	Ft Union	0.00	
7353.0	7398.3	Ohio Creek	0.00	
7359.0	7404.3	Top of Gas	0.00	
7519.0	7564.3	Williams Fork	0.00	
10989.0	11034.3	Cameo	0.00	
11489.0	11534.3	Rollins	0.00	
11656.0	11701.3	Cozzette Fm	0.00	
12013.0	12058.3	Corcoran	0.00	

