



Ursa Operating Company, LLC

Rio Blanco County, Colorado

Jimmy Gulch 3K Pad

Jimmy Gulch 3K 23B-3-3-97

Wellbore #1

Plan: Design #1

Standard Planning Report

25 July, 2017



Database:	EDM 5000.1 Single User Db	Local Co-ordinate Reference:	Well Jimmy Gulch 3K 23B-3-3-97
Company:	Ursa Operating Company, LLC	TVD Reference:	Jimmy Gulch 3K 23B-3-3-97 @ 6733.5usft (Est KB)
Project:	Rio Blanco County, Colorado	MD Reference:	Jimmy Gulch 3K 23B-3-3-97 @ 6733.5usft (Est KB)
Site:	Jimmy Gulch 3K Pad	North Reference:	True
Well:	Jimmy Gulch 3K 23B-3-3-97	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1		

Project	Rio Blanco County, Colorado		
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	Colorado Northern Zone		Using geodetic scale factor

Site	Jimmy Gulch 3K Pad				
Site Position:		Northing:	1,187,943.19 usft	Latitude:	39.815928222
From:	Lat/Long	Easting:	2,222,132.68 usft	Longitude:	-108.269550766
Position Uncertainty:	0.0 usft	Slot Radius:	13-3/16 "	Grid Convergence:	-1.79 °

Well	Jimmy Gulch 3K 23B-3-3-97, SHL: Lat 39.815805543 Long -108.269569189					
Well Position	+N/-S	-44.7 usft	Northing:	1,187,898.69 usft	Latitude:	39.815805543
	+E/-W	-5.2 usft	Easting:	2,222,126.11 usft	Longitude:	-108.269569189
Position Uncertainty		0.0 usft	Wellhead Elevation:	6,733.5 usft	Ground Level:	6,712.5 usft

Wellbore	Wellbore #1				
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF2015	7/21/2017	9.85	65.80	51,649

Design	Design #1			
Audit Notes:				
Version:	Phase:	PROTOTYPE	Tie On Depth:	0.0
Vertical Section:	Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)	Direction (°)
	0.0	0.0	0.0	53.74

Plan Sections										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
1,000.0	0.00	0.00	1,000.0	0.0	0.0	0.00	0.00	0.00	0.00	
1,168.3	5.89	53.74	1,168.0	5.1	7.0	3.50	3.50	0.00	53.74	
7,268.5	5.89	53.74	7,236.0	375.3	511.7	0.00	0.00	0.00	0.00	
7,436.8	0.00	0.00	7,404.0	380.4	518.7	3.50	-3.50	0.00	180.00	JG 3K 23B-3-3-97 TG
13,116.8	0.00	0.00	13,084.0	380.4	518.7	0.00	0.00	0.00	0.00	

Database:	EDM 5000.1 Single User Db	Local Co-ordinate Reference:	Well Jimmy Gulch 3K 23B-3-3-97
Company:	Ursa Operating Company, LLC	TVD Reference:	Jimmy Gulch 3K 23B-3-3-97 @ 6733.5usft (Est KB)
Project:	Rio Blanco County, Colorado	MD Reference:	Jimmy Gulch 3K 23B-3-3-97 @ 6733.5usft (Est KB)
Site:	Jimmy Gulch 3K Pad	North Reference:	True
Well:	Jimmy Gulch 3K 23B-3-3-97	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	0.00	0.00
0.1	0.00	0.00	0.1	0.0	0.0	0.0	0.00	0.00	0.00	0.00
SHL 39.815805543, -108.269569189										
100.0	0.00	0.00	100.0	0.0	0.0	0.0	0.00	0.00	0.00	0.00
200.0	0.00	0.00	200.0	0.0	0.0	0.0	0.00	0.00	0.00	0.00
300.0	0.00	0.00	300.0	0.0	0.0	0.0	0.00	0.00	0.00	0.00
400.0	0.00	0.00	400.0	0.0	0.0	0.0	0.00	0.00	0.00	0.00
500.0	0.00	0.00	500.0	0.0	0.0	0.0	0.00	0.00	0.00	0.00
600.0	0.00	0.00	600.0	0.0	0.0	0.0	0.00	0.00	0.00	0.00
700.0	0.00	0.00	700.0	0.0	0.0	0.0	0.00	0.00	0.00	0.00
800.0	0.00	0.00	800.0	0.0	0.0	0.0	0.00	0.00	0.00	0.00
900.0	0.00	0.00	900.0	0.0	0.0	0.0	0.00	0.00	0.00	0.00
1,000.0	0.00	0.00	1,000.0	0.0	0.0	0.0	0.00	0.00	0.00	0.00
Start Build 3.50										
1,100.0	3.50	53.74	1,099.9	1.8	2.5	3.1	3.50	3.50	0.00	0.00
1,168.3	5.89	53.74	1,168.0	5.1	7.0	8.6	3.50	3.50	0.00	0.00
Start 6100.2 hold at 1168.3 MD										
1,200.0	5.89	53.74	1,199.5	7.0	9.6	11.9	0.00	0.00	0.00	0.00
1,215.5	5.89	53.74	1,215.0	8.0	10.9	13.5	0.00	0.00	0.00	0.00
Green River Fm - Mahogany Bench										
1,272.8	5.89	53.74	1,272.0	11.5	15.6	19.4	0.00	0.00	0.00	0.00
Dissolution Surface										
1,300.0	5.89	53.74	1,299.0	13.1	17.9	22.2	0.00	0.00	0.00	0.00
1,400.0	5.89	53.74	1,398.5	19.2	26.1	32.4	0.00	0.00	0.00	0.00
1,500.0	5.89	53.74	1,498.0	25.2	34.4	42.7	0.00	0.00	0.00	0.00
1,600.0	5.89	53.74	1,597.4	31.3	42.7	52.9	0.00	0.00	0.00	0.00
1,700.0	5.89	53.74	1,696.9	37.4	51.0	63.2	0.00	0.00	0.00	0.00
1,800.0	5.89	53.74	1,796.4	43.4	59.2	73.5	0.00	0.00	0.00	0.00
1,900.0	5.89	53.74	1,895.8	49.5	67.5	83.7	0.00	0.00	0.00	0.00
2,000.0	5.89	53.74	1,995.3	55.6	75.8	94.0	0.00	0.00	0.00	0.00
2,100.0	5.89	53.74	2,094.8	61.7	84.1	104.2	0.00	0.00	0.00	0.00
2,200.0	5.89	53.74	2,194.3	67.7	92.3	114.5	0.00	0.00	0.00	0.00
2,300.0	5.89	53.74	2,293.7	73.8	100.6	124.8	0.00	0.00	0.00	0.00
2,400.0	5.89	53.74	2,393.2	79.9	108.9	135.0	0.00	0.00	0.00	0.00
2,410.9	5.89	53.74	2,404.0	80.5	109.8	136.1	0.00	0.00	0.00	0.00
Green River Fm - Garden Gulch Mbr										
2,500.0	5.89	53.74	2,492.7	85.9	117.2	145.3	0.00	0.00	0.00	0.00
2,600.0	5.89	53.74	2,592.1	92.0	125.4	155.6	0.00	0.00	0.00	0.00
2,636.0	5.89	53.74	2,628.0	94.2	128.4	159.3	0.00	0.00	0.00	0.00
Wasatch Fm										
2,700.0	5.89	53.74	2,691.6	98.1	133.7	165.8	0.00	0.00	0.00	0.00
2,800.0	5.89	53.74	2,791.1	104.1	142.0	176.1	0.00	0.00	0.00	0.00
2,900.0	5.89	53.74	2,890.6	110.2	150.3	186.3	0.00	0.00	0.00	0.00
3,000.0	5.89	53.74	2,990.0	116.3	158.5	196.6	0.00	0.00	0.00	0.00
3,100.0	5.89	53.74	3,089.5	122.3	166.8	206.9	0.00	0.00	0.00	0.00
3,200.0	5.89	53.74	3,189.0	128.4	175.1	217.1	0.00	0.00	0.00	0.00
3,300.0	5.89	53.74	3,288.5	134.5	183.4	227.4	0.00	0.00	0.00	0.00
3,400.0	5.89	53.74	3,387.9	140.5	191.6	237.6	0.00	0.00	0.00	0.00
3,500.0	5.89	53.74	3,487.4	146.6	199.9	247.9	0.00	0.00	0.00	0.00
3,600.0	5.89	53.74	3,586.9	152.7	208.2	258.2	0.00	0.00	0.00	0.00
3,700.0	5.89	53.74	3,686.3	158.7	216.5	268.4	0.00	0.00	0.00	0.00
3,800.0	5.89	53.74	3,785.8	164.8	224.7	278.7	0.00	0.00	0.00	0.00

Database:	EDM 5000.1 Single User Db	Local Co-ordinate Reference:	Well Jimmy Gulch 3K 23B-3-3-97
Company:	Ursa Operating Company, LLC	TVD Reference:	Jimmy Gulch 3K 23B-3-3-97 @ 6733.5usft (Est KB)
Project:	Rio Blanco County, Colorado	MD Reference:	Jimmy Gulch 3K 23B-3-3-97 @ 6733.5usft (Est KB)
Site:	Jimmy Gulch 3K Pad	North Reference:	True
Well:	Jimmy Gulch 3K 23B-3-3-97	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
3,900.0	5.89	53.74	3,885.3	170.9	233.0	288.9	0.00	0.00	0.00	
4,000.0	5.89	53.74	3,984.8	176.9	241.3	299.2	0.00	0.00	0.00	
4,015.3	5.89	53.74	4,000.0	177.9	242.5	300.8	0.00	0.00	0.00	
Surface Casing										
4,100.0	5.89	53.74	4,084.2	183.0	249.6	309.5	0.00	0.00	0.00	
4,200.0	5.89	53.74	4,183.7	189.1	257.8	319.7	0.00	0.00	0.00	
4,300.0	5.89	53.74	4,283.2	195.2	266.1	330.0	0.00	0.00	0.00	
4,400.0	5.89	53.74	4,382.6	201.2	274.4	340.3	0.00	0.00	0.00	
4,500.0	5.89	53.74	4,482.1	207.3	282.6	350.5	0.00	0.00	0.00	
4,600.0	5.89	53.74	4,581.6	213.4	290.9	360.8	0.00	0.00	0.00	
4,700.0	5.89	53.74	4,681.1	219.4	299.2	371.0	0.00	0.00	0.00	
4,800.0	5.89	53.74	4,780.5	225.5	307.5	381.3	0.00	0.00	0.00	
4,900.0	5.89	53.74	4,880.0	231.6	315.7	391.6	0.00	0.00	0.00	
5,000.0	5.89	53.74	4,979.5	237.6	324.0	401.8	0.00	0.00	0.00	
5,090.0	5.89	53.74	5,069.0	243.1	331.5	411.1	0.00	0.00	0.00	
Ft Union										
5,100.0	5.89	53.74	5,079.0	243.7	332.3	412.1	0.00	0.00	0.00	
5,200.0	5.89	53.74	5,178.4	249.8	340.6	422.3	0.00	0.00	0.00	
5,300.0	5.89	53.74	5,277.9	255.8	348.8	432.6	0.00	0.00	0.00	
5,400.0	5.89	53.74	5,377.4	261.9	357.1	442.9	0.00	0.00	0.00	
5,500.0	5.89	53.74	5,476.8	268.0	365.4	453.1	0.00	0.00	0.00	
5,600.0	5.89	53.74	5,576.3	274.0	373.7	463.4	0.00	0.00	0.00	
5,700.0	5.89	53.74	5,675.8	280.1	381.9	473.6	0.00	0.00	0.00	
5,800.0	5.89	53.74	5,775.3	286.2	390.2	483.9	0.00	0.00	0.00	
5,900.0	5.89	53.74	5,874.7	292.2	398.5	494.2	0.00	0.00	0.00	
6,000.0	5.89	53.74	5,974.2	298.3	406.8	504.4	0.00	0.00	0.00	
6,100.0	5.89	53.74	6,073.7	304.4	415.0	514.7	0.00	0.00	0.00	
6,200.0	5.89	53.74	6,173.1	310.5	423.3	525.0	0.00	0.00	0.00	
6,300.0	5.89	53.74	6,272.6	316.5	431.6	535.2	0.00	0.00	0.00	
6,400.0	5.89	53.74	6,372.1	322.6	439.9	545.5	0.00	0.00	0.00	
6,500.0	5.89	53.74	6,471.6	328.7	448.1	555.7	0.00	0.00	0.00	
6,600.0	5.89	53.74	6,571.0	334.7	456.4	566.0	0.00	0.00	0.00	
6,700.0	5.89	53.74	6,670.5	340.8	464.7	576.3	0.00	0.00	0.00	
6,800.0	5.89	53.74	6,770.0	346.9	473.0	586.5	0.00	0.00	0.00	
6,900.0	5.89	53.74	6,869.4	352.9	481.2	596.8	0.00	0.00	0.00	
7,000.0	5.89	53.74	6,968.9	359.0	489.5	607.0	0.00	0.00	0.00	
7,100.0	5.89	53.74	7,068.4	365.1	497.8	617.3	0.00	0.00	0.00	
7,200.0	5.89	53.74	7,167.9	371.1	506.1	627.6	0.00	0.00	0.00	
7,268.5	5.89	53.74	7,236.0	375.3	511.7	634.6	0.00	0.00	0.00	
Start Drop -3.50										
7,300.0	4.79	53.74	7,267.4	377.0	514.1	637.5	3.50	-3.50	0.00	
7,400.0	1.29	53.74	7,367.2	380.2	518.4	642.8	3.50	-3.50	0.00	
7,430.8	0.21	53.74	7,398.0	380.4	518.7	643.2	3.50	-3.50	0.00	
Ohio Creek										
7,436.8	0.00	0.00	7,404.0	380.4	518.7	643.2	3.50	-3.50	-895.74	
Back to Vertical - Start 5680.0 hold at 7436.8 MD - Top of Gas - JG 3K 23B-3-3-97 TGT										
7,500.0	0.00	0.00	7,467.2	380.4	518.7	643.2	0.00	0.00	0.00	
7,596.8	0.00	0.00	7,564.0	380.4	518.7	643.2	0.00	0.00	0.00	
Williams Fork										
7,600.0	0.00	0.00	7,567.2	380.4	518.7	643.2	0.00	0.00	0.00	
7,700.0	0.00	0.00	7,667.2	380.4	518.7	643.2	0.00	0.00	0.00	

Database:	EDM 5000.1 Single User Db	Local Co-ordinate Reference:	Well Jimmy Gulch 3K 23B-3-3-97
Company:	Ursa Operating Company, LLC	TVD Reference:	Jimmy Gulch 3K 23B-3-3-97 @ 6733.5usft (Est KB)
Project:	Rio Blanco County, Colorado	MD Reference:	Jimmy Gulch 3K 23B-3-3-97 @ 6733.5usft (Est KB)
Site:	Jimmy Gulch 3K Pad	North Reference:	True
Well:	Jimmy Gulch 3K 23B-3-3-97	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
7,800.0	0.00	0.00	7,767.2	380.4	518.7	643.2	0.00	0.00	0.00	
7,900.0	0.00	0.00	7,867.2	380.4	518.7	643.2	0.00	0.00	0.00	
8,000.0	0.00	0.00	7,967.2	380.4	518.7	643.2	0.00	0.00	0.00	
8,100.0	0.00	0.00	8,067.2	380.4	518.7	643.2	0.00	0.00	0.00	
8,200.0	0.00	0.00	8,167.2	380.4	518.7	643.2	0.00	0.00	0.00	
8,300.0	0.00	0.00	8,267.2	380.4	518.7	643.2	0.00	0.00	0.00	
8,400.0	0.00	0.00	8,367.2	380.4	518.7	643.2	0.00	0.00	0.00	
8,500.0	0.00	0.00	8,467.2	380.4	518.7	643.2	0.00	0.00	0.00	
8,600.0	0.00	0.00	8,567.2	380.4	518.7	643.2	0.00	0.00	0.00	
8,700.0	0.00	0.00	8,667.2	380.4	518.7	643.2	0.00	0.00	0.00	
8,800.0	0.00	0.00	8,767.2	380.4	518.7	643.2	0.00	0.00	0.00	
8,900.0	0.00	0.00	8,867.2	380.4	518.7	643.2	0.00	0.00	0.00	
9,000.0	0.00	0.00	8,967.2	380.4	518.7	643.2	0.00	0.00	0.00	
9,100.0	0.00	0.00	9,067.2	380.4	518.7	643.2	0.00	0.00	0.00	
9,200.0	0.00	0.00	9,167.2	380.4	518.7	643.2	0.00	0.00	0.00	
9,300.0	0.00	0.00	9,267.2	380.4	518.7	643.2	0.00	0.00	0.00	
9,400.0	0.00	0.00	9,367.2	380.4	518.7	643.2	0.00	0.00	0.00	
9,500.0	0.00	0.00	9,467.2	380.4	518.7	643.2	0.00	0.00	0.00	
9,600.0	0.00	0.00	9,567.2	380.4	518.7	643.2	0.00	0.00	0.00	
9,700.0	0.00	0.00	9,667.2	380.4	518.7	643.2	0.00	0.00	0.00	
9,800.0	0.00	0.00	9,767.2	380.4	518.7	643.2	0.00	0.00	0.00	
9,900.0	0.00	0.00	9,867.2	380.4	518.7	643.2	0.00	0.00	0.00	
10,000.0	0.00	0.00	9,967.2	380.4	518.7	643.2	0.00	0.00	0.00	
10,100.0	0.00	0.00	10,067.2	380.4	518.7	643.2	0.00	0.00	0.00	
10,200.0	0.00	0.00	10,167.2	380.4	518.7	643.2	0.00	0.00	0.00	
10,300.0	0.00	0.00	10,267.2	380.4	518.7	643.2	0.00	0.00	0.00	
10,400.0	0.00	0.00	10,367.2	380.4	518.7	643.2	0.00	0.00	0.00	
10,500.0	0.00	0.00	10,467.2	380.4	518.7	643.2	0.00	0.00	0.00	
10,600.0	0.00	0.00	10,567.2	380.4	518.7	643.2	0.00	0.00	0.00	
10,700.0	0.00	0.00	10,667.2	380.4	518.7	643.2	0.00	0.00	0.00	
10,800.0	0.00	0.00	10,767.2	380.4	518.7	643.2	0.00	0.00	0.00	
10,900.0	0.00	0.00	10,867.2	380.4	518.7	643.2	0.00	0.00	0.00	
11,000.0	0.00	0.00	10,967.2	380.4	518.7	643.2	0.00	0.00	0.00	
11,066.8	0.00	0.00	11,034.0	380.4	518.7	643.2	0.00	0.00	0.00	
Cameo										
11,100.0	0.00	0.00	11,067.2	380.4	518.7	643.2	0.00	0.00	0.00	
11,200.0	0.00	0.00	11,167.2	380.4	518.7	643.2	0.00	0.00	0.00	
11,300.0	0.00	0.00	11,267.2	380.4	518.7	643.2	0.00	0.00	0.00	
11,400.0	0.00	0.00	11,367.2	380.4	518.7	643.2	0.00	0.00	0.00	
11,500.0	0.00	0.00	11,467.2	380.4	518.7	643.2	0.00	0.00	0.00	
11,566.8	0.00	0.00	11,534.0	380.4	518.7	643.2	0.00	0.00	0.00	
Rollins										
11,600.0	0.00	0.00	11,567.2	380.4	518.7	643.2	0.00	0.00	0.00	
11,700.0	0.00	0.00	11,667.2	380.4	518.7	643.2	0.00	0.00	0.00	
11,733.8	0.00	0.00	11,701.0	380.4	518.7	643.2	0.00	0.00	0.00	
Cozette Fm										
11,800.0	0.00	0.00	11,767.2	380.4	518.7	643.2	0.00	0.00	0.00	
11,900.0	0.00	0.00	11,867.2	380.4	518.7	643.2	0.00	0.00	0.00	
12,000.0	0.00	0.00	11,967.2	380.4	518.7	643.2	0.00	0.00	0.00	
12,090.8	0.00	0.00	12,058.0	380.4	518.7	643.2	0.00	0.00	0.00	
Corcoran										
12,100.0	0.00	0.00	12,067.2	380.4	518.7	643.2	0.00	0.00	0.00	

Database:	EDM 5000.1 Single User Db	Local Co-ordinate Reference:	Well Jimmy Gulch 3K 23B-3-3-97
Company:	Ursa Operating Company, LLC	TVD Reference:	Jimmy Gulch 3K 23B-3-3-97 @ 6733.5usft (Est KB)
Project:	Rio Blanco County, Colorado	MD Reference:	Jimmy Gulch 3K 23B-3-3-97 @ 6733.5usft (Est KB)
Site:	Jimmy Gulch 3K Pad	North Reference:	True
Well:	Jimmy Gulch 3K 23B-3-3-97	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
12,200.0	0.00	0.00	12,167.2	380.4	518.7	643.2	0.00	0.00	0.00	
12,300.0	0.00	0.00	12,267.2	380.4	518.7	643.2	0.00	0.00	0.00	
12,400.0	0.00	0.00	12,367.2	380.4	518.7	643.2	0.00	0.00	0.00	
12,500.0	0.00	0.00	12,467.2	380.4	518.7	643.2	0.00	0.00	0.00	
12,600.0	0.00	0.00	12,567.2	380.4	518.7	643.2	0.00	0.00	0.00	
12,700.0	0.00	0.00	12,667.2	380.4	518.7	643.2	0.00	0.00	0.00	
12,800.0	0.00	0.00	12,767.2	380.4	518.7	643.2	0.00	0.00	0.00	
12,900.0	0.00	0.00	12,867.2	380.4	518.7	643.2	0.00	0.00	0.00	
13,000.0	0.00	0.00	12,967.2	380.4	518.7	643.2	0.00	0.00	0.00	
13,100.0	0.00	0.00	13,067.2	380.4	518.7	643.2	0.00	0.00	0.00	
13,116.8	0.00	0.00	13,084.0	380.4	518.7	643.2	0.00	0.00	0.00	
TD at 13116.8 - BHL 39.8168498, -108.2677227										

Design Targets									
Target Name	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude
JG 3K 23B-3-3-97 TGT	0.00	0.00	7,404.0	380.4	518.7	1,188,262.70	2,222,656.42	39.816849800	-108.267722700
- hit/miss target									
- Shape									
- plan hits target center									
- Rectangle (sides W100.0 H40.0 D5,680.0)									


Formations						
Measured Depth (usft)	Vertical Depth (usft)	Name	Lithology	Dip (°)	Dip Direction (°)	
1,215.5	1,215.0	Green River Fm - Mahogany Bench		0.00		
1,272.8	1,272.0	Dissolution Surface		0.00		
2,410.9	2,404.0	Green River Fm - Garden Gulch Mbr		0.00		
2,636.0	2,628.0	Wasatch Fm		0.00		
5,090.0	5,069.0	Ft Union		0.00		
7,430.8	7,398.0	Ohio Creek		0.00		
7,436.8	7,404.0	Top of Gas		0.00		
7,596.8	7,564.0	Williams Fork		0.00		
11,066.8	11,034.0	Cameo		0.00		
11,566.8	11,534.0	Rollins		0.00		
11,733.8	11,701.0	Cozzette Fm		0.00		
12,090.8	12,058.0	Corcoran		0.00		

Database:	EDM 5000.1 Single User Db	Local Co-ordinate Reference:	Well Jimmy Gulch 3K 23B-3-3-97
Company:	Ursa Operating Company, LLC	TVD Reference:	Jimmy Gulch 3K 23B-3-3-97 @ 6733.5usft (Est KB)
Project:	Rio Blanco County, Colorado	MD Reference:	Jimmy Gulch 3K 23B-3-3-97 @ 6733.5usft (Est KB)
Site:	Jimmy Gulch 3K Pad	North Reference:	True
Well:	Jimmy Gulch 3K 23B-3-3-97	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1		

Plan Annotations				
Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates		Comment
		+N/-S (usft)	+E/-W (usft)	
0.1	0.1	0.0	0.0	SHL 39.815805543, -108.269569189
1,000.0	1,000.0	0.0	0.0	Start Build 3.50
1,168.3	1,168.0	5.1	7.0	Start 6100.2 hold at 1168.3 MD
4,015.3	4,000.0	177.9	242.5	Surface Casing
7,268.5	7,236.0	375.3	511.7	Start Drop -3.50
7,436.8	7,404.0	380.4	518.7	Back to Vertical
7,436.8	7,404.0	380.4	518.7	Start 5680.0 hold at 7436.8 MD
13,116.8	13,084.0	380.4	518.7	TD at 13116.8
13,116.8	13,084.0	380.4	518.7	BHL 39.8168498, -108.2677227



Well Name: Jimmy Gulch 3K 23B-3-3-97
 Surface Location: Jimmy Gulch 3K Pad
 North American Datum 1983 US State Plane 1983 Colorado Northern Zone
 Ground Elevation: 6712.5
 +N/-S +E/-W Northing Easting Latitude Longitude
 0.0 0.0 1187898.69 2222126.11 39.815805543 -108.269569189
 Est KB Jimmy Gulch 3K 23B-3-3-97 @ 6733.5usft (Est KB)



Azimuths to True North
 Magnetic North: 9.85°
 Magnetic Field
 Strength: 51649.3snT
 Dip Angle: 65.80°
 Date: 7/21/2017
 Model: IGRF2015

Jimmy Gulch 3K Pad
 Jimmy Gulch 3K 23B-3-3-97
 Design #1
 19:37, July 25 2017

WELLBORE TARGET DETAILS (MAP CO-ORDINATES AND LAT/LONG)

Name	TVD	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude	Shape
JG 3K 23B-3-3-97 TGT	7404.0	380.4	518.7	1188262.71	2222656.42	39.816849800	-108.267722700	Rectangle (Sides: L40.0 W100.0)

SECTION DETAILS

Sec	MD	Inc	Azi	TVD	+N/-S	+E/-W	Dleg	TFace	VSec	Target
1	0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.0	
2	1000.0	0.00	0.00	1000.0	0.0	0.0	0.00	0.00	0.0	
3	1168.3	5.89	53.74	1168.0	5.1	7.0	3.50	53.74	8.6	
4	7268.5	5.89	53.74	7236.0	375.3	511.7	0.00	0.00	634.6	
5	7436.8	0.00	0.00	7404.0	380.4	518.7	3.50	180.00	643.2	JG 3K 23B-3-3-97 TGT
6	13116.8	0.00	0.00	13084.0	380.4	518.7	0.00	0.00	643.2	

ANNOTATIONS

TVD	MD	Annotation
0.1	0.1	SHL 39.815805543, -108.269569189
1000.0	1000.0	Start Build 3.50
1168.0	1168.3	Start 6100.2 hold at 1168.3 MD
4000.0	4015.3	Surface Casing
7236.0	7268.5	Start Drop -3.50
7404.0	7436.8	Back to Vertical
7404.0	7436.8	Start 5680.0 hold at 7436.8 MD
13084.0	13116.8	TD at 13116.8
13084.0	13116.8	BHL 39.8168498, -108.2677227

FORMATION TOP DETAILS

TVDPath	MDPath	Formation	DipAngle	DipDir
1215.0	1215.5	Mahogany Bench	0.00	
1272.0	1272.8	Dissolution Surface	0.00	
2404.0	2410.9	Garden Gulch Mbr	0.00	
2628.0	2636.0	Wasatch Fm	0.00	
5069.0	5090.0	Ft Union	0.00	
7398.0	7430.8	Ohio Creek	0.00	
7404.0	7436.8	Top of Gas	0.00	
7564.0	7596.8	Williams Fork	0.00	
11034.0	11066.8	Cameo	0.00	
11534.0	11566.8	Rollins	0.00	
11701.0	11733.8	Cozzette Fm	0.00	
12058.0	12090.8	Corcoran	0.00	

