

## WORK OVER PROCEDURE

WELLNAME: **UPRR Pan Am 1-55**

API # 05-123-07249

Location: 660 FSL660 FWL SWSW 13 4N 63W 6th PM

SPUD DATE: 2/16/1971

SURFACE CASING SIZE: 8.625, 24 #/ft, 204', 12.25" hole

SURFACE CEMENT: Cemented to surface w/215 sx.

REMEDIAL CEMENT: NA

TD: 7155

AQUIFER DEPTH:

ORIGINAL COMPLETION

FORMATIONS:	As found in well:	UPRR Pan Am 1-55
	Niobrara	6290 '
	Codell	0 '
		'

REPLUGGING PROCEDURE:

- 1) MIRU ON LOCATION. ND WH, NU BOP, RU WORK FLOOR, CONTROL WELL, RU POWER SWIVEL
- 2) PU BIT, BIT SUB AND DRILL COLLAR
- 3) DRILL OUT 10 SX SURFACE PLUG
- 4) WASH DOWN TO SURFACE SHOE PLUG @ 170'
- 5) DRILL OUT PLUG FROM 170' - 290'
- 6) WASH DOWN TO 6240'. 50' ABOVE EST NIO TOP @ 6290'
- 7) CIRCULATE @ 6240'
- 8) MIRU CEMENTERS. ESTABLISH CIRCULATION, PUMP 100 SXS CEMENT 6240' - 5900'
- 9) TAG PLUG @ 6240'
- 10) TOH to 410'
- 11) PUMP 200 SX CMT TO SURFACE
- 9) ND BOP. CUT OFF BELL NIPPLE & CASING TO 4' BELOW GROUND LEVEL.  
FILL TOP OF CASING WITH READY MIX
- 10) WELD ON PLATE. OPERATOR NAME, API NO., LOCATION
- 11) FILL SURFACE HOLE, MAKING SURE TO REPLACE TOP SOIL LAST
- 12) RIG DOWN AND MOVE OUT ALL EQUIPMENT