
gyrodata
Directional Survey
Run 1
Run 2
Run 3
Run 4
Run 5
Run 6
Run 7
Run 8
Run 9
Run 10
Run 11
Run 12
Run 13
Run 14
Run 15
Run 16
Run 17
Run 18
Run 19
Run 20
Run

REPEAT PASS - Run with 1 PU
0 to 100 ft



Calibration Report

Database File	d:\warrior\data\2017-09-22_extraction_cssherwood 1-1-13_cbl\2017-09-22_extraction_cssherwood 1-1-13_c
Dataset Pathname	pass4.3
Dataset Creation	Fri Sep 22 13:57:11 2017

Gamma Ray Calibration Report

Serial Number:	ISHV2-03	
Tool Model:	2 3/4" TekCo	
Performed:	Tue Dec 13 00:23:06 2016	
Calibrator Value:	194.0	GAPI
Background Reading:	58.9	cps
Calibrator Reading:	300.8	cps
Sensitivity:	0.8020	GAPI/cps

Segmented Cement Bond Log Calibration Report

Serial Number:	IPPO2-01	
Tool Model:	2 3/4" RIB Analog	
Calibration Casing Diameter:	5.500	in
Calibration Depth:	0.000	ft

Master Calibration, performed (Derived):

	Raw (v)		Calibrated (mv)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
3'	0.002	1.281	0.000	72.000	56.304	-0.129
CAL	0.000	0.750				
5'	-0.003	1.898	0.000	72.000	37.876	0.122
SUM						
S1	0.019	1.175	0.000	50.000	43.244	-0.813
S2	0.027	1.017	0.000	50.000	50.524	-1.388
S3	0.036	0.986	0.000	50.000	52.587	-1.867
S4	0.033	0.923	0.000	50.000	56.193	-1.864
S5	0.031	1.002	0.000	50.000	51.494	-1.602
S6	0.022	1.140	0.000	50.000	44.725	-1.005
S7	0.017	1.330	0.000	50.000	38.070	-0.636
S8	0.020	1.295	0.000	50.000	39.214	-0.800

Internal Reference Calibration, performed Fri Aug 25 16:15:12 2017:

	Raw (v)		Calibrated (v)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
CAL	0.000	0.750	0.000	0.750	1.000	0.000

Air Zero Calibration, performed Fri Aug 25 16:15:12 2017:

	Raw (v)	Calibrated (v)	Results
	Zero	Zero	Offset
3'	0.000	0.000	0.000
5'	0.000	0.000	0.000
SUM			
S1	0.000	0.000	0.000
S2	0.000	0.000	0.000
S3	0.000	0.000	0.000
S4	0.000	0.000	0.000
S5	0.000	0.000	0.000
S6	0.000	0.000	0.000
S7	0.000	0.000	0.000
S8	0.000	0.000	0.000

Temperature Calibration Report

Serial Number:	IPPO2-01			
Tool Model:	2 3/4" RIB Analog			
Performed:	Fri Aug 26 11:07:15 2016			
	Reference		Reading	
Low Reference:	0.00	degF	0.00	usec
High Reference:	1.00	degF	1.00	usec
Gain:	0.33			
Offset:	0.00			
Delta Spacing	1			

Sensor	Offset (ft)	Schematic	Description	Length (ft)	O.D. (in)	Weight (lb
			CableHead-TitanConeType2	1.03	1.44	3.60
CCL	18.96		CCL_Log-2 3/4" TekCo (IPSN7-03) 450 Deg. CCL	1.83	2.75	33.00
			TekCo-275_Tekco 2 3/4" Tekco Adjustable SPRING Centralizer	2.73	2.75	25.00
TEMP	12.78					
WVFS8	11.49		RBTA-2 3/4" RIB Analog (IPPO2-01) Radial Incremented Bond Tool with Temp	9.13	2.75	102.00
WVFS7	11.49					
WVFS6	11.49					
WVFS5	11.49					
WVFS4	11.49					
WVFS3	11.49					
WVFS2	11.49					
WVFS1	11.49					
WVF3FT	10.74					
WVF5FT	9.74					
WVFSYNC	6.41					
WVFTEMP	6.41					
WVFCAL	6.41		TekCo-275_Tekco 2 3/4" Tekco Adjustable SPRING Centralizer	2.73	2.75	25.00
			GR_Log-2 3/4" TekCo (ISHV2-03) 400 Deg. Gamma Ray	3.68	2.75	47.00
GR	1.04					
LOCTIM	0.00					
UTCTIM	0.00					

Dataset:	2017-09-22_extraction_cssherwood 1-1-13_cbl.db: field/well/run1/pass4.3
Total length:	21.13 ft
Total weight:	235.60 lb
O.D.:	2.75 in

gyrodata

Company	Extraction Oil and Gas		
Well	CS Sherwood 1-1-13		
Field	Wattenberg		
County	Weld		
State	Colorado	Country	U.S.A.