



SRC ENERGY

Operator: SRC Energy
Well Name: Hergert 8-43
Legal: SWSE, Section 8, Township 6N, Range 66W
Location: Weld County, CO
API: 05-123-22693
Surface: 8.625" 24# @ 839' **Hole Size:** 12.25" **TOC:** Surface
Production: 4.5" 11.6# @ 7,405' **Hole Size:** 7.875" **TOC:** 6,430' (CBL) & 0' (CALC)
Perforations: 6,908' – 7,256' (Niobrara-Codell)
TD: 7,405'

P&A Procedure

1. Conduct pre-job safety meeting and complete daily JSA
2. Blow down well if necessary, circulate hole with treated water
3. Dig out around wellhead and perform bradenhead test
4. MIRU WO unit, ND wellhead, NU BOP, tally all pipe
5. TIH w/ 4-1/2" 11.6# CIBP, set at 6,833'
6. Run CBL, ensure adequate cement for remedial plug
7. Pressure test casing to 500 psi for 15 minutes
8. Set 13 sx on top of CIBP (cover 200' above Niobrara top)
9. TIH to 3,800' and pump casing plug (300' plug)
 - a. Pump 29 sx to create casing plug (3,500' – 3,800')
10. TIH to 1000' and pump surface plug (0' – 1000')
 - a. 95 sx of 15.8# class G neat 1.15 cu./ft. yield cement
 - b. 161' out of surface casing
 - c. Wait 4 hours and tag plug
11. RDMO WO unit
12. Dig up wellhead and cut off 10' below restored ground level, top off if necessary
13. Weld on cap with ID plate, inscribed with well location, and identity
14. Backfill, clean location
15. P&A complete