



SRC ENERGY

Operator: Trans-Era Petroleum, Inc.
Well Name: State 1
Legal: NWNE, Section 16, Township 6N, Range 66W
Location: Weld County, CO
API: 05-123-05233
Surface: 10.75" 32.75# @ 382' **Hole Size:** 14.75" **TOC:** Surface
Production: N/A **Hole Size:** 9.5" (382'-9,091') **TOC:** N/A
TD: 9,091'

P&A Procedure

1. Conduct pre-job safety meeting and complete daily JSA
2. Dig out to find wellhead and check pressure
3. Cut cap off, extend surface pipe to achieve ground level
4. MIRU WO unit, ND wellhead, NU BOP, tally all pipe to be ran in well
5. Mill through 2 cement plugs in surface casing.
 - a. Surface plug – 15 sx (≈30' plug)
 - b. SC Shoe plug – 15 sx (≈30' plug)
6. Wash run to depth that well allows
7. TOOH, remove BHA for milling
8. TIH to 6,800' based off of pipe tally and pump a 500' plug (6,300'-6,800')
 - a. 268 sx of 15.8# class G neat 1.15 cu/ft yield cement
 - b. Wait 4 hours and tag plug
9. TIH to 4,250' based off of pipe tally and pump a 250' plug (4,000'-4,250')
 - a. 134 sx of 15.8# class G neat 1.15 cu/ft yield cement
 - b. Wait 4 hours and tag plug
10. TIH to 800' based off of pipe tally and pump a 800' surface plug (0'-800')
 - a. 460 sx of 15.8# class G neat 1.15 cu/ft yield cement
 - b. Wait 4 hours and tag plug
11. RDMO WO unit
12. Remove extension of surface pipe. Top off if necessary.
13. Weld on cap with ID plate, inscribed with well location, and identity
14. Backfill, clean location
15. Re-Entry to Re-plug complete