




OFFICE OF STATE OIL INSPECTOR  
Oil and Gas Conservation  
Department

Locate  
Well  
Correctly



LOG OF OIL AND GAS WELL

OIL & GAS  
CONSERVATION COMMISSION

Company The Texas Company Address Box 1346 - Casper, Wyoming  
State or Patented Field Luft State Colorado  
Well No. 1 Sec. 17 T. 8N R. 53W Meridian 6 PM County Logan  
Location 330 Ft. (N) of S Line and 330 Ft. (E) of W line of NE Elevation 4190 KB  
(Derrick floor relative to sea level) 4177 GR

The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records.

Date March 20, 1953 Signed Walter Raul Title District Superintendent

The summary on this page is for the condition of the well as above date.

Commenced drilling Aug. 1, 1952 Finished Drilling Aug. 19, 1952

OIL SANDS OR ZONES

No. 1, from 4818' to 4828' No. 4, from \_\_\_\_\_ to \_\_\_\_\_  
No. 2, from \_\_\_\_\_ to \_\_\_\_\_ No. 5, from \_\_\_\_\_ to \_\_\_\_\_  
No. 3, from \_\_\_\_\_ to \_\_\_\_\_ No. 6, from \_\_\_\_\_ to \_\_\_\_\_

IMPORTANT WATER SANDS

No. 1, from \_\_\_\_\_ to \_\_\_\_\_ No. 3, from \_\_\_\_\_ to \_\_\_\_\_  
No. 2, from \_\_\_\_\_ to \_\_\_\_\_ No. 4, from \_\_\_\_\_ to \_\_\_\_\_

CASING RECORD

Size	Weight per ft.	Threads per inch	Make	Amount	Kind of Shoe	Cut & Pulled from	Perforated From to	Purpose
10-3/4"	32.75		R-2	161'	Howco	Guide Shoe	1.35	Surface
					Howco	Float Collar	1.40	
5-1/2"	15.50		R-2	4890'	Howco	Guide Shoe	1.66	Production
					Howco	Float Collar	1.41	

MUDDING AND CEMENTING RECORD

Size	Where Set	No. Sacks of Cement	Methods used	Mud Gravity	Amount of Mud Used
10-3/4"	176'	150	Howco		
5-1/2"	4880'	300	Howco		

PLUGS AND ADAPTERS

Heaving plug-Material \_\_\_\_\_ Length \_\_\_\_\_ Depth Set \_\_\_\_\_  
Adapters-Material \_\_\_\_\_ Size \_\_\_\_\_

SHOOTING RECORD

Size	Shell Used	Explosive Used	Quantity	Date	Depth Shot	Depth Cleaned Out

TOOLS USED

Rotary Tools used from 0 ft. to 5000 ft. and from \_\_\_\_\_ ft. to \_\_\_\_\_ ft.  
Cable tools were used from -- ft. to -- ft. and from \_\_\_\_\_ ft. to \_\_\_\_\_ ft.

DATES

19 Put to producing Sept. 29, 1952  
The production for the first 24 hours was 288 barrels of fluid of which  
100 % was oil, \_\_\_\_\_ % emulsion; \_\_\_\_\_ % sediment. Gravity Be, \_\_\_\_\_  
If gas well, cu. ft. per 24 hours \_\_\_\_\_ Gallons gasoline per 1,000 cu. ft.  
of gas \_\_\_\_\_ Rock Pressure, lbs. per sq. in \_\_\_\_\_

EMPLOYEES

A. J. Klein Driller \_\_\_\_\_, Driller  
E. A. Coleman Driller \_\_\_\_\_, Driller

FORMATION RECORD

From \_\_\_\_\_ To \_\_\_\_\_ Total Feet \_\_\_\_\_ Formation \_\_\_\_\_

COGC  
U of C  
COLO. SCH. MINES  
TTF  
WR  
MME