



UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

Colo. 02763

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Cache Unit

8. FARM OR LEASE NAME

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Cache

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

**SE/4 Section 34,
T-33-N, R-20-W**

12. COUNTY OR PARISH

Montezuma

13. STATE

Colorado

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ **Water Injection**

RECEIVED

MAR 12 1968

2. NAME OF OPERATOR

PAN AMERICAN PETROLEUM CORPORATION

COLO. OIL & GAS CONS. COMM

3. ADDRESS OF OPERATOR

501 Airport Drive, Farmington, New Mexico 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FEL & 1900' FEL

14. PERMIT NO.

65 203

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4949' Gr.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☒

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

Convert to water injection

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

It is planned to convert the well to water injection as follows:

1. Pull rods, pump, and tubing.
2. Drill out cement to 5660'.
3. Perforate 5624-46' with 4 SPF and acidize with 500 gallons 28% HCl.
4. Acidize perforations 5502-11', 5565-71', 5576-83', 5593-98' with 1500 gallons 28% HCl.
5. Run Baker Model "W" Packer to be set at 5530'.
6. Put well on injection.

DVR	
FJP	<input checked="" type="checkbox"/>
HUM	<input checked="" type="checkbox"/>
JAN	<input checked="" type="checkbox"/>
JJD	<input checked="" type="checkbox"/>

18. I hereby certify that the foregoing is true and correct.

SIGNED

Lloyd A. Chien

TITLE

Petroleum Engineer

DATE

March 11, 1968

(This space for Federal or State office use)

APPROVED BY

W. A. Rogers

TITLE

Director

DATE

MAR 14 1968

CONDITIONS OF APPROVAL, IF ANY: