



UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

Colo. 02763

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Cache Unit

8. FARM OR LEASE NAME

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Cache

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

22/4 Section 34,  
T-35-N, R-20-W

12. COUNTY OR PARISH

Montezuma

13. STATE

Colorado

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/> <b>Water Injection</b>	RECEIVED APR 11 1968
2. NAME OF OPERATOR <b>PAN AMERICAN PETROLEUM CORPORATION</b>	COLO. OIL & GAS CONS. COMM.
3. ADDRESS OF OPERATOR <b>501 Airport Drive, Farmington, New Mexico 87401</b>	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface <b>660' TEL &amp; 1980' TSL</b>	
14. PERMIT NO. <b>13 203</b>	15. ELEVATIONS (Show whether DF, RT, GR, etc.) <b>4949' GR</b>

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) **Convert to Water Injection**

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL


ALTERING CASING

ABANDONMENT\*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

The well was converted to water injection in the following manner:

1. Pulled rods, pump and tubing.
2. Drill out cement to 5660'.
3. Perforated 5624-46' with 4 SPF and acidized with 500 gallons 28% HCl.
4. Acidized perforations 5565-71, 5576-83, 5593-98 with 1500 gallons 28% HCl.
5. Ran Baker Model N packer set at 5490.
6. Put well on injection 3-29-68.



18. I hereby certify that the foregoing is true and correct

SIGNED

**L. A. Chism**

TITLE

**Petroleum Engineer**

DATE **April 3, 1968**

(This space for Federal or State office use)

APPROVED BY

**J. H. Rogers**

TITLE

**Director**

DATE

**APR 12**