

WELL SERVICE REPORT

STATE ANDERSON 1-36

NW NE

SEC 36-T5N-R68W

LARIMER COUNTY, COLORADO

WELL DATA:

| | | | | | | |
|--------------|---------------------------------|-------|-------|-------|----------|-------|
| ELEVATIONS | G.L. | 4892' | K.B. | 4903' | T.D. | 7655' |
| PROD CSG | 4 1/2" 11.6# N-80 LTC @ | 7658' | | | | |
| PERFORATIONS | | | | | | |
| CODELL | 7056' | - | 7080' | 4 SPF | 96 HOLES | |
| J-SAND | 7526' | - | 7553' | 2 SPF | 55 HOLES | |
| PROD TBG | 2 3/8", 4.7# J-55, EUE 8RD | | | | | |
| CIBP | 4 1/2" SET @ 7420' | | | | | |
| PBTD | FLOAT @ 7641' SAND FILL @ 7626' | | | | | |

PROCEDURE

7-Jan-97

MIRU POS RIG #3, KILL WELL W/40 BBL 2% KCL. DISMANTLE WELL HEAD. POOH LAYING DOWN 2 3/8" PROD TBG. (233 JTS) RIG UP BRAND-X WIRELINE, RUN 3.81" GAUGE RING TO 7450'. RUN AND SET 4 1/2" CIBP @ 7420'. RIH W/3 1/8" DML GUN & PERFORATE FROM 7056' TO 7080', 4 SHOTS PER FOOT (96 HOLES).

RD WIRELINE, RU DUMP BAILER ON SANDLINE & SPOT 2 SKS. 20/40 SAND ON CIBP. LAY DOWN DUMP BAILER. SHUT WELL IN. SDFN.

8-Jan-97

65 PSI ON WELL, BLOW WELL DOWN. PICK UP 4 1/2" LOCK-SET PKR & 2 7/8" N-80 SLIM-HOLE TBG. RIH AS FOLLOWS:

| | |
|--|-----------|
| 4 1/2" X 2 3/8" LOCK-SET PKR | 3.40 ' |
| 2 7/8" X 2 3/8" HP SWEDGE W/ 2 7/8" FULL HOLE COLLAR | 0.80 |
| 2 7/8" API SN W/FULL HOLE COLLAR | 1.20 ' |
| 228 JTS 2 7/8" N-80 SLIM-HOLE TBG | 7021.74 ' |
| | 7027.14 |

SET PKR. PACK WELL HEAD OFF. LOAD CSG W/51 BBL 2% KCL & PRESSURE TEST TO 500 PSI. PICK-UP SWAB & MAKE 1 RUN. SFL 5800' 200' FREE OIL. SHUT WELL IN. SDFN.

9-Jan-97

47 PSI ON TBG. BLOW WELL DOWN. RIH W/TBG SWAB. SFL 6600' 125' FREE OIL. LAY DOWN SWAB. SHUT WELL IN. RDMO

RON DOZIER