




COLORADO OIL AND GAS CONSERVATION COMMISSION  
SUNDRY NOTICES AND REPORTS OF WELLS



**075-06659**

OIL & GAS  
CONSERVATION COMMISSION

(Indicate nature of data by checking below)

Notice of intention to drill \_\_\_\_\_  
 Notice of intention to change plans \_\_\_\_\_  
 Notice of date for test of water shut-off \_\_\_\_\_  
 Report on result of test of water shut-off \_\_\_\_\_  
 Notice of intention to re-drill or repair well \_\_\_\_\_  
 Notice of intention to clean out well \_\_\_\_\_  
 Statement of shooting \_\_\_\_\_  
 Statement of perforating \_\_\_\_\_  
 Notice to pull or otherwise alter casing \_\_\_\_\_  
 Notice of intention to abandon well XX  
 Report of work done on well since previous report XX

Following is a (notice of intention to do work) July 3, 19 52  
 (report of work done) (On land) (patented) described as follows:

Colorado Logan West Padroni  
 State County Field  
5-27  
3 Francis Parke SW 1/4 SE 1/4 Sec. 31 10N 52W 6th P.M.  
 (Well No.) (Lease) (Sec. and 1/4 Sec.) (Twp.) (Range) (Meridian)  
 The well is located 330 ft. (N) of South Line and 990 ft. (E) of West  
Line SW 1/4 SE 1/4

The elevation above sea level is 4054 ft.

Details of Plan of Work: (State names of and expected depths to objective sands:  
 Show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement-  
 ing points, and all other important proposed work.)

Having drilled the above well to a depth of 5267-TD, having cored and drill stem tested  
 as shown in detail on the well log attached, and having run Schlumberger electric log  
 and finding no oil or gas in commercial quantities in any zone, we propose to plug and  
 abandon the well as follows:

1 Spot 25 sacks cement	5267-TD	-	5207
Fill hole w/heavy mud	5207	-	5090
3 Spot 25 sacks cement	5090	-	5030
Fill hole w/heavy mud	5030	-	4820
5 Spot 25 sacks cement	4820	-	4760
Fill hole w/heavy mud	4760	-	4690
7 Spot 25 sacks cement	4690	-	4630
Fill hole w/heavy mud	4630	-	310
9 Spot 25 sacks cement	310	-	250
Fill hole w/heavy mud	250	-	10
11 Spot 5 sacks cement	10	-	0.

We will weld steel plate on top of 10-3/4" casing.

We will back fill the pits w/earth and clean the well site.

(3) COPIES WELL LOG ATTACHED.

(1) COPY ELECTRIC LOG ATTACHED.

Approved: JUL 25 1952

Director

Company SINCLAIR OIL & GAS COMPANY  
P. O. Box 1809 % J. B. Kennedy  
 Address Casper, Wyoming

By

Title Asst. Division Supt.

Submit reports of proposed work, for approval, on this form in Duplicate for patented  
 lands and in Triplicate for school and state lands.

