



H2S CONTINGENCY PLAN

CB-4

Table of Contents

I. INTRODUCTION	3
II. TRAINING PROGRAM	3
III. SITE IDENTIFICATION.....	4
IV. KEY PERSONNEL RESPONSIBILITIES	4
A. All Personnel.....	4
B. Drilling Supervisor	4
V. RESCUE AND MANAGEMENT PERSONNEL	4
VI. WELL SITE	5
A. Rig Layout and Equipment	5
B. Access, Egress and Roads	5
C. PPE for Essential Personnel.....	5
D. H2S Detection and Monitoring Equipment.....	5
E. Visual Warning Systems	5
F. Operating Conditions	6
VIII. METALLURGY	7
VIII. WELL CONTROL	8
A. Equipment	8
B. Testing and Inspection.....	8
IX. MUD PROGRAM	8
X. PROCEDURES.....	8
A. Operating	8
B. Emergency.....	9
Appendix A: Emergency Contact List	11
Appendix B: Rig Layout and Equipment.....	13
Appendix C: Access, Egress and Roads	14
Appendix D: Radius of Exposure	16
Appendix E: Well Control Equipment	19

I. INTRODUCTION

H₂S is a toxic, poisonous gas that could cause death or injury. The objective of this contingency plan is to provide an organized plan of action for alerting and protecting the public from H₂S exposure in the event a potentially hazardous volume is accidentally released to the atmosphere. This plan should be activated immediately if any such release occurs. The Drilling Supervisor is responsible for initiating and carrying out the plan.

II. TRAINING PROGRAM

All personnel associated with the drilling operations will receive training to insure efficient and correct action in various potential situations. This training will be in the general areas of: (1) personnel safety, (2) rig operations, and (3) well control procedures.

A. Personnel Safety Training – All personnel shall have received H₂S training in the following areas:

1. Hazards and characteristics of H₂S.
2. Effect on metal components of the system.
3. Safety precautions.
4. Operation of safety equipment and life support systems.
5. Corrective action and shutdown procedures.

B. Rig Operations – All rig personnel shall have received training in the following areas:

1. Well control procedures.
2. Layout and operations of the well control equipment.

NOTE: Proficiency will be developed through BOP drills which will be documented by the Drilling Superintendent.

C. Service Company Personnel – All service personnel shall have been trained by their employers in the hazards and characteristics of H₂S and the operation of safety equipment and life support systems.

D. Visitors – All first time visitors to the location will be required to attend a safety orientation. The Drilling Superintendent shall be responsible for this orientation and he shall see that every visitor is logged in correctly.

E. Public – The public within the area of exposure shall be given an advance briefing by Kinder Morgan personnel or representative. This briefing must include the following elements:

1. Hazards and characteristics of hydrogen sulfide. It is an extremely dangerous gas. It is normally detectable by its “rotten egg” odor, but odor is not a reliable means of detection because the sense of smell may be dulled or lost due to intake of the gas. It is colorless, transparent, and flammable. It is heavier than air and may accumulate in low places.
2. The necessity of an emergency action plan. Due to the danger of persons exposed to hydrogen sulfide and the need for expeditious action should an emergency occur, this action plan will be put into effect if a leak occurs.
3. The location of hydrogen sulfide within the area of exposure at the drilling location.

4. The manner in which the public will be notified of an emergency is by telephone or in person.
5. Steps to be taken in case of an emergency:
 - a. Abandon danger area.
 - b. Notify necessary agencies and request assistance for controlling traffic and evacuating people.

III. SITE IDENTIFICATION

Operator Name: Kinder Morgan
Well Name: Cow Canyon B4 (CB-4)
Lat / Long: 37.56141 N / 108.92479 W
Legal Location: 949' FSL & 906' FEL S10, T38N, R19W NMPM
API Number: TBD

IV. KEY PERSONNEL RESPONSIBILITIES

It is the responsibility of all personnel on the location to familiarize themselves with the procedures outlined in this contingency plan.

A. All Personnel

1. Are responsible for their assigned safety equipment.
2. Are responsible for familiarizing themselves with the location of all safety equipment.
3. Are responsible for reporting any indications of H2S to those in the area and to a supervisor.

B. Drilling Supervisor

1. Is responsible for thoroughly understanding and seeing that all aspects of this contingency plan are enforced.
2. Is responsible for implementing all phases of this contingency plan.
3. Is responsible for keeping a minimum of personnel on the location during expected hazardous operations.
4. Is responsible for coordinating all well site operations and communications in the event that an emergency condition develops.
5. Is responsible for ensuring that all visitors receive an H2S Safety Orientation. A visitor's log will be maintained as well as a list of all personnel on the location after drilling has progressed to the suspected H2S formation.

V. RESCUE AND MANAGEMENT PERSONNEL

See Appendix A for the Emergency Contact List

VI. WELL SITE

A. Rig Layout and Equipment

There will be at least two pre-determined safe areas on location in the event of an emergency. These locations should be located 180 degrees to one another, and in the direction of the prevailing winds. See Appendix B.

B. Access, Egress and Roads

See Appendix B and C

C. PPE for Essential Personnel

The location and type of all air masks will remain the same for all drilling locations. Self-contained breathing apparatus for use by rig personnel will be kept in the following location(s):

Type: 1-30 Min. Rescue Unit	Location: Drilling Supervisor's Trailer
Type: 1-30 Min. Rescue Unit	Location: Tools Pusher's Trailer
Type: 2-30 Min. Rescue Units	Location: Briefing Area #1
Type: 2-30 Min. Rescue Units	Location: Briefing Area #2
Type: 5-5 Min. Escape Units	Location: Rig Floor

If a cascade system is utilized, indicate the locations(s):

Type:	Location:
Type:	Location:

Testing and calibration records are maintained on location.

D. H2S Detection and Monitoring Equipment

See Appendix D. The rig's H2S monitor contains three (3) heads. One located at the bell nipple, one located at the shale shaker, and one on the rig floor. Personal H2S monitors are worn by all personnel on location. Indicate here any other additional H2S detector locations for this well:

Type:	Location:
Type:	Location:

Testing and calibration records are maintained on location.

E. Visual Warning Systems

The location of windsocks or streamer will remain the same for all drilling locations. The wind direction indicators for this well will be located at:

Type: Windsock	Location: Briefing Area #1
Type: Windsock	Location: Briefing Area #2
Type: Windsock	Location: Pits
Type: Windsock	Location: Rig Floor

4. The Drilling Supervisor will initiate action to reduce the H₂S concentration to zero.

CONDITION III – Moderate to Extreme Danger to Life

Characterized by: H₂S present in concentrations at or above 10 PPM. Critical well operations or well control problems. In the extreme, loss of well control.

Warning Flag: Red

Alarm: Flashing light and continuous blast on horn at 10 PPM H₂S.

Probable Occurrence: 1. As drill gas.
2. As trip gas when circulating bottoms up.
3. When a core barrel is pulled.
4. When a well kick is circulated out.
5. Surface pressure, well flow or lost returns.
6. Equipment failure during testing operations.

General Action: 1. Put on breathing equipment. Move to “SAFE BRIEFING AREA” and remain there if not working to correct the problem.
2. Follow instructions of Drilling Supervisor or other supervisor.
3. The Drilling Supervisor will initiate emergency action as provided in the contingency plan and as appropriate to the actual conditions. If testing operations are in progress, the well will be shut in.
4. The Drilling Supervisor will conduct any necessary operations with an absolute minimum of personnel. All persons in the immediate area will wear a breathing apparatus. All other personnel will restrict their movements to those directed by the Drilling Supervisor.
5. If gas containing H₂S is ignited, the burning H₂S will be converted to sulfur dioxide (SO₂), which is poisonous.

VIII. METALLURGY

When operating in a zone with H₂S present, certain equipment will be used that is constructed of materials with metallurgical properties that resist or prevent sulfide stress cracking and other failure modes. The following will be in effect:

- A. An effective means will be used for monitoring and controlling corrosion caused by acid gases (H₂S and CO₂) in both downhole and surface portions of a production system.
- B. Metals used for sensing lines and safety control devices which are necessarily exposed to H₂S bearing fluids must be constructed of H₂S corrosion resistant materials or coated so as to resist H₂S corrosion.
- C. H₂S resistant materials will be used for all elastomer seals.

Additionally because CO₂ is produced from the reservoir, all materials exposed to the production stream are CO₂ compliant.

VIII. WELL CONTROL

A. Equipment

See Appendix E

B. Testing and Inspection

Routine blowout preventer assembly pressure and operating tests shall be made:

1. following installation of assembly and prior to drilling out after each string of casing is set
2. at least monthly while drilling
3. prior to drilling into a known abnormally pressured section
4. following repairs or replacement that require disconnecting a pressure seal in the assembly
5. any other time deemed necessary by the Kinder Morgan Representative

Preventer operating tests will be performed on each round trip but not more than once per day.

IX. MUD PROGRAM

Hole Size: 8-3/4"

Mud Type: Salt saturated brine

pH: 11+, as required to control H₂S

Maximum salt concentration expected: 190,000 ppm

Problems: H₂S, Paradox Salt Shale gas influx, hole cleaning

Displace the fresh water system with salt saturated brine 100' above the Desert Creek formation. Circulate through the closed loop system to maintain a clean fluid and to assist in breaking out any entrained gas.

Pre-treat mud for H₂S prior to drilling the P4 Shale.

Follow the guidelines for drilling the Paradox Salt Shale, titled "Paradox Salt Drilling Procedure", which is located in Appendix A of the drilling prognosis. The recommendations have proven to be very successful in recent drilling programs.

X. PROCEDURES

A. Operating

The following operating procedures will be utilized for drilling in areas with H₂S.

1. Any gas kick will be controlled by using approved well control techniques. Upon evidence that ambient H₂S concentrations have reached 10 PPM, all non-essential personnel will be evacuated to pre-determined safe areas. Personnel remaining on the rig floor will continue to control the well until the situation indicates the area is safe to re-enter.
2. Special Operations

- a. Drill Stem Tests. All drill stem tests must be closed chamber and conducted during daylight hours.
- b. Coring. After a core has been cut, circulate bottoms up and monitor for H2S. If hole conditions (and/or detectors) indicate potentially hazardous conditions, put breathing equipment on 10 stands before core barrel reaches the surface. Breathing equipment will be worn by all personnel while core barrel is pulled, broken out and opened up, and until a safe atmosphere is indicated.

B. Emergency

The procedures listed below apply to drilling and testing operations.

1. If at any time during Condition I, the Mud Logger, Mud Engineer, or any other person detects H2S, he will notify the Drilling Supervisor. All personnel should keep alert to the Drilling Supervisor's orders.

He will:

- a. Immediately begin to ascertain the cause or the source of the H2S and take steps to reduce the H2S concentration to zero. This should include having the mud engineer run a sulfide and Ph determination on the flowline mud if water-base mud is in use. If an oil-base mud is in use, the Mud Engineer should check the lime content of the mud.
 - b. Order non-essential personnel out of the potential danger area.
 - c. Order all personnel to check their safety equipment to see that it is working properly and in the proper location. Persons without breathing equipment will not be allowed to work in a hazard area.
 - d. Notify the Rig Supervisor of the condition and action taken.
 - e. Increase gas monitoring activities with portable H2S detectors and continue operations with caution.
 - c. Display the orange warning flag.
2. If the H2S concentration exceeds 10 PPM the following steps **will** be taken:
- a. Put on breathing equipment.
 - b. Display red flag.
 - c. Driller – prepare to shut the well in.
 - i. Ensure tool joint out of BOP's
 - ii. Close BOP's if necessary.
 - d. If testing operations are in progress, the well will be shut-in.
 - e. Help anyone who may be affected by gas.
 - f. Evacuate quickly to the "SAFE BRIEFING AREA" if instructed or conditions warrant.
3. In the event a potentially hazardous volume of H2S is released into the atmosphere, the following steps must be taken to alert the public:

- a. Remove all rig personnel from the danger area and assemble at a pre-determined safe area, preferably upwind from the well site.
- b. Alert the drilling office, public safety personnel, regulatory agencies, and the general public of the existence and location of an H₂S release. See attached emergency contact list.
- c. Assign personnel to block any public road (and access road to location) at the boundary of the area of exposure. Any unauthorized people within the area should be informed that an emergency exists and be ordered to leave immediately.
- d. Request assistance from public safety personnel to control traffic and/or evacuate people from the threatened area.

H₂S Contingency Plan Emergency Contact List

Well Name: Cow Canyon B-4 (CB-4)

API #: TBD

Date of Completion: _____

Date of Release: _____


NAME	ADDRESS	PHONE	# RESIDENT	Relocated Yes/No	Comments
Barry Swift - KM Engineering Manager		C: 432-638-6209			
		O: 970-882-5545			
Chris Lopez - KM Project Manager		C: 505-699-9832			
		O: 970-882-5537			
Valerie Cawthorn - KM Drilling Engineer		C: 281-798-8769			
		O: 713-369-8509			
		C:			
		O:			
		C:			
		H:			
		C:			
		H:			
		C:			
		H:			
		C:			
		H:			
		C:			
		H:			

Notes: _____


Submit Completed Form to KM Drilling Engineer, Drilling Superintendant and Regulatory Manager

Appendix C: Access, Egress and Roads

Well Pad Map



Topographic Map



HYDROGRAPHY:		WELLS:		
FEATURE	PRESENT WITHIN 1 MILE	API/PERMIT #	OWNER	STATUS
Intermittent Stream	Yes	05-083-06407	Kinder Morgan	PR
*No additional hydrography features have been identified within 1 mile of the proposed facility.		05-083-06572	Ballard Petroleum	AL
		05-083-06576	Ampolex	DA
PR - Producing AL - Abandoned Location DA - Dry and Abandoned *No known water wells exist within 1 mile of the proposed facility				
HILL COMPLIANCE SOLUTIONS, INC. Environmental Consultants				

KINDER MORGAN

Hydrology and Wells Map


CB-4 CO₂ Well Pad, Access, and Pipeline

37.501302 -108.024082
 Section 10, Township 38 North, Range 19 West

Features ● Active Gas Wells (Top Hole) □ Well Pad — Pipeline	■ Access and Pipeline ROW □ 1 Mile Buffer Transportation — Local Roads
Author: E. Fought Revisor: Date: 11/15/2017	

Appendix D: Radius of Exposure

Location Map




Pasquill-Gifford Model

CB-4


CB-4						
Scenario:	9/7/2017					
flow rate, Q, cubic feet/day:		1,066,000				
H2S, mole %:		0.10%				
feet to 100 ppm radius of exposure:		105				
feet to 500 ppm radius of exposure:		48				
100 ppm radius of exposure = $[1.589(\text{mole fraction H}_2\text{S})(Q)]$ to the power of 0.6258, where Q is ft ³ /day						
500 ppm radius of exposure = $[0.4546(\text{mole fraction H}_2\text{S})(Q)]$ to the power of 0.6258, where Q is ft ³ /day						

Radius of Exposure Map



Appendix E: Well Control Equipment

Blowout Preventer



Choke Manifold

