



Service Order #: 70205

Date: 07-Apr-18

Well Name	Location	County	St	API#		
WEYERMAN 6B-18		YUMA	CO	05-125-09207-00		
Formation	Cement Via	Type Of Service	Well Type	Age	AFE#	PO#
	CASING	PLUG		REWORK		

Customer: PRIME OPERATING COMPANY

Remarks: SAFETY MEETING  
13.6 BBLS, 66 SKS  
ANNULUS 311'-0'  
CASING 325'-0'

Customer Rep: TOM

PH:

WELLBORE DATA				
Type	Size	Weight	Depth	Volume
Surface Casing:	7.000	20.0	262.0	
Production Casing:	4.500	11.6	325.0	
Intermediate:				
Drill Pipe:				
Tubing:				

Type	Size	Depth (Top)	Depth (Bot)	Volume
Liner:				
Open Hole:	6.250	262.0	311.0	

OTHER DATA		
BHT	Max PSI	Total Depth

Packer or RetainerType / Depth:

CIBP	325.0
------	-------

Perf Depths:		#	Total
310.0	311.0	0	0
		0	
		0	

TIME	PUMP RATES		DENSITY (lb/gal)	PRESS (psi)	STG TOT (bbls)	TOTAL (bbls)	REMARKS
	WATER (gpm)	PUMP (bpm)					
10:04	0	0.4	10.17	13	13.3	16.1	PSI TEST
10:06	0	0.2	10.12	13	0.0	16.2	H2O SPACER
10:09	48	0.5	15.96	19	1.3	1.3	END SPACER / START CMT
10:16	0	0.0	14.99	32	13.6	14.9	CMT TO SURFACE / OFF LINE

## Summary

Max Fl. Rate	Avg Fl. Rate	Max Psi	Avg Psi
0.5	1.6	808	40

Customer Acknowledgement:

Service Rating:

- ☐ Satisfactory  
☐ Unsatisfactory

Cementor:

S. BOHLEN

## PRODUCTS USED

CLASS G CMT 1.15 YEILD, 15.8 LBS/GAL