



Service Order #: 73080

Date: 31-Mar-18

Well Name	Location	County	St	API#		
OSMUS C4-24		YUMA	CO	05-125-06593-00		
Formation	Cement Via	Type Of Service	Well Type	Age	AFE#	PO#
	CASING	PLUG		REWORK		

Customer: PRIME OPERATING CO.

Remarks: SAFETY MEETING
165 SKS, 33.8 BBL
ANNLUS 396' - 0'
CASING, 410' - 0'

Customer Rep: TOM

PH:

WELLBORE DATA				
Type	Size	Weight	Depth	Volume
Surface Casing:	7.000	17.0	347.0	
Production Casing:	4.500	9.5	410.0	
Intermediate:				
Drill Pipe:				
Tubing:				

Type	Size	Depth (Top)	Depth (Bot)	Volume
Liner:				
Open Hole:	6.250	347.0	396.0	

OTHER DATA		
BHT	Max PSI	Total Depth

Packer or RetainerType / Depth:

CIBP	410.0
------	-------

Perf Depths:		#	Total
395.0	396.0	0	0
		0	
		0	

TIME	PUMP RATES		DENSITY (lb/gal)	PRESS (psi)	STG TOT (bbls)	TOTAL (bbls)	REMARKS
	WATER (gpm)	PUMP (bpm)					
10:27	0	0.0	6.88	0	25.8	51.9	PSI TEST
10:28	0	0.0	6.88	0	0.0	0.0	H2O SPACER
10:35	47	1.5	15.73	6	7.1	7.1	END SPACER / START CMT
10:51	0	0.0	15.38	107	33.8	40.9	CMT TO SURFACE / OFF LINE

Summary

Max Fl. Rate	Avg Fl. Rate	Max Psi	Avg Psi
1.5	2.2	1,626	29

Customer Acknowledgement:

Service Rating:

- ☐ Satisfactory
☐ Unsatisfactory

Cementer:

S. BOHLEN

PRODUCTS USED

CLASS G CMT, 1.15 YEILD, 15.85 LBS/GAL