



Service Order #: 73081

Date: 31-Mar-18

| Well Name  | Location   | County          | St        | API#            |      |     |
|------------|------------|-----------------|-----------|-----------------|------|-----|
| OSMUS 9-24 |            | YUMA            | CO        | 05-125-07068-00 |      |     |
| Formation  | Cement Via | Type Of Service | Well Type | Age             | AFE# | PO# |
|            | CASING     | PLUG            |           | REWORK          |      |     |

Customer: PRIME OPERATING COMPANY

Remarks: SAFETY MEETING  
140 SKS, 28.7 BBLS  
ANNULUS 501' - 0'  
CASING 510' - 0'

Customer Rep: TOM

PH:

| WELLBORE DATA      |       |        |       |        |
|--------------------|-------|--------|-------|--------|
| Type               | Size  | Weight | Depth | Volume |
| Surface Casing:    | 8.625 | 24.0   | 448.0 |        |
| Production Casing: | 5.500 | 15.5   | 510.0 |        |
| Intermediate:      |       |        |       |        |
| Drill Pipe:        |       |        |       |        |
| Tubing:            |       |        |       |        |

| Type       | Size  | Depth (Top) | Depth (Bot) | Volume |
|------------|-------|-------------|-------------|--------|
| Liner:     |       |             |             |        |
| Open Hole: | 7.875 | 448.0       | 501.0       |        |

| OTHER DATA |         |             |
|------------|---------|-------------|
| BHT        | Max PSI | Total Depth |
|            |         |             |

Packer or RetainerType / Depth:

|      |       |
|------|-------|
| CIBP | 510.0 |
|------|-------|

| Perf Depths: | #     | Total |
|--------------|-------|-------|
| 501.0        | 500.0 | 0     |
|              |       | 0     |
|              |       | 0     |

| TIME  | PUMP RATES  |            | DENSITY  | PRESS | STG TOT | TOTAL  | REMARKS                |
|-------|-------------|------------|----------|-------|---------|--------|------------------------|
|       | WATER (gpm) | PUMP (bpm) | (lb/gal) | (psi) | (bbls)  | (bbls) |                        |
| 11:54 | 189         | 0.0        | 12.71    | 6     | 36.2    | 43.3   | PSI TEST               |
| 11:55 | 182         | 1.5        | 12.75    | 6     | 0.0     | 0.0    | H2O SPACER             |
| 11:59 | 0           | 1.5        | 15.88    | 6     | 6.1     | 6.1    | END SPACER / START CMT |
| 12:16 | 0           | 0.0        | 15.35    | 6     | 28.7    | 34.8   | OFF LINE               |

## Summary

|              |              |         |         |
|--------------|--------------|---------|---------|
| Max Fl. Rate | Avg Fl. Rate | Max Psi | Avg Psi |
| 1.5          | 2.0          | 2,097   | 19      |

Customer Acknowledgement:

Service Rating:

- ☐ Satisfactory  
☐ Unsatisfactory

Cementer:

S. BOHLEN

PRODUCTS USED

CLASS G CMT, 1.15 YEILD, 15.8 LBS/GAL