

FORM
2A

Rev
08/13

State of Colorado
Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203
Phone: (303) 894-2100 Fax: (303) 894-2109



Document Number:

401525931

(SUBMITTED)

Date Received:

Oil and Gas Location Assessment

☒ New Location ☐ Refile ☐ Amend Existing Location Location#: _____

This Oil and Gas Location Assessment is to be submitted to the COGCC for approval prior to any ground disturbance activity associated with oil and gas operations. Approval of this Oil and Gas Location Assessment will allow for the construction of the below specified Location; however, it does not supersede any land use rules applied by the local land use authority. Please see the COGCC website at <http://cogcc.state.co.us/> for all accompanying information pertinent this Oil and Gas Location Assessment.

Location ID:

Expiration Date:

☒ This location assessment is included as part of a permit application.

CONSULTATION

- ☐ This location is included in a Comprehensive Drilling Plan. CDP # _____
- ☐ This location is in a sensitive wildlife habitat area.
- ☐ This location is in a wildlife restricted surface occupancy area.
- ☐ This location includes a Rule 306.d.(1)A.ii. variance request.

Operator

Operator Number: 10459

Name: EXTRACTION OIL & GAS INC

Address: 370 17TH STREET SUITE 5300

City: DENVER State: CO Zip: 80202

Contact Information

Name: Alyssa Andrews

Phone: (720) 481-2379

Fax: ()

email: aandrews@extractionog.com

RECLAMATION FINANCIAL ASSURANCE

☒ Plugging and Abandonment Bond Surety ID: 20130028

☐ Gas Facility Surety ID: _____

☐ Waste Management Surety ID: _____

LOCATION IDENTIFICATION

Name: NORTHWEST B PAD

Number: _____

County: BROOMFIELD

Quarter: NENW Section: 9 Township: 1S Range: 68W Meridian: 6 Ground Elevation: 5298

Define a single point as a location reference for the facility location. When the location is to be used as a well site then the point shall be a well location.

Footage at surface: 1145 feet FNL from North or South section line

1665 feet FWL from East or West section line

Latitude: 39.983547 Longitude: -105.009884

PDOP Reading: 1.3 Date of Measurement: 12/21/2017

Instrument Operator's Name: T. WINNICKI

RELATED REMOTE LOCATIONS

(Enter as many Related Locations as necessary. Enter the Form 2A document # only if there is no established COGCC Location ID#)

This proposed Oil and Gas Location is:

LOCATION ID #

FORM 2A DOC #

FACILITIES

Indicate the number of each type of oil and gas facility planned on location

Wells	8	Oil Tanks*		Condensate Tanks*		Water Tanks*		Buried Produced Water Vaults*	
Drilling Pits		Production Pits*		Special Purpose Pits		Multi-Well Pits*		Modular Large Volume Tanks	
Pump Jacks		Separators*	16	Injection Pumps*		Cavity Pumps*		Gas Compressors*	4
Gas or Diesel Motors*		Electric Motors		Electric Generators*		Fuel Tanks*		LACT Unit*	
Dehydrator Units*		Vapor Recovery Unit*		VOC Combustor*		Flare*		Pigging Station*	

OTHER FACILITIES*

Other Facility Type

Number

AIR COMPRESSOR	1
ELECTRICAL SWITCHRACK	1
EMISSIONS CONTROL DEVICE	1
GAS LIFT METERING BUILDING	2
MAINTENANCE VESSEL	1
OIL SURGE DRUM	1
PIG LAUNCHER	2
PRODUCED WATER SURGE DRUM	1
SALES GAS METER	1
TRANSFORMER	1

Those facilities indicated by an asterisk () shall be used to determine the distance from the Production Facility to the nearest cultural feature on the Cultural Setbacks Tab.

Per Rule 303.b.(3)C, description of all oil, gas, and/or water pipelines:

Extraction will trench flowlines in one piping corridor that runs between the drill pad and the separator pad and be placed at 12" centers. These lines will most likely be 2" or 3" fusion bonded SCH160 steel pipe and have proper cathodic protection throughout the run. Extraction will then sweep up with a long radius that will tie off each line to the appropriate separator. All welds on these are 100% x-ray and hydro tested to the API and Manufactures specs for a class 1500 series flange. Also meets ASME code B31.4.

CONSTRUCTION

Date planned to commence construction: 07/01/2018

Size of disturbed area during construction in acres: 8.76

Estimated date that interim reclamation will begin: 10/01/2018

Size of location after interim reclamation in acres: 4.56

Estimated post-construction ground elevation: 5298

DRILLING PROGRAM

Will a closed loop system be used for drilling fluids: Yes

Is H₂S anticipated? No

Will salt sections be encountered during drilling: No

Will salt based mud (>15,000 ppm Cl) be used? No

Will oil based drilling fluids be used? Yes

DRILLING WASTE MANAGEMENT PROGRAM

Drilling Fluids Disposal: OFFSITE

Drilling Fluids Disposal Method: Commercial Disposal

Cutting Disposal: OFFSITE

Cuttings Disposal Method: Commercial Disposal

Other Disposal Description:

Beneficial reuse or land application plan submitted? _____

Reuse Facility ID: _____ or Document Number: _____

Centralized E&P Waste Management Facility ID, if applicable: _____

SURFACE & MINERALS & RIGHT TO CONSTRUCT

Name: City&County of Broomfield

Phone: _____

Address: One DesCombes Dr.

Fax: _____

Address: _____

Email: _____

City: Broomfield State: CO Zip: 80020

Surface Owner: ☒ Fee ☐ State ☐ Federal ☐ Indian

Check all that apply. The Surface Owner: ☒ is the mineral owner

☒ is committed to an oil and Gas Lease

☒ has signed the Oil and Gas Lease

☐ is the applicant

The Mineral Owner beneath this Oil and Gas Location is: ☒ Fee ☐ State ☐ Federal ☐ Indian

The Minerals beneath this Oil and Gas Location will be developed from or produced to this Oil and Gas Location: No

The right to construct this Oil and Gas Location is granted by: Surface Use Agreement

Surface damage assurance if no agreement is in place: _____ Surface Surety ID: _____

Date of Rule 306 surface owner consultation _____

CURRENT AND FUTURE LAND USE

Current Land Use (Check all that apply):

Crop Land: ☐ Irrigated ☒ Dry land ☐ Improved Pasture ☐ Hay Meadow ☐ CRP

Non-Crop Land: ☐ Rangeland ☐ Timber ☐ Recreational ☐ Other (describe): _____

Subdivided: ☐ Industrial ☐ Commercial ☐ Residential

Future Land Use (Check all that apply):

Crop Land: ☐ Irrigated ☒ Dry land ☐ Improved Pasture ☐ Hay Meadow ☐ CRP

Non-Crop Land: ☐ Rangeland ☐ Timber ☐ Recreational ☐ Other (describe): _____

Subdivided: ☐ Industrial ☐ Commercial ☐ Residential

CULTURAL DISTANCE INFORMATION

Provide the distance to the nearest cultural feature as measured from Wells or Production Facilities onsite.

	From WELL	From PRODUCTION FACILITY
Building:	728 Feet	616 Feet
Building Unit:	1010 Feet	791 Feet
High Occupancy Building Unit:	5280 Feet	5280 Feet
Designated Outside Activity Area:	5280 Feet	5280 Feet
Public Road:	356 Feet	263 Feet
Above Ground Utility:	1106 Feet	1003 Feet
Railroad:	5280 Feet	5280 Feet
Property Line:	116 Feet	12 Feet

INSTRUCTIONS:

- All measurements shall be provided from center of nearest Well or edge of nearest Production Facility to nearest of each cultural feature as described in Rule 303.b.(3)A.
- Enter 5280 for distance greater than 1 mile.
- Building - nearest building of any type. If nearest Building is a Building Unit, enter same distance for both.
- Building Unit, High Occupancy Building Unit, and Designated Outside Activity Area - as defined in 100-Series Rules.
- For measurement purposes only, Production Facilities should only include those items with an asterisk(*) on the Facilities Tab.

DESIGNATED SETBACK LOCATION INFORMATION

Check all that apply. This location is within a:

- ☒ Buffer Zone
- ☐ Exception Zone
- ☐ Urban Mitigation Area

- Buffer Zone - as described in Rule 604.a.(2), within 1,000' of a Building Unit.
- Exception Zone - as described in Rule 604.a.(1), within 500' of a Building Unit.
- Urban Mitigation Area - as defined in 100-Series Rules.
- Large UMA Facility - as defined in 100-Series Rules.

Pre-application Notifications (required if location is within 1,000 feet of a building unit):

Date of Rule 305.a.(1) Urban Mitigation Area Notification to Local Government: _____

Date of Rule 305.a.(2) Buffer Zone Notification to Building Unit Owners: 01/29/2018

FOR MULTI-WELL PADS AND PRODUCTION FACILITIES WITHIN DESIGNATED SETBACK LOCATIONS ONLY:

- ☒ Check this box if this Oil and Gas Location has or will have Production Facilities that serve multiple wells (on or offsite) and the Production Facilities are proposed to be located less than 1,000 feet from a Building Unit. *(Pursuant to Rule 604.c.(2)E.i., the operator must evaluate alternative locations for the Production Facilities that are farther from the Building Unit, and determine whether those alternative locations were technically feasible and economically practicable for the same proposed development.)*
- ☒ By checking this box, I certify that no alternative placements for the Production Facilities, farther from the nearest Building Unit, were available based on the analysis conducted pursuant to Rule 604.c.(2)E.i.

In the space below, explain rationale for siting the multi-well Production Facility(ies) that supports your Rule 604.c.(2)E.i determination. Attach documentation that supports your determination to this Form 2A.

Please see the siting rationale attached.

SOIL

List all soil map units that occur within the proposed location. attach the National Resource Conservation Service (NRCS) report showing the "Map Unit Description" report listing the soil typical vertical profile. This data is to be used when segregating topsoil.

The required information can be obtained from the NRCS web site at <http://soildatamart.nrcs.usda.org/> or from the COGCC web site GIS Online map page found at <http://colorado.gov/cogcc>. Instructions are provided within the COGCC web site help section.

NRCS Map Unit Name: PIB—Platner loam, 0 to 3 percent slopes

NRCS Map Unit Name: UIC—Ulm loam, 3 to 5 percent slopes

NRCS Map Unit Name: _____

PLANT COMMUNITY:

Complete this section only if any portion of the disturbed area of the location's current land use is on non-crop land.

Are noxious weeds present: Yes ☐ No ☒

Plant species from: ☒ NRCS or, ☐ field observation Date of observation: _____

List individual species: _____

Check all plant communities that exist in the disturbed area.

- ☐ Disturbed Grassland (Cactus, Yucca, Cheatgrass, Rye)
☒ Native Grassland (Bluestem, Grama, Wheatgrass, Buffalograss, Fescue, Oatgrass, Brome)
☐ Shrub Land (Mahogany, Oak, Sage, Serviceberry, Chokecherry)
☐ Plains Riparian (Cottonwood, Willow, Aspen, Maple, Poplar, Russian Olive, Tamarisk)
☐ Mountain Riparian (Cottonwood, Willow, Blue Spruce)
☐ Forest Land (Spruce, Fir, Ponderosa Pine, Lodgepole Pine, Juniper, Pinyon, Aspen)
☐ Wetlands Aquatic (Bullrush, Sedge, Cattail, Arrowhead)
☐ Alpine (above timberline)
☐ Other (describe): _____

WATER RESOURCES

Is this a sensitive area: ☒ No ☐ Yes

Distance to nearest

downgradient surface water feature: 27 Feet

water well: 925 Feet

Estimated depth to ground water at Oil and Gas Location 90 Feet

Basis for depth to groundwater and sensitive area determination:

Surface water feature: Ditch 27' NW
Nearest water well: Permit # 90995- - , 925' SW
Depth to ground water: 90' provided by water well with permit # 90995- -

Is the location in a riparian area: ☒ No ☐ Yes

Was an Army Corps of Engineers Section 404 permit filed ☒ No ☐ Yes If yes attach permit.

Is the location within a Rule 317B Surface Water Supply Area buffer zone: No

If the location is within a Rule 317B Surface Water Supply Area buffer have all public water supply systems within 15 miles been notified: _____

Is the Location within a Floodplain? ☒ No ☐ Yes Floodplain Data Sources Reviewed (check all that apply)

☐ Federal (FEMA)

☒ State

☐ County

☐ Local

☐ Other _____

GROUNDWATER BASELINE SAMPLING AND MONITORING AND WATER WELL SAMPLING

Water well sampling required per Rule 318A

WILDLIFE

☐

This location is included in a Wildlife Mitigation Plan

☐ This location was subject to a pre-consultation meeting with CPW held on _____

Operator Proposed Wildlife BMPs

No BMP

DESIGNATED SETBACK LOCATION EXCEPTIONS

Check all that apply:

- ☐ Rule 604.a.(1)A. Exception Zone (within 500' of a Building Unit) and is in an Urban Mitigation Area
- ☐ Rule 604.b.(1)A. Exception Location (existing or approved Oil & Gas Location now within a Designated Setback as a result of Rule 604.a.)
- ☐ Rule 604.b.(1)B. Exception Location (existing or approved Oil & Gas Location is within a Designated Setback due to Building Unit construction after Location approval)
- ☐ Rule 604.b.(2) Exception Location (SUA or site-specific development plan executed on or before August 1, 2013)
- ☐ Rule 604.b.(3) Exception Location (Building Units constructed after August 1, 2013 within setback per an SUA or site-specific development plan)

RULE 502.b VARIANCE REQUEST

☐ Rule 502.b. Variance Request from COGCC Rule or Spacing Order Number _____

ALL exceptions and variances require attached Request Letter(s). Refer to applicable rule for additional required attachments (e.g. waivers, certifications, SUAs).

OPERATOR COMMENTS AND SUBMITTAL

Comments Reference well for Location Identification: Northwest B S16-20-1C

Notification Zone Drawing and UMA Check Exhibit both attached as "OTHER". This location is within a buffer zone. This location is not within a Large UMA.

I hereby certify that the statements made in this form are, to the best of my knowledge, true, correct and complete.

Signed: _____ Date: _____ Email: aandrews@extractionog.com

Print Name: Alyssa Andrews Title: Regulatory Analyst

Based on the information provided herein, this Application for Permit-to-Drill complies with COGCC Rules and applicable orders and is hereby approved.

COGCC Approved: _____ Director of COGCC Date: _____

Conditions Of Approval

All representations, stipulations and conditions of approval stated in this Form 2A for this location shall constitute representations, stipulations and conditions of approval for any and all subsequent operations on the location unless this Form 2A is modified by Sundry Notice, Form 4 or an Amended Form 2A.

COA Type

Description

--	--

Best Management Practices

No BMP/COA Type

Description

1	Planning	Fencing: No fencing is planned for this location.
---	----------	---------------------------------------------------

2	Planning	The location was approved by an Oil and Gas Operator Agreement with Broomfield on October 24, 2017. The development of this location is subject to a Comprehensive Development Plan (CDP) approval from The City and County of Broomfield. Operator is currently working through the CDP application with the City and County of Broomfield staff.
3	Planning	Backup stabbing valves will be required on well servicing operations during reverse circulation. Valves shall be pressure tested before each well servicing operation using both low-pressure air and high-pressure fluid.
4	Planning	All ground within twenty-five (25) feet of any tank, or other structure containing flammable or combustible materials, shall be kept free of dry weeds, grass or rubbish, and shall conform to COGCC 600 Series Safety Regulations and the applicable Fire Code.
5	Planning	Extraction maintains a Tactical Response Plan (TRP), also at times referred to as the Emergency Response Plan, which is designed to provide Extraction employees and designated Emergency Response Team (ERT) members with the information necessary to respond to incidents in a safe, rapid, effective, and efficient manner. The TRP is kept at Extraction's office and a copy is provided to the North Metro Fire Rescue District and the City of Broomfield. Extraction will place the TRP summary card in strategic places on the facilities during specific operational and copies of the summary card is provided to the North Metro Fire Rescue District to be kept in the responding fire engines.
6	Community Outreach and Notification	<p>Extraction will establish a live, 24-hour telephone hotline, as well as an email address, to receive feedback on our drilling and completion activities with the goal of having a tool for us to immediately investigate and address any complaints that arise.</p> <p>Prior to the initiation of 24-hour operations (drilling) Extraction will mail a post card (to include the email address and 24 hour manned phone number) to residents within 1/2 mile of the location.</p>
7	Traffic control	Access Roads: The access road will be constructed to accommodate local emergency vehicles. This road will be maintained for access at all times. Traffic will be routed to minimize local interruption. During construction and through the life of this location, Operator will utilize watering, via water trucks, to control fugitive dust. Additionally, the access road will be constructed with aggregate road base material and recycled asphalt and vehicle speeds will be limited to twenty five miles per hour to reduce dust.
8	Traffic control	A traffic plan is required by the City and County of Broomfield and shall be coordinated with the local jurisdiction prior to commencement of move in and rig up. Any subsequent modification to the traffic plan must be coordinated with the local jurisdiction.
9	General Housekeeping	Maintain appearance with garbage clean-up; a trash bin will be located on site to accumulate waste by the personnel drilling the wells. Site will have unused equipment, trash and junk removed immediately and legally disposed of as applicable.
10	Storm Water/Erosion Control	<p>Implement and maintain BMPs to control stormwater runoff in a manner that minimizes erosion, transport of sediment offsite, and site degradation. Co-locate flowlines and/or gathering lines whenever feasible, and mitigate any erosion problems that arise due to the construction of any gathering lines. Location will be covered under Extraction Oil & Gas's field wide permit, permit number COR03M013.</p> <p>Typical stormwater BMPs installed include a diversion ditch and berm with sediment traps and installation of wattles where necessary.</p> <p>Please see the attached Stormwater and Management Plan.</p>
11	Dust control	805.c. Operator shall employ practices for control of fugitive dust caused by their operations. Such practices shall include but are not limited to the use of speed restrictions, regular road maintenance, restriction of construction activity during high-wind days, and silica dust controls when handling sand used in hydraulic fracturing operations. Additional management practices such as road surfacing, wind breaks and barriers may be used.

12	Construction	<p>803. Permanent lighting will be installed around the facility to allow both the operator and haulers to conduct safe operations at night. All lights will be directed downward, inward and shielded so light pollution is minimized.</p> <p>During the Drilling and Completion Phases, consistent with applicable law, Operator will construct a 32 foot perimeter wall surrounding the well pads and operations area, as permitted, to reduce light escaping from the site.</p>
13	Construction	Base beams will be used and not guy line anchors.
14	Construction	<p>Containment Berms. The Operator shall utilize steel-rim berms around all permanent facility equipment at the Well Sites with sufficient capacity to contain 1.5 times the maximum volume of all liquids that will be contained at a facility at any given time plus sufficient freeboard to prevent overflow. All berms and containment devices shall be inspected quarterly by the Operator and maintained in good condition. No potential ignition sources shall be installed inside the secondary containment area unless the containment area encloses a fired vessel or such sources are rated in accordance with industry codes and standards. Secondary containment such as duck ponds or lined earthen berms for temporary tanks shall also be used.</p> <p>A. Permanent containment berms shall be constructed of steel rings, designed and installed to prevent leakage and resist degradation from erosion or routine operation.</p> <p>B. Secondary containment for tanks shall be constructed with a synthetic or engineered liner that contains all primary containment vessels and is mechanically connected to the steel ring to prevent leakage.</p>
15	Noise mitigation	Quiet Technology. The Operator agrees to use the Liberty Quiet Fleet or comparable technology from an alternative vendor on all Well Sites.
16	Noise mitigation	Thirty-two foot sound walls will be used during drilling and completion operations. Sound walls will be installed on the edges impacting nearest neighbors. Sound walls will be placed on the southwest, south, and southeast edges of the pad.
17	Noise mitigation	<p>Baseline noise monitoring will be conducted prior to commencement of pad construction. Additional sound mitigation measures will be considered and implemented pursuant to third party recommendations. All noise survey data will be made available to the COGCC inspector upon request.</p> <p>The Operator shall continuously monitor noise and continuously collect and store noise readings with instruments placed between the Oil and Gas Location and residential Building Units. The Operator shall conduct the monitoring and data collection during construction, drilling, and completions operations. This data shall be available to COGCC on tables or graphs within 48 hours of being requested by COGCC. The Operator shall conduct a 72 hour baseline noise survey from a minimum of three points prior to the commencement of construction.</p>
18	Noise mitigation	For the development wells, to provide long term noise mitigation at this location all production equipment will powered by electricity. If needed, sound mitigation panels will be installed around the compressors during production operations to shield sensitive areas.
19	Noise mitigation	Electrified Drilling Rig - Extraction is working with United Power to supply sufficient electrical power for the drilling rig to drill the wells. Easements are being procured from the Landowners and the existing infrastructure is being upgraded in order to handle the larger electrical loads. While Extraction plans on drilling these wells on electrical power only, the rig will have diesel-powered generators in the event of an upset condition with the electrical supply from United Power. At that point, Extraction would use the diesel generators to power the rig until service from United Power was restored.
20	Emissions mitigation	Operator will bring a new oil, gas, and water pipelines, in a timely manner, to send produced volumes immediately down the pipeline.

21	Emissions mitigation	This location is designed without permanent tanks. Oil, Gas, and produced water will be transported through a pipeline gathering to a Central Gathering Facility. Saleable gas will not be flared, it will be sent downline. For maintenance or upset conditions the use of a maintenance vessel and emission control devices will be utilized.
22	Emissions mitigation	Green Completions - Emission Control System. Test separators and associated flow lines and sand traps shall be installed on-site to accommodate green completions techniques pursuant to COGCC Rules.
23	Emissions mitigation	Leak Detention Plan: Operator will monitor production facilities weekly at a minimum to a maximum of daily to identify fluid leaks, including, but not limited to, visually inspecting all wellheads and equipment. As part of Extraction's Leak Detection and Repair (LDAR) program, all equipment including above ground flowlines and piping will be inspected quarterly with an infra-red camera for the first 5 years of production.
24	Odor mitigation	805. Oil & gas facilities and equipment shall be operated in such a manner that odors do not constitute a nuisance or hazard to public welfare. Extraction will use a mud cooling system to control the release of odors within the drilling and fracturing fluids. Odor preventing additives will be on site for use if and when needed. Extraction will use a base fluid that will decrease the measurable BTEX and aromatic properties by more than 50% of regular diesel. Operator is prohibited from masking odors from any oil and gas facility site by using masking fragrances.
25	Drilling/Completion Operations	Blowout Prevention Equipment ("BOPE"): A double ram and annular preventer will be used during drilling. Stabbing valves shall be installed in the event of reverse circulation and shall be prior tested with low and high pressure fluid.
26	Drilling/Completion Operations	Leak Detention Plan: Extraction will monitor production facilities weekly at a minimum to a maximum of daily to identify fluid leaks, including, but not limited to, visually inspecting all wellheads, tanks and fittings. Additionally annual SPCC inspections will be conducted and documented. Annual flowline testing will also occur according to COGCC rules 1101 and 1102. Inspection and record retention of flowline testing will be in accordance per COGCC regulation. All records will be made available to the COGCC upon request.
27	Drilling/Completion Operations	All fresh water for completions shall be transported to the well site via temporary water lines.
28	Drilling/Completion Operations	BOPE testing for drilling operations. Upon initial rig-up and at least once every thirty (30) days during drilling operations thereafter, pressure testing of the casing string and each component of the blowout prevention equipment including flange connections shall be performed to seventy percent (70%) of working pressure or seventy percent (70%) of the internal yield of casing, whichever is less. Pressure testing shall be conducted and the documented results shall be retained by the operator for inspection by the Director for a period of one (1) year. Activation of the pipe rams for function testing shall be conducted on a daily basis when practicable.
29	Drilling/Completion Operations	Closed chamber drill stem tests shall be allowed. All other drill stem tests shall require approval by the Director. None planned for this well.
30	Drilling/Completion Operations	All loadlines shall be bull plugged or capped.
31	Drilling/Completion Operations	Closed-Loop Pitless Systems for the Containment and/or Recycling of Drilling Fluids. Wells shall be drilled, completed and operated using closed-loop pitless systems for containment and/or recycling of all drilling, completion, flowback and produced fluids. Operator shall recycle fluids to the maximum extent practicable.
32	Interim Reclamation	Operator shall be responsible for segregating the topsoil, backfilling, re-compacting, reseeding, and re-contouring the surface of any disturbed area so as not to interfere with Owner's operations and shall reclaim such area to be returned to pre-existing conditions as best as possible with control of all noxious weeds.
33	Final Reclamation	Within 90 days subsequent to the time of plugging and abandonment of the entire site, superfluous debris and equipment shall be removed from the site. Identification of plugged and abandoned wells will be identified pursuant to 319.a.(5)
34	Final Reclamation	The operator shall identify the location of the wellbore with a permanent monument as specified in Rule 319.a.(5). The operator shall also inscribe or imbed the well number and date of plugging upon the permanent monument

Total: 34 comment(s)

Attachment Check List

<u>Att Doc Num</u>	<u>Name</u>
401526656	SITING RATIONALE
401526658	ACCESS ROAD MAP
401526660	FACILITY LAYOUT DRAWING
401526671	HYDROLOGY MAP
401526672	LOCATION DRAWING
401526673	LOCATION PICTURES
401526675	MULTI-WELL PLAN
401526683	NRCS MAP UNIT DESC
401526684	NRCS MAP UNIT DESC
401526685	SURFACE AGRMT/SURETY
401543292	OTHER
401543294	OTHER
401555283	PRE-APPLICATION NOTIFICATION CERTIFICATION
401562836	OTHER
401573026	WASTE MANAGEMENT PLAN
401600699	PRE-APPLICATION NOTIFICATION CERTIFICATION

Total Attach: 16 Files

General Comments

<u>User Group</u>	<u>Comment</u>	<u>Comment Date</u>
		Stamp Upon Approval

Total: 0 comment(s)

Public Comments

No public comments were received on this application during the comment period.

