



Service Order #: 75321C

Date: 14-Apr-18

Well Name	Location	County	St	API#		
PERKINS 32-22		WELD	CO	05-123-22034		
Formation	Cement Via	Type Of Service	Well Type	Age	AFE#	PO#
	TUBING	PLUG	GAS	REWORK		

Customer: BONANZA CREEK

Remarks: \*CIBP @ 6285\*  
Cement Pumped: 5.1 bbls / 25 sks  
\*Plug Coverage: 6285 - 5956\*

Customer Rep: KURT DODGE PH:

WELLBORE DATA				
Type	Size	Weight	Depth	Volume
Surface Casing:				
Production Casing:	4.500	11.6	6,285.0	
Intermediate:				
Drill Pipe:				
Tubing:	2.375	4.7	6,285.0	

  

Type	Size	Depth (Top)	Depth (Bot)	Volume
Liner:				
Open Hole:				

OTHER DATA		
BHT	Max PSI	Total Depth
	2,000	6,285.0

Packer or RetainerType / Depth:

Perf Depths:	#	Total

TIME	PUMP RATES		DENSITY (lb/gl)	PRESS (psi)	STG TOT (bbls)	TOTAL (bbls)	REMARKS
	WATER (gpm)	PUMP (bpm)					
15:08	0	0.1	6.88	3,720		0.1	PSI TEST LINES
15:10	0	0.0	6.88	0		0.0	ESTABLISH CIRCULATION
15:12	0	0.0	6.88	0		2.8	SHUT DOWN - CIRCULATION ESTABLISHED
15:13	0	0.0	6.89	37		0.0	BEGIN BATCHING UP CEMENT TO 15.8 PPG
15:17	0	0.3	15.49	123		0.0	PUMP CEMENT
15:21	0	2.0	15.90	78		6.0	END CEMENT - DISPLACE CEMENT WITH H2O
15:33	0	1.9	6.88	330		22.5	SHUT DOWN - END JOB

Summary

Max Fl. Rate	Avg Fl. Rate	Max Psi	Avg Psi
2.0	1.3	3,720	104

Customer Acknowledgement:

Service Rating:

- Satisfactory
- Unsatisfactory

Cementer:

CORY THAUT

PRODUCTS USED

Cement: Cass G (neat)  
#Density: 15.8 ppg / Yield: 1.15