

Attachment #1 – Current Wellbore Diagram

Crestone Peak Resources

Well : Bangert 33-19
Field : Wattenberg
County : Weld **State** : Colorado
Surface : Lat: 40.121926 Long: -104.817693
: 2143' FSL, 1950' FEL, NWSE Sec 19-T2N-R66W
API # : 05-123-20852
Grd Elev : 4862' GL 4878' KB

Log Tops:

Sussex 4376'
Niobrara 7095'
Codell 7387'
J-Sand 7826'

Well History:

Spud 04/29/2002
TD 05/04/2002
Completion 05/22/2002

8-5/8" 24# Surface Casing
set @ 777', cmt'd w/ 315 sx
to surface

DV Tool @ 5525'
Cmt w/ 350 sx
TOC 4216'

2-3/8" tbg landed @ 7825'

J Sand Perfs

7835'-7875', 68 holes
Frac'd with 550,340# sand,
199,332 gal frac fluid

4-1/2" 11.6# production casing set @
8001'. Cmt w/ 230 sx, TOC 6000'

PB TD 7983' MD
TD 8001' MD

Drawn by:
Cole Carveth

Date:
04/26/2018

Crestone Peak Resources			
Well	: Bangert 33-19		
Field	: Wattenberg		
County	: Weld	State :	Colorado
Surface	: Lat: 40.121926	Long:	-104.817693
	: 2143' FSL, 1950' FEL, NWSE Sec 19-T2N-R66W		
API #	: 05-123-20852		
Grd Elev	: 4862' GL 4878' KB		
<div>Log Tops:</div> <div>Sussex 4376'</div> <div>Niobrara 7095'</div> <div>Codell 7387'</div> <div>J-Sand 7826'</div>			
		<div>Well History:</div> <div>Spud 04/29/2002</div> <div>TD 05/04/2002</div> <div>Completion 05/22/2002</div>	
<div>8-5/8" 24# Surface Casing set @ 777', cmt'd w/ 315 sx to surface</div>		<div>CIBP set @ 80' w/ 20 sx cement to surface</div> <div>50 sx balanced plug ~655' - 830'</div> <div>75 sx balanced plug 1,742' – 2,000' 4-½" casing cut at 2,000'</div> <div>DV Tool @ 5525' Cmt w/ 350 sx TOC 4216'</div> <div>105 sx balanced plug ~4240'-5575'</div> <div>CIBP set @ 7025' w/ 2 sx cement</div> <div>CIBP set @ 7775' w/ 2 sx cement</div> <div>J Sand Perfs 7835'-7875', 68 holes Frac'd with 550,340# sand, 199,332 gal frac fluid</div> <div>4-½" 11.6# production casing set @ 8001'. Cmt w/ 230 sx, TOC 6000'</div> <div>PB TD 7983' MD TD 8001' MD</div>	
Drawn by:	Date:		
Cole Carveth	04/26/2018		