
Main Pipes
Recorded With 2 Microphones Through Focusrite Preamps
Recorded At 24bit/96kHz Resolution
Recorded Direct To Hard Disk Recording System
Recorded By Nick Pickard
Recorded On The Organ Of
St Andrew's Church, Roker, Sunderland
Recording Engineer: Nick Pickard
Recording Date: 17th March 2007
Recording Time: 10:00 - 13:00
Recording Venue: St Andrew's Church, Roker, Sunderland
Recording Equipment: Focusrite Preamps, Apple Mac G5 Dual 2.5GHz, Logic Pro 7.2.3
Microphone Configuration: 2 Rode NT5 Cardioid Microphones
Microphone Placement: Left & Right Channels Spaced Apart
Microphone Distance: Approx 2 Metres From Front Of Pipework
Recording Method: Direct To Hard Disk Recording
Recording Format: 24bit/96kHz Stereo Interleaved
Recording Software: Logic Pro 7.2.3
Recording Hardware: Apple Mac G5 Dual 2.5GHz
Recording Interface: Focusrite Preamps
Recording Microphones: 2 Rode NT5 Cardioid Microphones
Recording Microphone Configuration: Left & Right Channels Spaced Apart
Recording Microphone Placement: Approx 2 Metres From Front Of Pipework
Recording Microphone Distance: Approx 2 Metres From Front Of Pipework
Recording Microphone Method: Direct To Hard Disk Recording
Recording Microphone Format: 24bit/96kHz Stereo Interleaved
Recording Microphone Software: Logic Pro 7.2.3
Recording Microphone Hardware: Apple Mac G5 Dual 2.5GHz
Recording Microphone Interface: Focusrite Preamps
Recording Microphone

Repeat Pass

Recorded With 0 PSI Surface Induced Pressure

Database File	North Jake trucking ka 42A-24,Hz_R date trucking ka 42A-24_Hz_04-03-16.db
Dataset Pathname	Hz_4800A_fast
Presentation Format	Hz_4800A_fast
Dataset Creation	Tue Apr 03 11:26:50 2018
Charted by	Depth of Hole Scaled 1:240

Sleeve	Offset (ft)	Schematic	Description	Length (ft)	O.D. (in)	Weight (lb)
			1 Titan CHD-1A375-GO 1.375" OD Titan Hybrid Electric Centre Head w/ 0.375" Thread	1.03	1.44	3.00
			1 DSG RAC-2750 04-GO 2.750" OD Radial 4 Arm Centraliser w/ GO Shoe	2.55	2.75	32.00
TEMP	16.33		1 Probe Rads 2750 RBT (FW1535-068) Tuffstop 2.5-4" Radial Centred Bond Tool with Integral Temperature Sub	9.38	2.75	105.00
WVF08 WVF07 WVF06 WVF05 WVF04 WVF03 WVF02 WVF01 WVFCAL WVFJET WVFSET HEADVOL	14.15 14.17 14.19 14.21 14.23 14.25 14.27 14.29 14.31 14.33 13.10 9.85					
CCL92 CCL91	6.42 6.42		1 DSG RAC-2750 04-GO *2.625 2.5-4" Rad 4 Arm Centraliser w/ GO Shoe	2.55	2.75	32.00
GR	1.18		1 Probe GR-CCL-2750 OSB (FW1307-035) *2.625 2.5-4" Rad 4 Arm Centraliser w/ GO Shoe Gamma Ray/CCL Combined	4.51	2.75	65.00
			1 DSG RAC-2750 04-GO *2.625 2.5-4" Rad 4 Arm Centraliser w/ GO Shoe	2.55	2.75	32.00
			GO RH HA375	0.25	1.44	1.00

Dataset Pathname	No_Gr 4side trucking ka 42A-24_Hz_04-03-16.db: Fieldwellrun1/main
Total length	29.16 ft
Total weight	250.00 lb
O.D.	2.75 in

Calibration Report

Calibrated Date	C:\Program\Alan\Alarm\Calibs\FW1307-068 Trucking FY 42A-24TEP_Tri State Trucking FY 42A-24_RBL_04-03-16.clb
Dataset Creation	Tue Apr 03 11:31:29 2018

Gamma Ray Calibration Report

Serial Number	FW1307-068
Tool Model	2750 OSB
Performed	Sun Nov 13 11:44:16 2017
Calibration Value	637.5 GAPI
Background Reading	113.2 cps
Calibrator Reading	1002.4 cps
Sensitivity	0.7007 GAPI/cps

Segmented Cement Bond Log Calibration Report

Serial Number	FW1305-068
Tool Model	2750 RBT
Calibration Casing Diameter	4.500 in
Calibration Depth	13.442 ft

Master Calibration, performed Tue Apr 03 08:49:56 2018

	Raw (v)		Calibrated (mv)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
T	-0.007	0.714	0.000	81.186	111.441	1.562
CHL	0.006	0.701				
C	-0.002	0.709	0.000	81.186	113.162	0.960
SUM						
57	-0.006	0.713	0.000	100.000	138.631	1.151
52	-0.005	0.727	0.000	100.000	136.656	0.630
53	-0.004	0.732	0.000	100.000	135.870	0.524
54	-0.005	0.719	0.000	100.000	138.252	0.524
55	-0.004	0.721	0.000	100.000	137.864	0.562
56	-0.004	0.722	0.000	100.000	137.672	0.562
57	-0.004	0.722	0.000	100.000	137.672	0.562
58	-0.005	0.721	0.000	100.000	137.864	0.709

Internal Reference Calibration, performed (Not Performed)

	Raw (v)		Calibrated (v)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
CAL	0.000	0.000	0.000	0.751	1.000	0.000

Air Zero Calibration, performed Tue Apr 03 09:03:21 2018

	Raw (v)		Calibrated (v)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
T	-0.007		0.000		1.000	0.000
C	-0.001		0.000		1.000	0.000
SUM						
57	-0.009		0.000		1.000	0.000
52	-0.005		0.000		1.000	0.000
53	-0.004		0.000		1.000	0.000
54	-0.005		0.000		1.000	0.000
55	-0.004		0.000		1.000	0.000
56	-0.005		0.000		1.000	0.000
57	-0.004		0.000		1.000	0.000
58	-0.005		0.000		1.000	0.000

Temperature Calibration Report

Serial Number	FW1305-068
Tool Model	2750 RBT
Performed	Sun Nov 13 12:43:57 2017

	Reference	Reading
Low Reference	100.00 degF	105.40 degF
High Reference	350.00 degF	405.87 degF
Gain	0.84	
Offset	7.72	
Delta Spacing	1	

RELIANCE WIRELINE SERVICES

Company TEP Rocky Mountain LLC
Well Tri State Trucking FK-42A-24
Field Parachute
County Garfield
State Colorado