



SRC ENERGY

Operator: SRC Energy
Well Name: Flockhart 12-44
Legal: SESE, Section 12, Township 6N, Range 67W
Location: Weld County, CO
API: 05-123-29054
Surface: 8.625" 24# @ 796' **Hole Size:** 12.25" **TOC:** Surface
Production: 4.5" 11.6# @ 7,421' **Hole Size:** 7.875" **TOC:** 0' (CBL)
Perforations: 6,960' – 7,176' (Niobrara), 7,278' – 7,296' (Codell)
TD: 7,444'

P&A Procedure

1. Conduct pre-job safety meeting and complete daily JSA
2. Blow down well if necessary, circulate hole with treated water
3. Dig out around wellhead and perform bradenhead test
4. MIRU WO unit, ND wellhead, NU BOP, tally all pipe
5. TIH w/ 4-1/2" 11.6# CIBP, set at 6,885'
6. Pressure test casing to 500 psi for 15 minutes
7. Set 28 sx on top of CIBP (cover 400' above Niobrara top)
8. TIH w/ 4-1/2" 11.6# CIBP, set at 4,300'
 - a. Dump bail 2 sx on top of CIBP
9. TIH w/ 4-1/2" 11.6# CIBP, set at 2,000'
 - a. Dump bail 2 sx on top of CIBP
10. TIH to 946' and pump surface plug (0' – 946')
 - a. 72 sx of 15.8# class G neat 1.15 cu./ft. yield cement
 - b. 150' out of surface casing
 - c. Wait 4 hours and tag plug
11. RDMO WO unit
12. Dig up wellhead and cut off 10' below restored ground level, top off if necessary
13. Weld on cap with ID plate, inscribed with well location, and identity
14. Backfill, clean location
15. P&A complete