Schlumberger
Compensated Neutron Porosity - SNP (SWN)
Gamma Ray (GR)
Caliper (CALI)
Bit Size (BS)
Deep Resistivity (RT)
Medium Resistivity (RM)
Shallow Resistivity (RS)
Micro Resistivity (RXO)
Density Correction (DRHO)
Photoelectric Factor (PEF)
Bulk Density (RHOB)
Neutron Porosity (NPHI)
Delta-T Compressional (DT)
Delta-T Shear (DTS)
Stoneley Slowness (DTST)
Mud Weight (MW)
Mud Resistivity (RM)
Mud Filtrate Resistivity (RMF)
Mud Cake Resistivity (RMC)
Mud Temperature (MT)
Bottom Hole Temperature (BHT)
Logging Speed (LS)
Logging Unit Number (LUN)
Logging Engineer's Name (LEN)
Operating Rig Time (ORT)
Date Logged (DL)
Run Number (RUN)
Depth Driller (DD)
Depth Logger (DL)
Bottom Logged Interval (BLI)
Top Logged Interval (TLI)
Casing Driller Size (CDS)
Casing Logger Size (CLS)
Casing Weight (CW)
Casing Grade (CG)
Casing Thickness (CT)
Casing Depth (CD)
Casing Shoe Depth (CSD)
Casing Shoe Size (CSS)
Casing Shoe Weight (CSW)
Casing Shoe Grade (CSG)
Casing Shoe Thickness (CST





12480
12490
12500
12510
12520
12530
12540
12550
12560
12570
12580
12590
12600
12610
12620
12630
12640
12650
12660
12670
12680
12690
12700
12710
12720
12730
12740
12750
12760
12770
12780
12790
12800
12810
12820
12830
12840
12850
12860
12870
12880
12890
12900
12910
12920

#129 MD(12523.00) Inc(90.6) Azm(267.9) TVD(6794.98)
VS(5027.46) NS(-483.12) EW(-5004.32) TEMP(208.5)

#130 MD(12619.00) Inc(90.4) Azm(268.1) TVD(6794.14)
VS(5123.31) NS(-486.47) EW(-5100.25) TEMP(208.5)

#131 MD(12714.00) Inc(90.7) Azm(267.6) TVD(6793.23)
VS(5218.18) NS(-490.03) EW(-5195.18) TEMP(208.5)

#132 MD(12810.00) Inc(90.3) Azm(267.4) TVD(6792.39)
VS(5314.08) NS(-494.22) EW(-5291.09) TEMP(1.2)

#133 MD(12874.00) Inc(90.0) Azm(267.0) TVD(6792.23)
VS(5378.03) NS(-497.35) EW(-5355.01) TEMP(1.2)

Gamma
API
0.0 300.0
300.0 600.0

ROP
0
0.0 500.0
500.0 1000.0