

HALLIBURTON

iCem[®] Service

SRC ENERGY INC-EBUS

Date: Saturday, March 24, 2018

Boomerang 28N-3A-L Production

Job Date: Thursday, February 22, 2018

Sincerely,

Bryce Hinsch

Legal Notice

Warning Disclaimer

Although the information contained in this report is based on sound engineering practices, the copyright owner(s) does (do) not accept any responsibility whatsoever, in negligence or otherwise, for any loss or damage arising from the possession or use of the report whether in terms of correctness or otherwise. The application, therefore, by the user of this report or any part thereof, is solely at the user's own risk.

Limitations of Liability

Except as expressly set forth herein, there are no representations or warranties by Halliburton, express or implied, including implied warranties of merchantability and/or fitness for a particular purpose. In no event will Halliburton or its suppliers be liable for consequential, incidental, special, punitive or exemplary damages (including, without limitation, loss of data, profits, use of hardware, or software). Customer accepts full responsibility for any investment made based on results from the Software. Any interpretations, analyses or modeling of any data, including, but not limited to Customer data, and any recommendation or decisions based upon such interpretations, analyses or modeling are opinions based upon inferences from measurements and empirical relationships and assumptions, which inferences and assumptions are not infallible, and with respect to which professional may differ. Accordingly, Halliburton cannot and does not warrant the accuracy, correctness or completeness of any such interpretation, recommendation, modeling or other products of the Software Product. As such, any interpretation, recommendation or modeling resulting from the Software for the purpose of any drilling, well treatment, production or financial decision will be at the sole risk of Customer. Under no circumstances will Halliburton or its suppliers be liable for any damages.

Table of Contents

1.0	Cementing Job Summary	4
1.1	Executive Summary	4
2.0	Real-Time Job Summary	7
2.1	Job Event Log	7
3.0	Attachments.....	10
3.1	SRC Boomerang 28N-3A-L Production Job Chart	10

1.0 Cementing Job Summary

1.1 Executive Summary

Halliburton appreciates the opportunity to perform the cementing services on the **Boomerang 28N-3A-L** cement **production** casing job. A pre-job safety meeting was held before the job where details of the job were discussed, potential safety hazards were reviewed, and environmental compliance procedures were outlined.

Approximately 48 bbls of cement were returned to surface.

Halliburton maintains a continuous quality improvement process and appreciates any comments or suggestions that you may have. Halliburton again thanks you for the opportunity to perform service work on this well. We hope to be your solutions provider for future projects.

Respectfully,

Halliburton [Fort Lupton]

The Road to Excellence Starts with Safety

Sold To #: 359915	Ship To #: 3843184	Quote #:	Sales Order #: 0904654248
Customer: SRC ENERGY INC-EBUS		Customer Rep: Lovel Young	
Well Name: BOOMERANG		Well #: 28N-3A-L	API/UWI #: 05-123-45998-00
Field: WATTENBERG	City (SAP): GREELEY	County/Parish: WELD	State: COLORADO
Legal Description: SE NW-5-5N-66W-1526FNL-2327FWL			
Contractor: Precision		Rig/Platform Name/Num: Precision 462	
Job BOM: 7523 7523			
Well Type: HORIZONTAL OIL			
Sales Person: HALAMERICA\HB41307		Srvc Supervisor: Steven Markovich	

Job

Formation Name			
Formation Depth (MD)	Top		Bottom
Form Type	BHST		
Job depth MD	17245ft	Job Depth TVD	
Water Depth	Wk Ht Above Floor		
Perforation Depth (MD)	From		To

Well Data

Description	New / Used	Size in	ID in	Weight lbm/ft	Thread	Grade	Top MD ft	Bottom MD ft	Top TVD ft	Bottom TVD ft
Casing		9.625	8.921	36	LTC	J-55	0	1802		1802
Casing		5.5	4.778	20	BTC	P-110	0	17245	0	0
Open Hole Section			8.5				1802	17263	1802	6990

Tools and Accessories

Type	Size in	Qty	Make	Depth ft	Type	Size in	Qty	Make
Guide Shoe	5.5			17245	Top Plug	5.5		HES
Float Shoe	5.5				Bottom Plug	5.5		HES
Float Collar	5.5				SSR plug set	5.5		HES
Insert Float	5.5				Plug Container	5.5		HES
Stage Tool	5.5				Centralizers	5.5		HES

Fluid Data

Stage/Plug #: 1										
Fluid #	Stage Type	Fluid Name	Qty	Qty UoM	Mixing Density lbm/gal	Yield ft3/sack	Mix Fluid Gal	Rate bbl/min	Total Mix Fluid Gal	
1	Tuned Spacer III	Tuned Spacer III	40	bbl	11.5	3.8		6		
35.10 gal/bbl		FRESH WATER								
0.50 gal/bbl		MUSOL A, 330 GAL TOTE - (790828)								
0.50 gal/bbl		DUAL SPACER SURFACTANT B, 5 GAL PAIL (100003665)								

Fluid #	Stage Type	Fluid Name	Qty	Qty UoM	Mixing Density lbm/gal	Yield ft3/sack	Mix Fluid Gal	Rate bbl/min	Total Mix Fluid Gal
2	ElastiCem LEAD	ELASTICEM (TM) SYSTEM	1003	sack	13.2	1.57		6	7.54
7.54 Gal		FRESH WATER							
Fluid #	Stage Type	Fluid Name	Qty	Qty UoM	Mixing Density lbm/gal	Yield ft3/sack	Mix Fluid Gal	Rate bbl/min	Total Mix Fluid Gal
3	NeoCem	NeoCem TM	1312	sack	13.2	2.04		4	9.77
9.77 Gal		FRESH WATER							
Fluid #	Stage Type	Fluid Name	Qty	Qty UoM	Mixing Density lbm/gal	Yield ft3/sack	Mix Fluid Gal	Rate bbl/min	Total Mix Fluid Gal
4	MMCR Displacement	MMCR Displacement	20	bbl	8.34				
0.1250 gal/bbl		MICRO MATRIX CEMENT RETARDER, 5 GAL PAIL (100003781)							
0.50 gal/bbl		CLA-WEB - BULK (101985043)							
Fluid #	Stage Type	Fluid Name	Qty	Qty UoM	Mixing Density lbm/gal	Yield ft3/sack	Mix Fluid Gal	Rate bbl/min	Total Mix Fluid Gal
5	Water	Water	358	bbl	8.33				

Comment Spacer to surface at 290bbls away, cement to surface at 330bbls away bringing 48bbls of cement to surface. Estimated Top of Tail Cement 5620'. Kicked in pumps to shear WSS. WSS sheered at 5374psi and we got flow at the shakers, started to pump 6bbl wet shoe but the pressure maintained. Checked floats and got back 5bbls back. Company mad requested to pump the 5bbls back in and hold and see where the pressure levels out at. While pumping back in we re gained flow at the shaker. After pressure leveled out we checked floats and after 2.5bbls back floats held.

2.0 Real-Time Job Summary

2.1 Job Event Log

Type	Seq. No.	Activity	Graph Label	Date	Time	Source	DS Pump Press <i>(psi)</i>	Comb Pump Rate <i>(bbl/min)</i>	Pump Stg Tot <i>(bbl)</i>	Downhole Density <i>(ppg)</i>	Recirc Density <i>(ppg)</i>	Comments
Event	1	Call Out	Call Out	2/22/2018	02:00:00	USER						Job called out with an on location time of 08:00
Event	2	Pre-Convoy Safety Meeting	Pre-Convoy Safety Meeting	2/22/2018	06:00:00	USER						JSA with HES crew on driving safety and route to rig.
Event	3	Arrive at Location from Service Center	Arrive at Location from Service Center	2/22/2018	07:20:00	USER						Arrived on location, rig still running casing. Rig had 2000' to run.
Event	4	Assessment Of Location Safety Meeting	Assessment Of Location Safety Meeting	2/22/2018	07:30:00	USER						JSA and hazard hunt with HES crew.
Event	5	Rig-Up Equipment	Rig-Up Equipment	2/22/2018	07:40:00	USER						Rigged up HES lines and equipment.
Event	6	Pre-Job Safety Meeting	Pre-Job Safety Meeting	2/22/2018	12:30:00	USER	-42.00	0.00	1.3	0.00	0.00	JSA with HES and rig crew on job safety and procedure
Event	7	Start Job	Start Job	2/22/2018	13:03:56	COM4	-50.00	0.00	19.9	0.00	0.52	TD 17263 TP 17245.81' WSS 17138.68' 5 1/2" 20# Production Casing, 8 1/2" Open Hole, 9 5/8 36# Surface Casing at 1802', TVD 6990'
Event	8	Check Weight	Check weight	2/22/2018	13:07:44	COM4	-41.00	0.00	20.0	0.00	11.65	Weight verified by pressurized scales.
Event	9	Other	Other	2/22/2018	13:09:35	COM4	-42.00	0.00	20.0	0.00	11.58	Fill lines.
Event	10	Test Lines	Test Lines	2/22/2018	13:13:32	COM4	1.00	0.00	1.3	0.00	11.65	Set kick outs to 500psi and check kick outs, kick outs good. Then bring pressure up to 5000psi and hold.

Event	11	Pump Spacer 1	Pump Spacer 1	2/22/2018	13:23:51	COM4	-42.00	0.00	0.0	8.40	10.25	Pump 40bbls of 11.5ppg 3.8yield Tuned Spacer. Pumped at 5bbl/min 290psi. Added 20 gallons of Musol A and Dual Spacer B on the fly.
Event	12	Drop Bottom Plug	Drop Bottom Plug	2/22/2018	13:31:52	USER	335.00	5.00	24.8	11.72	11.54	Plug pre loaded into HES head. Plugs were loaded and dropped in front of company rep.
Event	13	Check Weight	Check weight	2/22/2018	13:37:41	COM4	-14.00	0.70	40.4	11.01	13.22	Weight verified by pressurized scales.
Event	14	Pump Lead Cement	Pump Lead Cement	2/22/2018	13:39:28	COM4	232.00	4.00	1.1	11.98	13.30	Pump 280bbls of 13.2ppg 1.57yield Lead Cement. Pumped at 7bbl/min 600psi.
Event	15	Check Weight	Check weight	2/22/2018	13:57:23	COM4						Weight verified by pressurized scales.
Event	16	Check Weight	Check weight	2/22/2018	14:19:21	COM4						Weight verified by pressurized scales.
Event	17	Pump Tail Cement	Pump Tail Cement	2/22/2018	14:27:57	COM4						Pump 476bbls of 13.2ppg 2.04yield Tail Cement. Pumped at 6bbl/min 630psi.
Event	18	Check Weight	Check weight	2/22/2018	14:30:11	COM4						Weight verified by pressurized scales.
Event	19	Check Weight	Check weight	2/22/2018	14:55:57	COM4						Weight verified by pressurized scales.
Event	20	Shutdown	Shutdown	2/22/2018	15:43:24	COM4						Shutdown and clean pumps and lines
Event	21	Drop Top Plug	Drop Top Plug	2/22/2018	15:54:15	COM4						Plug pre loaded into HES head. Plugs were loaded and dropped in front of company rep.
Event	22	Pump Displacement	Pump Displacement	2/22/2018	15:54:19	COM4						Pump 378bbls of H2O. First 20bbs with MMCR then

													358bbls with clay web and biocide added on the fly. Pumped at 8bbl/mn and slowed rate with pressure increase. Spacer to surface at 290bbls away, cement to surface at 330bbls away bringing 48bbls of cement to surface.
Event	23	Other	Other	2/22/2018	16:59:30	COM4	2668.00	4.00	379.6	8.35	-5.79	Bumped plug at 378bbls, final lift pressure was 2678psi. Brought pressure 1000psi over and held.	
Event	24	Other	Other	2/22/2018	17:00:25	USER	3596.00	0.50	380.7	8.37	-5.80	Kicked in pumps to hear WSS. WSS sheered at 5374psi and we got flow at the shakers, started to pump 6bbl wet shoe but the pressure maintained. Checked floats and got back 5bbls back.	
Event	25	Other	Other	2/22/2018	17:10:44	USER	-22.00	0.20	388.3	8.28	-5.80	Company mad requested to pump the 5bbls back in and hold and see where the pressure levels out at. While pumping back in we re gained flow at the shaker. After pressure leveled out we checked floats and after 2.5bbls back floats held.	
Event	26	End Job	End Job	2/22/2018	17:19:29	COM4						Thank you Steve Markovich and crew.	

3.0 Attachments

3.1 SRC Boomerang 28N-3A-L Production Job Chart

