

HALLIBURTON

iCem[®] Service

PDC ENERGY - EBUS

Date: Thursday, April 19, 2018

Fern 11V-304 Production

Job Date: Monday, March 12, 2018

Sincerely,

Bryce Hinsch

Legal Notice

Disclaimer:

All information in this report is provided subject to the terms and conditions which govern the services provided by Halliburton. Halliburton personnel use their best efforts in gathering information and their best judgment in interpreting it, but any interpretation, research, analysis or recommendation furnished by Halliburton are opinions based upon inferences from measurements and empirical relationships and assumptions, which inferences and empirical relationships and assumptions are not infallible, and with respect to which professionals in the industry may differ. iCem 3D Displacement results are used to understand how fluids intermix during a cement job. Simulation and 3D displacement results are not intended as and should not be used as a replacement for bond logs in determining top of cement. Current 3D model calculations are known to model more volume than the input volume for standard cases due to known calculation improvements required. For rotational cases, the modeled volume will be impacted by the same calculations impacting the standard cases, as well as additional constraints imposed to make the calculation time required operationally feasible. Therefore, until further notice, 3D displacement results should not be used for replacement of a bond log, or used as an identifier of top of cement. HALLIBURTON IS UNABLE TO GUARANTEE THE ACCURACY OF ANY CHART INTERPRETATION, RESEARCH ANALYSIS, OR JOB RECOMMENDATION and any interpretation or recommendation is not for use of or reliance upon by any third party. The customer has full responsibility for any of its decisions which are based on the information provided in this report.

Table of Contents

1.0 Cementing Job Summary 4

 1.1 Executive Summary4

2.0 Real-Time Job Summary 8

 2.1 Job Event Log8

3.0 Attachments..... 11

 3.1 PDC Fern 11V-304 Production Job Chart11

1.0 Cementing Job Summary

1.1 Executive Summary

Halliburton appreciates the opportunity to perform the cementing services on the **Fern 11V-304** cement **production** casing job. A pre-job safety meeting was held before the job where details of the job were discussed, potential safety hazards were reviewed, and environmental compliance procedures were outlined.

No spacer was seen to surface.

Halliburton maintains a continuous quality improvement process and appreciates any comments or suggestions that you may have. Halliburton again thanks you for the opportunity to perform service work on this well. We hope to be your solutions provider for future projects.

Respectfully,

Halliburton [Fort Lupton]

The Road to Excellence Starts with Safety

Sold To #: 304535		Ship To #: 3791976		Quote #:		Sales Order #: 0904699353				
Customer: PDC ENERGY-EBUS				Customer Rep: Chris McMullen						
Well Name: FERN			Well #: 11V-304		API/UWI #: 05-123-44581-00					
Field: WATTENBERG		City (SAP): GREELEY		County/Parish: WELD		State: COLORADO				
Legal Description: NW NW-11-5N-65W-321FNL-688FWL										
Contractor:				Rig/Platform Name/Num: Ensign 152						
Job BOM: 7523 7523										
Well Type: HORIZONTAL OIL										
Sales Person: HALAMERICA\HX38199				Srvc Supervisor: Nicholas Roles						
Job										
Formation Name										
Formation Depth (MD)		Top		Bottom						
Form Type				BHST						
Job depth MD		15135ft		Job Depth TVD						
Water Depth				Wk Ht Above Floor						
Perforation Depth (MD)		From		To						
Well Data										
Description	New / Used	Size in	ID in	Weight lbm/ft	Thread	Grade	Top MD ft	Bottom MD ft	Top TVD ft	Bottom TVD ft
Casing		9.625	8.921	36			0	1668	0	1668
Casing	0	5.5	4.778	20	BUTTRESS	HCP110	0	15135	0	6799
Open Hole Section			8.5				1668	15142	1668	6799
Tools and Accessories										
Type	Size in	Qty	Make	Depth ft		Type	Size in	Qty	Make	
Guide Shoe	5.5			15135		Top Plug	5.5		HES	
Float Shoe	5.5					Bottom Plug	5.5		HES	
Float Collar	5.5					SSR plug set	5.5		HES	
Insert Float	5.5					Plug Container	5.5	1	HES	
Stage Tool	5.5					Centralizers	5.5		HES	
Fluid Data										
Stage/Plug #: 1										
Fluid #	Stage Type	Fluid Name	Qty	Qty UoM	Mixing Density lbm/gal	Yield ft³/sack	Mix Fluid Gal	Rate bbl/min	Total Mix Fluid Gal	
1	Mud Flush III (Powder)	Mud Flush III	50	bbl	8.4			5		
42 gal/bbl		FRESH WATER								

Fluid #	Stage Type	Fluid Name	Qty	Qty UoM	Mixing Density lbm/gal	Yield ft3/sack	Mix Fluid Gal	Rate bbl/min	Total Mix Fluid Gal	
2	CLEANSPACER III	CLEANSPACER III	50	bbl	12	2.27		5		
0 gal/bbl		FRESH WATER								
Fluid #	Stage Type	Fluid Name	Qty	Qty UoM	Mixing Density lbm/gal	Yield ft3/sack	Mix Fluid Gal	Rate bbl/min	Total Mix Fluid Gal	
3	13.2# ElastiCem	ELASTICEM (TM) SYSTEM	1844	sack	13.2	1.57		8	7.52	
7.52 Gal		FRESH WATER								
0.40 %		HALAD(R)-344, 50 LB (100003670)								
0.35 %		HR-5, 50 LB SK (100005050)								
Fluid #	Stage Type	Fluid Name	Qty	Qty UoM	Mixing Density lbm/gal	Yield ft3/sack	Mix Fluid Gal	Rate bbl/min	Total Mix Fluid Gal	
4	MMCR Displacement	MMCR Displacement	30	bbl	8.34			9		
0.25 gal/bbl		MICRO MATRIX CEMENT RETARDER, 5 GAL PAIL (100003781)								
Fluid #	Stage Type	Fluid Name	Qty	Qty UoM	Mixing Density lbm/gal	Yield ft3/sack	Mix Fluid Gal	Rate bbl/min	Total Mix Fluid Gal	
5	Displacement fluid	Fresh Water	327	bbl	8.34			9		
Cement Left In Pipe		Amount	0 ft		Reason			Wet Shoe		
Comment Did not see MF to surface. Est. TOC-2487. Rig held pressure on Back Side for 8hours with cement head attached.										

HALLIBURTON

Rockies, Brighton

Lab Results- Primary

Job Information

Request/Slurry	2459236/3	Rig Name	ENSIGN 152	Date	08/MAR/2018
Submitted By	Bryce Hinsch	Job Type	Production Casing	Bulk Plant	Brighton
Customer	PDC Energy	Location	Weld	Well	Fern 11V-304

Well Information

Casing/Liner Size	5.5 in	Depth MD	15116 ft	BHST	104°C / 220°F
Hole Size	8.5 in	Depth TVD	6802 ft	BHCT	82°C / 180°F
Pressure	4000 psi				

Cement Information - Primary Design

Cement Properties


Slurry Density	13.2	lbm/gal
Slurry Yield	1.57	ft ³ /sack
Water Requirement	7.52	gal/sack

Operation Test Results Request ID 2459236/2

Thickening Time - ON-OFF-ON

10/MAR/2018

Test Temp (degF)	Pressure (psi)	Reached in (min)	30 Bc (hh:mm)	50 Bc (hh:mm)	70 Bc (hh:mm)	100 Bc (hh:mm)	Start Bc	Stirring before stop (mins)	Static Period (min)	Peak reading (BC)
180	4000	70	6:57	7:00	7:05	7:21	6	82	10	11



This report is the property of Halliburton Energy Services and neither it nor any part thereof, nor a copy thereof, is to be published or disclosed without first securing the expressed written approval of Halliburton. It may however be used in the course of regular business operations by any person or concern receiving such report from Halliburton. This report is for information purposes only and the content is limited to the sample described. Halliburton makes no warranties, expressed or implied, as to the accuracy of the contents or results. Any user of this report agrees Halliburton shall not be liable for any loss or damage regardless of cause, including any act or omission of Halliburton, resulting from the use hereof.

iCem® Service

(v. 4.5.139)

Created: Thursday, April 19, 2018

2.0 Real-Time Job Summary

2.1 Job Event Log

Type	Seq. No.	Activity	Graph Label	Date	Time	Source	DH Density (ppg)	Comb Pump Rate (bbl/min)	DS Pump Press (psi)	Pump Stg Tot (bbl)	Comments
Event	1	Call Out	Call Out	3/12/2018	05:00:00	USER					Called out by Service Coordinator for O/L at 0930
Event	2	Depart Yard Safety Meeting	Depart Yard Safety Meeting	3/12/2018	08:15:00	USER					Held meeting with all personnel in convoy to discuss directions and hazards associated with drive, all fit to drive.
Event	3	Depart from Service Center or Other Site	Depart from Service Center or Other Site	3/12/2018	08:30:00	USER					Journey Management prior to departure
Event	4	Arrive at Location from Service Center	Arrive at Location from Service Center	3/12/2018	09:30:00	USER					Upon arrival met with company man to discuss job details and calculations, performed hazard hunt and site assessment.
Event	5	Pre-Rig Up Safety Meeting	Pre-Rig Up Safety Meeting	3/12/2018	09:45:00	USER					Discussed rigging up hazards and procedure according to HMS.
Event	6	Other	Other	3/12/2018	10:15:00	USER					Water test- PH-6, Chlor-0, Temp-85.
Event	7	Safety Meeting - Pre Job	Safety Meeting - Pre Job	3/12/2018	13:00:00	USER	8.36	0.00	0.00	37.30	Held safety meeting with all job associated personnel to discuss job procedure, hazards and stop work authority.
Event	8	Start Job	Start Job	3/12/2018	13:16:13	COM4	8.36	0.00	1.00	37.30	TD-15142', TP-15135' 5.5" 20#, FC-15107', TVD-6799', OH-8.5", SURF-1668' 9.625" 36#, MUD-10.4#
Event	9	Test Lines	Test Lines	3/12/2018	13:18:53	COM4	8.28	0.00	92.00	40.90	Pumped 5bbls fresh water

											to fill lines, closed manifold and performed 500psi k/o function test, proceeded to perform 5th gear stall at 1450psi, continued to bring pressure up to 5000psi. Pressure stabilized and held with no leaks.
Event	10	Pump Spacer 1	Pump Spacer 1	3/12/2018	13:24:58	COM4	8.29	0.60	206.00	0.00	Pumped 50bbbls fresh water with 200lbs Mud Flush III with 5g of D-air at 5bpm 385psi.
Event	11	Pump Spacer 2	Pump Spacer 2	3/12/2018	13:37:12	COM4	8.26	0.00	243.00	50.30	Pumped 50bbbls 12# 2.27y 12.4g/s Clean Spacer at 5bpm 453psi.
Event	12	Pump Lead Cement	Pump Lead Cement	3/12/2018	13:49:11	COM4	11.93	4.80	557.00	44.80	Pumped 1844sks or 516bbbls 13.2# 1.57y 7.52g/s Elasticem at 8bpm 560psi.
Event	13	Check Weight	Check Weight	3/12/2018	13:52:59	COM4	13.33	4.50	585.00	14.90	Weight verified with pressurized mud scales.
Event	14	Check Weight	Check Weight	3/12/2018	14:17:18	COM4	13.20	7.00	330.00	143.40	Weight verified with pressurized mud scales.
Event	15	Check Weight	Check Weight	3/12/2018	14:39:07	COM4	13.23	7.50	323.00	294.90	Weight verified with pressurized mud scales.
Event	16	Drop Top Plug	Drop Top Plug	3/12/2018	15:31:48	COM4	8.23	0.00	5.00	628.80	
Event	17	Pump Displacement	Pump Displacement	3/12/2018	15:31:54	COM4	8.23	0.00	6.00	0.00	Pumped 335bbbls fresh water with 15g MMCR in first 30bbbls, 15g staclear and 5g biocide throughout.
Event	18	Bump Plug	Bump Plug	3/12/2018	16:23:42	COM4	8.26	0.00	2548.00	338.20	Slowed down to 4bpm at 300bbbls away, final circulating pressure- 2060psi, bump pressure- 2550psi Held for 5min test.
Event	19	Pressure Up Well	Pressure Up Well	3/12/2018	16:26:57	USER	8.24	3.90	1975.00	340.20	Pressured up to sheer at

											3686psi, continued to pump 5bbls at 4bpm 1800psi.
Event	20	Check Floats	Check Floats	3/12/2018	16:28:47	USER	8.22	0.00	1439.00	345.10	Released pressure and got 2bbls back to pump. Floats held.
Event	21	End Job	End Job	3/12/2018	16:30:14	COM4	8.28	0.00	2.00	345.10	Did not see MF to surface. Est. TOC-2487. Rig held pressure on Back Side for 8hours with cement head attached.
Event	22	Safety Meeting - Pre Rig-Down	Safety Meeting - Pre Rig-Down	3/12/2018	16:45:00	USER	8.11	4.00	62.00	394.40	All HSE present. Discussed red zone areas and trapped pressure hazards. Watch for suspended loads and rig down procedures, including hand placement, lifting techniques, and swing radius.
Event	23	Pre-Convoy Safety Meeting	Pre-Convoy Safety Meeting	3/12/2018	17:45:00	USER					All HSE present and fit to drive. Aware of directions and hazards.
Event	24	Depart Location for Service Center or Other Site	Depart Location for Service Center or Other Site	3/12/2018	18:00:00	USER					Pre journey managment prior to departure.

3.0 Attachments

3.1 PDC Fern 11V-304 Production Job Chart

