

OFFICE OF STATE OIL INSPECTOR  
SUNDRY NOTICES AND REPORTS OF WELLS  
LOCATED ON PRIVATE LANDS

3 copies ret'd  
12-3-51



(Indicate nature of data by checking below)

- Notice of intention to drill.....
- Notice of intention to change plans.....
- Notice of date for test of water shut-off.....
- Report on result of test of water shut-off.....
- Notice of intention to re-drill or repair well.....
- Notice of intention to clean out well.....
- Statement of shooting.....
- Statement of perforating.....
- Notice to pull or otherwise alter casing.....
- Notice of intention to abandon well.....
- Report of work done on well since previous report.....
- Report of Clean out and Hydrafrac.....**

Following is a ~~(notice of intention to do work)~~ (On land) November 23, 1951  
(report of work done) (patented) described as follows:

<u>Colorado</u>	<u>Larimer</u>	<u>Clark Lake</u>
State	County	Field
<u>1</u>	<u>John M. Galvin</u>	<u>Sec. 15, SE/4, SW/4</u>
(Well No.)	(Lease)	(Sec. and 1/4 Sec.)
		<u>9N</u>
		<u>68W</u>
		(Range) (Meridian)

The well is located 330 ft. (N) of South line and 330 ft. (W) of East line of SW/4, Sec. 15

The elevation above sea level is 5323 ft. (derrick floor)

Details of Plan of Work: (State names of and expected depths to objective sands: Show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work.)

- Sept. 19, 1951 - Christy Cable Tools on location at 6:30 PM 9-19-51.
- Sept. 20, 1951 - 6000' - Old PBD - pulling 2-7/8" OD tubing.
- Sept. 21 - Sept. 25 - Cleaning out from 5970' to 6000'. Swabbing - recovered 15 Bbls. oil - pulling swab from 5900'.
- Sept. 26, 1951 - 6000' - Old PBD - rigging up to run tubing to Hydrafrac.
- Sept. 27, 1951 - Ran 2-7/8" OD tubing with HY tool to Hydrafrac.
- Sept. 28, 1951 - Hydrafrac - loaded hole with 144 Bbls. oil. Broke formation down with 1200#. Pumped in formation at rate of 177 gallons per minute. Mixed 400# Nuogel, 400# Ottawa Sand with 28 Bbls. Kerosene. Followed with 60 Bbls. oil with 20 gallons breaker fluid. Displaced with 34 Bbls. oil Max. Press. 2400#. Min Press. 2100#. Finished at 12:30 PM. Pressure dropped to 0# in 3 Hrs. Total oil 210 Bbls. plus 28 Bbls. Kerosene. Total - 238 Bbls.
- Sept. 29, 1951 - Pull 2-7/8" tubing - bailing and swabbing - running swab to 5906' (continued)

Approved: DEC 4 1951  
*J. B. Burchak*  
State Oil Inspector  
DIRECTOR

Company Amerada Petroleum Corporation  
Address Box 1250 - Casper, Wyoming  
By H. T. Stewart H. T. Stewart  
Title Dist. Supt.

Submit reports of proposed work, for approval, on this form in Duplicate.