
Mine Plans
Recorded with CAD Mapping Technologies Workspace
Mine Plans
Recorded with CAD Mapping Technologies Workspace









RELIANCE
WIRELINE SERVICES

Repeat Pass

Recorded with 0 PSI Surface Induced Pressure

Database File	log_federal.pa 532-26_rst_06-04-18\processed_log_federal.pa 532-26_rst_06-04-18.db
Dataset Pathname	log_federal
Presentation Format	rst_06004_log
Dataset Creation	Tue Jun 05 10:52:46 2018
Charted by	Depth in Feet scaled 1:240

Sensor	Offset (ft)	Schematic	Description	Length (ft)	O.D. (in)	Weight (lb)
			Titan CHD-14375 GO *CCL Sub, Cablehead Electric Cable Head w/ 1" Fishing Neck	1.03	1.44	3.60
			DSS RAC-2750 54 GO *CCL 2.5-in* Roller 6 arm Centralizer w/ GO Ends	2.55	2.75	32.00
TEMP	16.33		Probe Radia-2750-RBT (FW1302-001) *Probe 2.5-in* Radial Cement Bond Tool with Integral Temperature Sub	9.39	2.75	105.00
WHFSE WHFST WHFS6 WHFS5 WHFS4 WHFS3 WHFS2 WHFS1 WVFCAL WVFSHT WHFSHT	14.10 14.10 14.10 14.10 14.10 14.10 14.10 14.10 14.10 14.10 13.10					
			DSS RAC-2750 54 GO *CCL 2.5-in* Roller 6 arm Centralizer w/ GO Ends	2.55	2.75	32.00
CCL32 CCL31	6.42 6.42					
GR	5.18		Probe GR-CCL-2750-SGB (FW1307-030) *Probe 2.5-in* GR, CCL, Combined	4.51	2.75	55.00
			DSS RAC-2750 54 GO *CCL 2.5-in* Roller 6 arm Centralizer w/ GO Ends	2.55	2.75	32.00
			GO BH-14375 *Bull Nose with Re-Entry Pin*	0.25	1.44	1.00

Dataset	processed_log_federal.pa 532-26_rst_06-04-18.db \ BaseMainHuman_2
Total length	22.82 ft
Total weight	244.00 lb
O.D.	2.75 in

Calibration Report

Database File	c:\programdata\reliance\robotability_federal.pa 532-26_rst_06-04-18\processed_log_federal.pa 532-26_rst_06-04-18.db
Dataset Pathname	main 2
Dataset Creation	Tue Jun 05 09:59:52 2018

Gamma Ray Calibration Report

Serial Number:	FW1307-030
Tool Model:	2750 GSB
Performed:	Sun Nov 12 12:44:12 2017
Calibrator Value:	637.0 GAPI
Background Reading:	113.2 cps
Calibrator Reading:	1522.4 cps
Sensitivity:	0.7507 GAPI/cps

Segmented Cement Bond Log Calibration Report

Serial Number:	FW1302-001
Tool Model:	2750 RBT
Calibration Casing Diameter:	4.500 in
Calibration Depth:	10.544 ft

Master Calibration, performed (Derived):

	Raw (v)		Calibrated (mv)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
3'	-0.004	0.820	0.800	81.195	97.627	1.119
5' CAL	-0.004	0.820	0.800	81.195	103.664	0.524
SUM	-0.007	0.782				
S1	-0.003	0.964	0.000	100.000	103.843	0.300
S2	-0.001	0.980	0.000	100.000	111.001	-0.122
S3	-0.000	0.775	0.000	100.000	129.070	0.012
S4	-0.000	0.716	0.000	100.000	139.655	-0.051
S5	0.002	0.721	0.000	100.000	138.678	-0.309
S6	-0.002	0.777	0.000	100.000	128.687	-0.127
S7	-0.003	0.820	0.000	100.000	120.225	0.407
S8	-0.004	0.942	0.000	100.000	105.714	0.409

Internal Reference Calibration, performed (Not Performed):

	Raw (v)		Calibrated (v)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
CAL	0.000	0.000	0.748	0.742	1.000	0.000

Air Zero Calibration, performed Mon Jun 04 16:22:37 2018:

	Raw (v)	Calibrated (v)	Results
	Zero	Zero	Offset
3'	-0.003	0.000	0.001
5'	0.005	0.000	0.001
SUM			
S1	-0.003	0.000	-0.000
S2	0.003	0.000	0.001
S3	-0.003	0.000	0.001
S4	-0.004	0.000	0.001
S5	-0.004	0.000	0.000
S6	-0.004	0.000	0.001
S7	-0.003	0.000	0.000
S8	-0.003	0.000	0.001

Temperature Calibration Report

Serial Number:	FW1302-001
Tool Model:	2750 RBT
Performed:	Sun Nov 12 13:24:59 2017

	Reference	Reading
Low Reference:	100.00 degF	107.47 degF
High Reference:	200.00 degF	404.05 degF
Gain:	0.84	
Offset:	9.42	
Delta Spacing:	4	

RELIANCE
WIRELINE SERVICES

Company	TEP Rocky Mountain LLC
Well	Federal PA 532-26
Field	Parachute
County	Garfield
State	Colorado