

LEGEND:

= 90° SYMBOL

= AS-DRILLED WELLHEAD.

= TOP OF GAS INTERVAL.

= BOTTOM HOLE.

= SECTION CORNERS LOCATED. (NAD 83)

= SECTION CORNERS RE-ESTABLISHED. (Not Set on Ground.) (NAD 83)

T6S, R97W, 6th P.M.

LINE TABLE

LINE	DIRECTION	LENGTH
L1	N89°38'09"W	2640.48'
L2	S89°56'16"W	2528.26'

NOTE:
WELLBORE DATA PROVIDED BY
Caerus Oil & Gas LLC.

Section Corner Details:

- 1917 Brass Cap, 1.0' High, Lat: 39.501243°, Long: 108.196735°
- 1917 Brass Cap, 0.6' High, Steel Post, Lat: 39.501239°, Long: 108.178056°
- 1917 Brass Cap, 2.0' High, Lat: 39.494008°, Long: 108.178056°
- Section Corner Re-Established Using Double Proportion Method, Lat: 39.486764°, Long: 108.178042°
- S 1/4 Cor. Sec. 25, 1920 Brass Cap, 2.0' High, Lat: 39.486778°, Long: 108.168697°
- SW Cor. Sec. 36, 1920 Brass Cap, 0.9' High, Lat: 39.481786°, Long: 108.178033°
- SW Cor. Sec. 35, 1920 Brass Cap, 1.5' High, Lat: 39.481792°, Long: 108.196089°
- Section Corner Re-Established Using Double Proportion Method, Lat: 39.486731°, Long: 108.196739°
- N 1/4 Cor. Sec. 34, W.C., 1917 Brass Cap, 2.2' High, Lat: 39.486769°, Long: 108.206467°
- N 1/4 Cor. Sec. 34, True Position, Lat: 39.486769°, Long: 108.206092°
- NW Cor. Sec. 34, Section Corner Re-Established Using Double Proportion Method, Lat: 39.486753°, Long: 108.215422°

Well Location Data:

- (AS-DRILLED) PUCKETT 24D-26-697, Elev. Graded Ground = 8322.4'
- Top of Gas Interval, Lat: 39.486769°, Long: 108.187389°
- Bottom Hole, Lat: 39.486769°, Long: 108.187389°

Section 26 Bearings:

- S89°54'51"E - 2633.48' (Meas.)
- S89°56'54"E - 2638.99' (Meas.)
- N00°02'37"E - 2634.46' (Meas.)
- S00°02'15"E - 2639.41' (Meas.)
- S00°01'47"E - 1813.28' (Meas.)
- N00°05'12"W - 1807.07' (Meas.)
- S00°04'15"W - 5287.69' (Meas.)

Section 26 Distances:

- 2329'
- 1697'
- 2457'
- 2388'
- 988'
- 1004'

Section 26 Detail:

- See Detail @ Below
- Detail No Scale

Scale: 1" = 1000'

PDOP = 1.3

NAD 83 (SURFACE LOCATION)	NAD 83 (TOP OF GAS INTERVAL)	NAD 83 (BOTTOM HOLE)
LATITUDE = 39°29'41.45" (39.494848)	LATITUDE = 39°29'22.29" (39.489525)	LATITUDE = 39°29'22.12" (39.489478)
LONGITUDE = 108°11'26.61" (108.190724)	LONGITUDE = 108°11'16.92" (108.188035)	LONGITUDE = 108°11'17.80" (108.188279)
NAD 27 (SURFACE LOCATION)	NAD 27 (TOP OF GAS INTERVAL)	NAD 27 (BOTTOM HOLE)
LATITUDE = 39°29'41.53" (39.494871)	LATITUDE = 39°29'22.37" (39.489547)	LATITUDE = 39°29'22.20" (39.489500)
LONGITUDE = 108°11'24.31" (108.190087)	LONGITUDE = 108°11'14.63" (108.187398)	LONGITUDE = 108°11'15.51" (108.187642)
UTM NAD 27 (ZONE 12)	UTM NAD 27 (ZONE 12)	UTM NAD 27 (ZONE 12)
N: 14354486.93 E: 2433184.96	N: 14352571.74 E: 2434004.41	N: 14352552.45 E: 2433936.06

CERTIFICATE

THIS IS TO CERTIFY THAT THE ABOVE PLAT WAS PREPARED AND LOCATION AS SHOWN WAS STAKED ON THE GROUND FROM FIELD NOTES OF ACTUAL SURVEYS MADE BY ME OR UNDER MY SUPERVISION AND THAT THE SAME ARE TRUE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF.

REGISTERED LAND SURVEYOR
REGISTRATION NO. 10180
STATE OF COLORADO

BASIS OF BEARINGS

BEARINGS ARE A BASED ASSUMPTION THAT THE WEST LINE OF SECTION 26 BEARS S°04'15"W. MONUMENTS DESCRIBED HEREON.

BASIS OF ELEVATION

SPOT ELEVATION AT THE NORTHWEST CORNER OF SECTION 30, T5S, R95W, 6th P.M. TAKEN FROM THE FORKED GULCH QUADRANGLE, COLORADO, GARFIELD COUNTY, 7.5 MINUTE SERIES (TOPOGRAPHICAL MAP) PUBLISHED BY THE UNITED STATES DEPARTMENT OF THE INTERIOR, GEOLOGICAL SURVEY. SAID ELEVATION IS MARKED AS BEING 5966 FEET.

UELS, LLC

Corporate Office * 85 South 200 East
Vernal, UT 84078 * (435) 789-1017

Caerus Oil & Gas LLC

(AS-DRILLED) PUCKETT 24D-26-697
SE 1/4 NW 1/4, SECTION 26, T6S, R97W, 6th P.M.
GARFIELD COUNTY, COLORADO

SURVEYED BY	BART HUNTING, C.R.	10-02-17	SCALE
DRAWN BY	T.L.L.	08-21-18	1" = 1000'

AS-DRILLED WELL LOCATION PLAT